

## Publish data to IBM cloud

Team ID	PNT2022TMID20420
Project Name	Industry-specific intelligent fire management system



The screenshot shows a Python script in a text editor and its execution output in a Python 3.6.5 Shell. The script is titled "#Through python coding we are going to access the subscriber" and uses the paho-mqtt library to connect to a broker at broker.mqttdashboard.com. It defines an on\_publish function that prints "Publish the data" and a while loop that publishes random data to the 'lottopic' topic every 10 seconds.


```
#Through python coding we are going to access the subscriber
import paho.mqtt.client as paho
import time
import random

def on_publish(client, userdata, mid):
    print("Publish the data ")

client = paho.Client()
client.on_publish = on_publish
client.connect('broker.mqttdashboard.com', 1883)
client.loop_start()
while True:
    temp = random.randint(1,30)
    (re,mid) = client.publish('lottopic',str(temp),qos=1)
    print(temp)
    time.sleep(10)
```

Python 3.6.5 Shell output:

```
Python 3.6.5 (v3.6.5:f59c0932b4, Mar 28 2018, 17:00:18) [MS
C v.1900 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more informatio
n.
>>>
===== RESTART: E:/IBM/Others/Develop a python script/
publish.py =====
7
Publish the data
19
Publish the data
10
Publish the data
```



The screenshot shows a Python script in a text editor and its execution output in a Python 3.6.5 Shell. The script is titled "subscribe.py" and uses the paho-mqtt library to connect to a broker at broker.mqttdashboard.com. It defines an on\_subscribe function that prints the subscriber ID and a message handler that prints the topic, QoS, and payload. The client subscribes to the 'lottopic' topic and runs a loop\_forever() to receive messages.


```
import paho.mqtt.client as paho
def on_subscribe(client,userdata,mid,grated_qos):
    print("subscriber:" + str(mid)+str(grated_qos))

def on_message(client,userdata,msg):
    print(msg.topic + "" + str(msg.qos) + "" + str(msg.payload))

client = paho.Client()
client.on_subscribe = on_subscribe
client.on_message = on_message
client.connect('broker.mqttdashboard.com', 1883)
client.subscribe('lottopic',qos=1)
client.loop_forever()
```

Python 3.6.5 Shell output:

```
Publish the data
13
Publish the data
3
Publish the data
25
Publish the data
19
Publish the data
2
Publish the data
7
Publish the data
9
Publish the data
```



### Program:

#IBM Watson IOT Platform

#Pip install wiotp-sdk

```
import wiotp.sdk.device
```

```
import time
```

```
import random
```

```
myConfig = {"identity": {
    "orgId": "hj5fmy",
    "typeId": "NodeMCU",
    "deviceId": "12345"},
    "auth": {"token": "12345678"}}
```

```
def myCommandCallback(cmd):
```

```
    print ("Message received from IBM IoT Platform: %s" % cmd.data['command'])
```

```
    m=cmd.data['command']
```

```
client = wiotp.sdk.device.DeviceClient (config=myConfig, logHandlers=None)
```

```
client.connect()
```

```
while True:
```

```
    temp=random.randint(-20,125)
```

```
    hum=random.randint(0,100)
```

```
myData= {'temperature':temp, 'humidity':hum}
client.publishEvent(eventId="status", msgFormat="json", data=myData, qos=0,
onPublish=None)
print("Published data Successfully: %s", myData)
client.commandCallback = myCommandCallback
time.sleep(2)
client.disconnect()
```