

Image Filtering - Spatial Filtering Import required packages for image filtering.

```
In [ ]:
import cv2
import numpy as np
from matplotlib import pyplot as plt

ref = cv2.imread('/content/02d0257a-d21a-43a4-9348-472043df801e____RS_HL
6065.JPG')
plt.imshow(ref),plt.grid(False)

#while learning how to perform spatial filtering,
#you can also note how to apply different python commands.
plt.title('The original image')
plt.xticks([])
plt.yticks([])
plt.show()
```

The original image



There are two key factors in applying a filter on an image in digital processing ;

1. the kernel type

- 2)the padding method

1-Averagingfilter Below you see how to define a very simple averaging kernel and apply it on your images

Below you see how to define a very simple averaging kernel and apply it on your images

```
In [ ]:
#Defining a kernel using numpy.
kernel_5 = np.ones((5,5),np.float32)/25
kernel_3 = np.ones((3,3),np.float32)/9

#Convolve an image with the kernel.
```

```

#-1 means that the center of the kernel is located on the center pixel.
#compare two kernel sizes.
filtered_5 = cv2.filter2D(ref,-1,kernel_5)
filtered_3 = cv2.filter2D(ref,-1,kernel_3)

#plot the results in two subplots.
fig=plt.figure(figsize=(14,14), dpi=80, facecolor='w', edgecolor='k')

plt.subplot(121), plt.imshow(filtered_3), plt.title('3-by-3 filter')
plt.grid(False)
plt.xticks([])
plt.yticks([])

plt.subplot(122), plt.imshow(filtered_5), plt.title('5-by-5 filter')
plt.grid(False)
plt.xticks([])
plt.yticks([])

plt.show()

```



The complete command for performing 2D spatial filter over images in OpenCV is `cv2.filter2D` with the following list of parameters. Some of the parameters are not necessarily used.

```
cv2.filter2D(src,ddepth,kernel[dst[anchor[delta[ borderType]]]])
```

`src`- input image.

`ddepth`-desired depth of the destination image;if it is negative,it will be the same as `src.depth()`;the following combinations of `src.depth()` and `ddepth` are supported:

```
src.depth()==CV_8U,ddepth=-1/CV_16S/CV_32F/CV_64F src.depth()==CV_16U/CV_16S,ddepth=-1/CV_32F/CV_64F
```

`kernel`-convolution kernel,a single-channel floating point matrix;if you want to apply different kernels to different channels,split the image into separate color planes using `split()` and process them individually.

anchor- anchor of the kernel that indicates the relative position of a filtered point within the kernel; the anchor should be within the kernel; default value(-1,-1) means that the anchor is at the kernel center.

delta-optional value added to the filtered pixels before storing them in dst.

border type- pixel extrapolation method(see[borderInterpolate()])

another simple way to apply a simple averaging filter is to use cv2.blur() function. The function can be applied as below:

In []:

```
# you can check the docs for further information.
blurred = cv2.blur(ref, (5,5), -1)

plt.imshow(blurred), plt.grid(False), plt.xticks([]), plt.yticks([]),
plt.show()
```



Out[]:

```
(,
None,
([], ),
([], ),
None)
2-padding
```

As we mentioned earlier, one of the key factors in applying a filter over an image is to understand how to extrapolate the border values of the image while some parts of the kernel are dropped outside of the image border. Various border types, image boundaries, are denoted with '|' *BORDER_REPLICATE*:aaaaa|abcdefgh|hhhhhhh *BORDER_REFLECT*:fedcba|abcdefgh|hgfedcb *BORDER_REFLECT_101*:gfedcb|abcdefgh|gfedcba *BORDER_WRAP*:cdeefgh_abcdefgh_abcdefg **BORDER_CONSTANT*:iiiiii|abcdefgh|iiiiiii with some specified 'i'

```
cv2.copyMakeBorder(src,top,bottom,left,right borderType[dst[value]])
```

src-source image

size(src.cols+left+right,src.rows+top+bottom

borderType-Border type.One of the border type declared above

value-Border valueif border Type==BORDER_CONSTANT

In []:

```
top = 10; bottom = 5; left = 20; right = 5
const = 100
img2 = cv2.copyMakeBorder(ref, top, bottom, left, right,
                           cv2.BORDER_WRAP)
img3 = cv2.copyMakeBorder(ref, top, bottom, left, right,
                           cv2.BORDER_REFLECT)
img4 = cv2.copyMakeBorder(ref, top, bottom, left, right,
                           cv2.BORDER_REPLICATE)
img5 = cv2.copyMakeBorder(ref, top, bottom, left, right,
                           cv2.BORDER_CONSTANT, const)

# Display the images
fig=plt.figure(figsize=(14, 14), dpi= 80, facecolor='w', edgecolor='k')





plt.subplot(221), plt.imshow(img2), plt.grid(False)
plt.xticks([], plt.yticks([]), plt.title('wrap')

plt.subplot(222), plt.imshow(img3), plt.grid(False)
plt.xticks([], plt.yticks([]), plt.title('reflect')

plt.subplot(223), plt.imshow(img4), plt.grid(False)
plt.xticks([], plt.yticks([]), plt.title('replicate')

plt.subplot(224), plt.imshow(img5), plt.grid(False)
plt.xticks([], plt.yticks([]), plt.title('constant')

plt.show()
```



3-User-defined kernels One can apply user-defined kernels just like the way we applied in section 1. For example, consider applying the following kernel (which is a vertical gradient filter) on the image.

In []:

```
# vertical gradient kernel
# define a random kernel
vertical_gd = np.array([[1, 0, -1], [1, 0, -1], [1, 0, -1]])

# apply it.
filter_v = cv2.filter2D(ref[:, :, 2], -1, vertical_gd)

# show in a different colormap.
plt.imshow(filter_v, cmap='gray'), plt.grid(False)
plt.xticks([], plt.yticks([]))
```

Out[]:

```
(([], ),
 ([[], ]))
```



4-Median filtering Median filter is a non-linear filter which is very useful in removing or decreasing the salt-and-pepper noise. The medianBlur function in OpenCV is designed to perform median filtering. cv2.medianBlur(src, ksize[, dst])

src – input 1-, 3-, or 4-channel image; when ksize is 3 or 5, the image depth should be CV_8U, CV_16U, or CV_32F, for larger aperture sizes, it can only be CV_8U.

ksize – aperture linear size; it must be odd and greater than 1, for example: 3, 5, 7 ...

In order to better understand the effect of median filtering, we first add some noise to the image.

In []:

```
s_and_p = np.random.rand(ref.shape[0], ref.shape[1])

# if we consider 5% salt and pepper noise, we'd like to have
# 2.5% salt and 2.5% pepper. thus:
salt = s_and_p > .975
pepper = s_and_p < .025



# in order to add some noise, we should turn off black (pepper) locations
and
# turn on white (white) locations.
channel_2 = np.atleast_1d(ref[:, :, 1])
noisy = np.zeros_like(channel_2)

for i in range(channel_2.shape[0]*channel_2.shape[1]):
    if salt.ravel()[i] == 1:
        noisy.ravel()[i] = 255
    elif pepper.ravel()[i] == 1:
        noisy.ravel()[i] = 0
    else:
        noisy.ravel()[i] = channel_2.ravel()[i]

# apply median filter with size 3
Med = cv2.medianBlur(noisy, 3)

# Display the results
fig=plt.figure(figsize=(14, 14), dpi= 80, facecolor='w', edgecolor='k')
```

```
plt.subplot(121), plt.xticks([]), plt.yticks([])
plt.imshow(noisy, cmap='gray'), plt.grid(False)
plt.subplot(122), plt.xticks([]), plt.yticks([])
plt.imshow(Med, cmap='gray'), plt.grid(False)
plt.show()
```



5- Gaussian filtering There are multiple ways to perform a gaussian filtering over an image:

using `cv2.GaussianBlur()` function, and, using `cv2.sepFilter2D()` after creating two separate horizontal and vertical kernels and applying them. But, first of all, we need to have a noisy image; specifically with gaussian noise added to it. To create such an image we use Numpy to create random gaussian noise and then add it to the image.

In []:

```
#Creating random normal (gaussian) noise with pre-defined mean and std.
# The noisy image should be the size of the reference image.
mean = 0
sigma = 20.0
gauss_noise = np.random.normal(mean, sigma, (ref.shape[0], ref.shape[1]))




# Convert RGB image to Grayscale image using cvtColor()
gray = cv2.cvtColor(ref, cv2.COLOR_BGR2GRAY)

# Add gaussian noise to the image
g_noisy = gray + gauss_noise # Gaussian noisy image

# Showing gray image, noise image, and noisy image
fig=plt.figure(figsize=(14, 14), dpi= 80, facecolor='w', edgecolor='k')
plt.subplot(131), plt.xticks([]), plt.yticks([])
plt.imshow(gray, cmap='gray'), plt.grid(False)
plt.subplot(132), plt.xticks([]), plt.yticks([])
plt.imshow(gauss_noise, cmap='gray'), plt.grid(False)
plt.subplot(133), plt.xticks([]), plt.yticks([])
plt.imshow(g_noisy, cmap='gray'), plt.grid(False)
```

Out []:

(, None)



Now, we use simple `cv2.GaussianBlur()` to reduce gaussian noise in `g_noisy` image created above.

```
cv2.GaussianBlur(src, ksize, sigmaX[, dst[, sigmaY[, borderType]]])
```

`src` – input image; the image can have any number of channels, which are processed independently, but the depth should be `CV_8U`, `CV_16U`, `CV_16S`, `CV_32F` or `CV_64F`.

`ksize` – Gaussian kernel size. `ksize.width` and `ksize.height` can differ but they both must be positive and odd. Or, they can be zero's and then they are computed from `sigma*`.

`sigmaX` – Gaussian kernel standard deviation in X direction.

`sigmaY` – Gaussian kernel standard deviation in Y direction; if `sigmaY` is zero, it is set to be equal to `sigmaX`, if both sigmas are zeros, they are computed from `ksize.width` and `ksize.height`, respectively (see `getGaussianKernel()` for details); to fully control the result regardless of possible future modifications of all this semantics, it is recommended to specify all of `ksize`, `sigmaX`, and `sigmaY`.

`border Type`-pixel extrapolation method


In []:

```
g_filtered = cv2.GaussianBlur(g_noisy, (3, 3), 20, 20)

# Display the result
plt.imshow(g_filtered, cmap='gray'), plt.grid(False)
plt.xticks([]), plt.yticks([])
```

Out[]:

```
(([], ),
 ([], ))
```

In order to use `cv2.sepFilter2D()` function, we should create a gaussian kernel. This is done using `cv2.getGaussianKernel()`. It creates 1-dimensional gaussian coefficients.

```
cv2.getGaussianKernel(ksize, sigma[, ktype])
```

`ksize` – Aperture size. It should be odd and positive.

`sigma` – Gaussian standard deviation. If it is non-positive, it is computed from `ksize` as $\sigma = 0.3((ksize-1)0.5 - 1) + 0.8$.

`ktype` – Type of filter coefficients. It can be `CV_32f` or `CV_64F`.

In []:

```
#Create a single gaussian kernel
g_kernel = cv2.getGaussianKernel(3, 20)
print(g_kernel)

# Apply two separate kernels over the image.
g_filtered_2 = cv2.sepFilter2D(g_noisy, -1, g_kernel, g_kernel)


# Displaying the results.
fig=plt.figure(figsize=(14, 14), dpi= 80, facecolor='w', edgecolor='k')
plt.subplot(121), plt.xticks([], plt.yticks([]), plt.title('first method')
plt.imshow(g_filtered, cmap='gray'), plt.grid(False)
plt.subplot(122), plt.xticks([], plt.yticks([]), plt.title('second
method')
plt.imshow(g_filtered_2, cmap='gray'), plt.grid(False)

[[0.33319442]
 [0.33361117]
 [0.33319442]]
```

Out []:

```
(, None)
```

first method



second method

