

Histogram

```
import cv2
import matplotlib.pyplot as plt
import numpy as np
%matplotlib inline
```

In []:

```
img = cv2.imread('/content/drive/MyDrive/Classroom/Dataset Plant
Disease/Veg-dataset/Veg-dataset/train_set/Pepper,_bell___healthy/1e4bbf82-
e2dd-48b2-b9fc-024c20bcd7b___JR_HL_8172.JPG')
plt.imshow(img,cmap='gray'),plt.grid(False)
plt.xticks([],plt.yticks([]))
```

Out[]:

```
(([], ),
 ([], ))
```



1-Histogram of an image

Image : it is the source image of type unit8 or float32.it should be given in square brackets,ie,"[img]". channels : it is also given in square brackets.It is the index of channel for which we calculate histogram

For example, if input is grayscale image,its value is [0].For color image,you can pass[0],[1]or[2]to calculate histogram of blue,green or red channel respectively.mask : mask image. To find histogram of full image,it is given as "None".But if you want to find histogram of particular region of image, you have to create a mask image for that and give it as mask.(I will show an example later.)histSize : this represents our BIN count.Need to be given in square brackets.For full scale,we pass[256].ranges : this is our RANGE.Normally,it is [0,256].


In []:

```
hist = cv2.calcHist([img],[0],None,[50],[0,256])

#different methods for displaying a histogram
plt.bar(range(50),hist.ravel())
plt.title('Histogram of the airplane image')
plt.xlabel('Gray values')
plt.ylabel('Frequency')
```

Out[]:


```
Text(0, 0.5, 'Frequency')
```



In []:

```
#Another method  
hist,bins = np.histogram(img.ravel(),256,[0,256])  
plt.plot(hist)
```

Out[]:



Let's look at another example.

In []:

```
#Let's read two other images
```

```
high = cv2.imread('/content/0da568cc-9b4d-4c12-b996-35b6f1f41c11__Rut._Bact.S 0951.JPG')
low = cv2.imread('/content/74fa2964-1307-4b24-8361-0145f7f7f371__RS_HL5919.JPG')
```

In []:

```
plt.subplot(121),plt.imshow(high)
plt.grid(False),plt.xticks([]),plt.yticks([])

plt.subplot(122),plt.imshow(low)
plt.grid(False),plt.xticks([]),plt.yticks([])
plt.show()
```



In []:

```
#calculate histogram of both images for the last channel.
#channels can differ from 0 to 2.
hist_high = cv2.calcHist([high], [2],None,[256],[0,256])
hist_low = cv2.calcHist([low],[2],None,[256],[0,256])
```


```
#plot histograms
plt.subplot(122)
plt.plot(hist_high)
```

```
plt.subplot(122)
plt.plot(hist_low)
```

```
plt.show()
```

```
/usr/local/lib/python3.7/dist-packages/ipykernel_launcher.py:10: Matplotlib
DeprecationWarning: Adding an axes using the same arguments as a previous a
xes currently reuses the earlier instance. In a future version, a new inst
ance will always be created and returned. Meanwhile, this warning can be s
uppressed, and the future behavior ensured, by passing a unique label to ea
ch axes instance.
```

```
# Remove the CWD from sys.path while we load stuff.
```



2- Cumulative histogram of an image Calculate cumulative distribution function (CDF) of an image
The cumulative histogram of an image is produced by calculating the cumulative sum of that image's histogram. There is no specific function in OpenCV to obtain the CDF of an image; thus we use the cumsum function in Numpy. You can find more about the function [here](#)

In []:


```
cdf_low = hist_low.cumsum()
cdf_high = hist_high.cumsum()

#plot cumulative histograms
plt.subplot(221),plt.plot(cdf_high),plt.title('cdf of bright image')
plt.subplot(222),plt.plot(hist_high,'k'),plt.title('pdf of bright image')

plt.subplot(223),plt.plot(cdf_low),plt.title('cdf of dark image')
plt.subplot(224),plt.plot(hist_low,'k'),plt.title('pdf of dark image')

#adjust the placement of subplots
plt.subplots_adjust(bottom=2,right=0.8,top=3)

plt.show()
```



3-Histogram manipulation In order to continue image manipulation,first of all,we change the RGB images to to grayscale using `cv2.cvtColor()`

In []:

```
low_gray = cv2.cvtColor(low,cv2.COLOR_BGR2GRAY)
high_gray = cv2.cvtColor(high,cv2.COLOR_BGR2GRAY)
```




In []:

```
#show images and their histograms
```

```
plt.subplot(221),plt.imshow(high_gray,cmap='gray')
plt.grid(False),plt.xticks([],plt.yticks([]))
plt.subplot(223),plt.plot(cv2.calcHist([high_gray],[0],None,[256],[0,256]))

plt.subplot(222),plt.imshow(low_gray,cmap='gray')
plt.grid(False),plt.xticks([],plt.yticks([]))
plt.subplot(224),plt.plot(cv2.calcHist([low_gray],[0],None,[256],[0,256]))

plt.show()
```



3-1 Brightness

In order to change the brightness and contrast of an image, two parameters are often used as and for contrast and brightness, respectively.

In []:

```
#Define a function to easily handle manipulation.
def manip_image(image,alpha,beta):

    new_image = np.zeros(image.shape,image.dtype)

    for y in range(image.shape[0]):
        for x in range(image.shape[1]):
            new_image[y,x]= np.clip(alpha*image[y,x]+beta,0,255)

    return new_image
```

In []:

```
#Test on the image
bright = manip_image(img,1,30)
dark = manip_image(img,1,-30)

#compare the results
plt.figure()
plt.subplot(231),plt.imshow(dark,cmap='gray')
plt.grid(False),plt.xticks([]),plt.yticks([])

plt.subplot(232),plt.imshow(dark,cmap='gray')
plt.grid(False),plt.xticks([]),plt.yticks([])

plt.subplot(233),plt.imshow(dark,cmap='gray')
plt.grid(False),plt.xticks([]),plt.yticks([])


plt.subplot(234)
plt.plot(cv2.calcHist([dark],[0],None,[256],[0,256])),plt.ylim((0,1750))

plt.subplot(235)
```

```
plt.plot(cv2.calcHist([img],[0],None,[256],[0,256]))

plt.subplot(236)
plt.plot(cv2.calcHist([bright],[0],None,[256],[0,256]))
```

Out[]:



You can see the histogram forward and backward shifts. When we increase and decrease brightness, histogram moves to brighter and darker regions, respectively.

In []:

```
#Test on the dark image
l_bright = manip_image(low_gray,1,150)
l_dark = manip_image(low_gray,1,-25)

#Compare the results
plt.figure()
plt.subplot(231),plt.imshow(l_dark,cmap='gray')
plt.grid(False),plt.xticks([]),plt.yticks([])

plt.subplot(232),plt.imshow(l_dark,cmap='gray')#
plt.grid(False),plt.xticks([]),plt.yticks([])

plt.subplot(233),plt.imshow(l_dark,cmap='gray')
plt.grid(False),plt.xticks([]),plt.yticks([])


plt.subplot(234)
plt.plot(cv2.calcHist([l_dark],[0],None,[256],[0,256])),plt.ylim((0,1100))

plt.subplot(235)
plt.plot(cv2.calcHist([low_gray],[0],None,[256],[0,256])),plt.ylim((0,1100))
)

plt.subplot(236)
plt.plot(cv2.calcHist([l_bright],[0],None,[256],[0,256])),plt.ylim((0,1100))
)
```

Out[]:

```
([], (0.0, 1100.0))
```



3-2 Contrast Contrast of an image could be defined in different ways. One simple rule of thumb is to behave contrast as the distance between largest and smallest values in an image. In fact, the more the gray values are distributed a over the 2k-1 range, the more the contrast will be

In []:

```
#Test on the image
increase_contrast = manip_image(img,1.35,0)
decrease_contrast = manip_image(img,0.35,0)

#Compare the results
plt.figure()
plt.subplot(231),plt.imshow(decrease_contrast,cmap='gray')
plt.grid(False),plt.xticks([],plt.yticks([]))

plt.subplot(232),plt.imshow(img,cmap='gray')
plt.grid(False),plt.xticks([],plt.yticks([]))

plt.subplot(233),plt.imshow(increase_contrast,cmap='gray')
plt.grid(False),plt.xticks([],plt.yticks([]))


plt.subplot(234)
plt.bar(range(256),
        cv2.calcHist([decrease_contrast],[0],None,[256],[0,256]).ravel())

plt.subplot(235)
plt.bar(range(256),
        cv2.calcHist([img],[0],None,[256],[0,256]).ravel())

plt.subplot(236)
plt.bar(range(256),
        cv2.calcHist([increase_contrast],[0],None,[256],[0,256]).ravel())
plt.ylim((0,1750))
```

Out[]:

```
(0.0, 1750.0)
```

Histogram equalization One usual method to stretch the intensity values of an image in order to make its histogram similar to the perfect histogram shape is the histogram equalization.
`cv2.equalizeHist(src,dst)` src: the only required argument is the original image to be equalized

In []:

```
img_eq = cv2.equalizeHist(img)

grid = plt.GridSpec(3,4, wspace=0.4, hspace=0.3)

plt.subplot(grid[:2,2])
plt.imshow(img,cmap='gray')
plt.grid(False), plt.xticks([]), plt.yticks([])

plt.subplot(grid[:2,2])
plt.imshow(img,cmap='gray')
plt.grid(False), plt.xticks([]), plt.yticks([])

plt.subplot(grid[:2,2])
plt.imshow(img,cmap='gray')
plt.grid(False), plt.xticks([]), plt.yticks([])

plt.subplot(grid[:2,2])
plt.bar(range(256),
        cv2.calcHist([img],[0],None,[256],[0,256]).ravel())

plt.subplot(grid[:2,2])
plt.bar(range(256),
        cv2.calcHist([img_eq],[0],None,[256],[0,256]).ravel())
```

```
-----
error                                Traceback (most recent call last)
in
----> 1 img_eq = cv2.equalizeHist(img)
      2
      3 grid = plt.GridSpec(3,4, wspace=0.4, hspace=0.3)
      4
      5 plt.subplot(grid[:2,2])
```

```
error: OpenCV(4.6.0) /io/opencv/modules/imgproc/src/histogram.cpp:3440: error: (-215:Assertion failed) _src.type() == CV_8UC1 in function 'equalizeHist'
```

CLAHE(Contrast Limited Adaptive Histogram Equalization) As you can see above, some parts of the image are brighter than the other parts in the equalized image. In order to reduce these artifacts in image enhancement, an adaptive algorithm was developed

In []:

```
clahe = cv2.createCLAHE(clipLimit=2.0, tileGridSize=(16,16))
img_cl = clahe.apply(img)
```

```
grid = plt.GridSpec(3,4,wspace=0.4,hspace=0.3)
```

```
plt.subplot(grid[:2,:2])
plt.imshow(img,cmap='gray')
plt.grid(False),plt.xticks([],plt.yticks([]))
```

```
plt.subplot(grid[:2,:2])
plt.imshow(img,cmap='gray')
plt.grid(False),plt.xticks([],plt.yticks([]))
```

```
plt.subplot(grid[:2,:2])
plt.bar(range(256),
        cv2.calcHist([img],[0],None,[256],[0,256]).ravel())
```

```
plt.subplot(grid[:2,:2])
plt.bar(range(256),
        cv2.calcHist([img],[0],None,[256],[0,256]).ravel())
```

```
-----
error                                     Traceback (most recent call last)
in
    1 clahe = cv2.createCLAHE(clipLimit=2.0, tileGridSize=(16,16))
----> 2 img_cl = clahe.apply(img)
    3
    4 grid = plt.GridSpec(3,4,wspace=0.4,hspace=0.3)
    5
```

```
error: OpenCV(4.6.0) /io/opencv/modules/imgproc/src/clahe.cpp:353: error: (-215:Assertion failed) _src.type() == CV_8UC1 || _src.type() == CV_16UC1 in function 'apply'
```