Assignment -3

Convolutional Neural Networks

Assignment Date	5 October 2022
Student Name	S. Jeyashree
Student Roll Number	9517201906019
Maximum Marks	2 Marks

#Import necessary libraries

from tensorflow.keras.models import Sequential

from tensorflow.keras.layers import Dense

from tensorflow.keras.layers import Convolution2D

from tensorflow.keras.layers import MaxPooling2D

from tensorflow.keras.layers import Flatten

#Image augmentation

from tensorflow.keras.preprocessing.image import ImageDataGenerator

```
train_datagen =
```

ImageDataGenerator(rescale=1./255,shear_range=0.2,zoom_range=0.2,horizontal_flip=True, vertical_flip=True)

test_datagen = ImageDataGenerator(rescale=1./255)

```
In [1]: #Import necessary Libraries
    from tensorflow.keras.models import Sequential
    from tensorflow.keras.layers import Dense
    from tensorflow.keras.layers import Convolution2D
    from tensorflow.keras.layers import MaxPooling2D
    from tensorflow.keras.layers import Flatten
In [2]: #Image augmentation
    from tensorflow.keras.preprocessing.image import ImageDataGenerator
    train_datagen = ImageDataGenerator(rescale=1./255,shear_range=0.2,zoom_range=0.2,horizontal_flip=True,vertical_flip=True)
    test_datagen = ImageDataGenerator(rescale=1./255)
```

#data set

x train =

 $train_datagen.flow_from_directory(r"E:\Flowers\Training",target_size=(128,128),batch_size=32,class_mode="categorical")$

```
x_test =
test_datagen.flow_from_directory(r"E:\Flowers\Testing",target_size=(128,128),batch_size=3
2,class_mode="categorical")
x_train.class_indices
model = Sequential()
 In [2]: #Image augmentation
        from tensorflow.keras.preprocessing.image import ImageDataGenerator
        train_datagen = ImageDataGenerator(rescale=1./255,shear_range=0.2,zoom_range=0.2,horizontal_flip=True,vertical_flip=True)
        test_datagen = ImageDataGenerator(rescale=1./255)
 In [3]: | x_train = train_datagen.flow_from_directory(r"E:\Flowers\Training",target_size=(128,128),batch_size=32,class_mode="categorical")
        x_test = test_datagen.flow_from_directory(r"E:\Flowers\Testing",target_size=(128,128),batch_size=32,class_mode="categorical")
        x_train.class_indices
        Found 3003 images belonging to 5 classes.
        Found 1325 images belonging to 5 classes.
 Out[3]: {'daisy': 0, 'dandelion': 1, 'rose': 2, 'sunflower': 3, 'tulip': 4}
#Add layers
#Convolution layer
model.add(Convolution2D(32,(3,3),input_shape=(128,128,3),activation='relu'))
#Maxpooling layer
model.add(MaxPooling2D(pool_size=(2,2)))
#flatten layer
model.add(Flatten())
#hidden layer
model.add(Dense(units=300,kernel_initializer="random_uniform",activation="relu"))
model.add(Dense(units=200,kernel_initializer="random_uniform",activation="relu"))
model.add(Dense(units=5,kernel_initializer="random_uniform",activation="softmax"))
model.summary()
```

```
In [4]: model = Sequential()
    #Add Layers
    #Convolution Layer
    model.add(Convolution2D(32,(3,3),input_shape=(128,128,3),activation='relu'))
    #Maxpooling Layer
    model.add(MaxPooling2D(pool_size=(2,2)))
    #flatten Layer
    model.add(Flatten())
    #hidden Layer
    model.add(Dense(units=300,kernel_initializer="random_uniform",activation="relu"))
    model.add(Dense(units=200,kernel_initializer="random_uniform",activation="relu"))
    model.add(Dense(units=5,kernel_initializer="random_uniform",activation="softmax"))
    model.summary()
```

Model: "sequential"

Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 126, 126, 32)	896
<pre>max_pooling2d (MaxPooling2D)</pre>	(None, 63, 63, 32)	0
flatten (Flatten)	(None, 127008)	0
dense (Dense)	(None, 300)	38102700
dense_1 (Dense)	(None, 200)	60200
dense_2 (Dense)	(None, 5)	1005

Total params: 38,164,801 Trainable params: 38,164,801 Non-trainable params: 0

#compile the model

model.compile(loss="categorical_crossentropy",optimizer="adam",metrics=["accuracy"])

#Fit the model

model.fit_generator(x_train,steps_per_epoch=75,epochs=15,validation_data=x_test,validation_steps=80)

```
In [6]: #compile the model
        model.compile(loss="categorical_crossentropy",optimizer="adam",metrics=["accuracy"])
        \verb|model.fit_generator(x_train,steps_per_epoch=75,epochs=15,validation_data=x_test,validation\_steps=80)|
        C:\Users\hp\Anaconda3\lib\site-packages\ipykernel_launcher.py:4: UserWarning: `Model.fit_generator` is deprecated and will be removed in a future version. Please use `Model.fit`, which supports generators.
          after removing the cwd from sys.path.
        75/75 [=======] - ETA: 0s - loss: 1.0726 - accuracy: 0.5791WARNING:tensorflow:Your input ran out of dat a; interrupting training. Make sure that your dataset or generator can generate at least `steps_per_epoch * epochs` batches (in this case, 80 batches). You may need to use the repeat() function when building your dataset.

75/75 [===========] - 83s 1s/step - loss: 1.0726 - accuracy: 0.5791 - val_loss: 1.2372 - val_accuracy: 0.504
        Epoch 2/15
        75/75 [===:
Epoch 3/15
                      -----] - 68s 906ms/step - loss: 0.9907 - accuracy: 0.6125
        75/75 [====
Epoch 4/15
                        75/75 [====
Epoch 5/15
                            =======] - 70s 922ms/step - loss: 0.8850 - accuracy: 0.6522
        75/75 [====
Epoch 6/15
                          -----] - 73s 962ms/step - loss: 0.8177 - accuracy: 0.6789
        75/75 [====
Epoch 7/15
                          75/75 [====
Epoch 8/15
                            -----] - 73s 966ms/step - loss: 0.8099 - accuracy: 0.6868
                                Epoch 9/15
                              Epoch 10/15
 75/75 [============ ] - 69s 911ms/step - loss: 0.6867 - accuracy: 0.7446
 Epoch 11/15
 75/75 [============] - 69s 920ms/step - loss: 0.6735 - accuracy: 0.7404
 Epoch 12/15
 75/75 [=========== - 70s 931ms/step - loss: 0.6735 - accuracy: 0.7562
 Epoch 13/15
 75/75 [============== ] - 69s 919ms/step - loss: 0.6310 - accuracy: 0.7595
 Epoch 14/15
 Epoch 15/15
 75/75 [============= - - 75s 988ms/step - loss: 0.6024 - accuracy: 0.7775
#Save the model
model.save("flower.h5")
from tensorflow.keras.models import load_model
from tensorflow.keras.preprocessing import image
```

import numpy as np

model = load_model("Flower.h5")

```
In [7]:
         #Save the model
         model.save("flower.h5")
```

#Test the model:

```
img = image.load_img(r"C:\Users\hp\Downloads\rose.jpg",target_size=(128,128))
```

img

type(img)

```
x = image.img\_to\_array(img)
X
x.shape
x = np.expand\_dims(x,axis=0)
x.shape
pred_prob = model.predict(x)
pred_prob
 In [8]: from tensorflow.keras.models import load_model
          from tensorflow.keras.preprocessing import image
          import numpy as np
          model = load_model("Flower.h5")
In [10]: #Testing with the image
          img = image.load_img(r"C:\Users\hp\Downloads\rose.jpg",target_size=(128,128))
          img
          type(img)
Out[10]: PIL.Image.Image
In [11]: x = image.img_to_array(img)
          x.shape
          x = np.expand_dims(x,axis=0)
          x.shape
Out[11]: (1, 128, 128, 3)
In [12]: pred_prob = model.predict(x)
          pred_prob
Out[12]: array([[0., 0., 1., 0., 0.]], dtype=float32)
class_name = ["daisy","dandelion","rose","sunfower","tulip"]
pred_id = pred_prob.argmax(axis=1)[0]
pred_id
print("Predicted flower is",str(class_name[pred_id]))
```

```
In [13]: class_name = ["daisy","dandelion","rose","sunfower","tulip"]
In [15]: pred_id = pred_prob.argmax(axis=1)[0]
    pred_id
    print("Predicted flower is",str(class_name[pred_id]))
```

Predicted flower is rose