## **IMAGE PREPROCESSING**

## APPLY IMAGE DATAGENERATOR FUNCTIONALITY TO TRAINSET AND TESTSET

DATE	01 NOVEMBER
TEAM ID	PNT2022TMID21338
PROJECT CATEGORY	ARTIFICIAL INTELLIGENCE
PROJECT NAME	AI-POWERED NUTRITION ANALYZER FOR FITNESS
	ENTHUSIASTS

Let us apply ImageDataGenerator functionality to Trainset and Testset by using the following code

For Training set using flow\_from\_directory function.

This function will return batches of images from the subdirectories 'apples', 'banana', 'orange', 'pineapple', 'watermelon' together with labels 0 to 4{'apples': 0, 'banana': 1, 'orange': 2, 'pineapple': 3, 'watermelon': 4}

## Arguments:

- directory: Directory where the data is located. If labels are "inferred", it should contain subdirectories, each containing images for a class. Otherwise, the directory structure is ignored.
- batch\_size: Size of the batches of data. Default: 32.
- target\_size: Size to resize images after they are read from disk.
- class mode:
- 'int': means that the labels are encoded as integers (e.g. for sparse\_categorical\_crossentropy loss).
- 'categorical' means that the labels are encoded as a categorical vector (e.g. for categorical\_crossentropy loss).
- 'binary' means that the labels (there can be only 2) are encoded as float32 scalars with values 0 or 1 (e.g. for binary\_crossentropy).
- None (no labels).

APPLY IMAGE DATAGENERATOR FUNCTIONALITY TO TRAINSET AND TESTSET



Found 2626 images belonging to 5 classes. Found 1055 images belonging to 5 classes.