IOT ENABLED SMART FARMING APPLICATION

SPRINT DELIVERY – 4

TEAM ID : PNT2022TMID08320

5.5 Receiving commands from IBM cloud using Python program

```
import time import
sys
import ibmiotf.application
import ibmiotf.device import
random

#Provide your IBM Watson Device Credentials
organization = "157uf3" deviceType = "abcd"
deviceId = "7654321" authMethod = "token"
authToken = "87654321"

# Initialize GPIO
def myCommandCallback(cmd):     print("Command
received: %s" % cmd.data['command'])
status=cmd.data['command']     if status=="motoron":
print ("motor is on")     elif status == "motoroff":        print
("motor is off")     else :
       print ("please send proper command")

try:
           deviceOptions = {"org": organization, "type": deviceType, "id": deviceId,
"auth-method": authMethod, "auth-token": authToken}
deviceCli = ibmiotf.device.Client(deviceOptions)
          #.....
```

```
except Exception as e:
        print("Caught exception connecting device: %s" % str(e))
sys.exit()
# Connect and send a datapoint "hello" with value "world" into the cloud as an event of type "greeting" 10 times deviceCli.connect()

while True:
      #Get Sensor Data from DHT11
temp=random.randint(90,110)
Humid=random.randint(60,100)
Mois=random. Randint(20,120)
   data = { 'temp' : temp, 'Humid': Humid ,
‘Mois’: Mois}
      #print data        def
myOnPublishCallback():
         print ("Published Temperature = %s C" % temp, "Humidity = %s %%" % Humid, “Moisture =%s deg c” % Mois “to IBM Watson")
        success = deviceCli.publishEvent("IoTSensor", "json", data, qos=0, on_publish=myOnPublishCallback)        if not success:
         print("Not connected to IoTF")
time.sleep(10)
      deviceCli.commandCallback = myCommandCallback #
Disconnect the device and application from the cloud
deviceCli.disconnect()
```


ibmiotpublishsubscribe.py - C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py (3.7.0)
File Edit Format Run Options Window Help
import time
import sys
import ibmiotf.application
import ibmiotf.device
import random
#Provide your IBM Watson Device Credentials
organization = "157uf3"
deviceType = "abcd"
deviceId = "7654321"
authMethod = "token"
authToken = "87654321"
# Initialize GPIO
def myCommandCallback(cmd):
print("Command received: %s" % cmd.data['command'])
status=cmd.data['command']
if status=="motoron":
print ("motor is on")
elif status == "motoroff":
print ("motor is off")
else :
print ("please send proper command")
try:
deviceOptions = {"org": organization, "type": deviceType, "id": deviceId, "auth-method": authMe
deviceCli = ibmiotf.device.Client(deviceOptions)
#.....
Ln: 22 Col: 21
File Explorer
29°C Cloudy
ENG 18:01


Python 3.7.0 Shell
File Edit Shell Debug Options Window Help
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD64)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
======== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py ========
2022-11-07 20:01:24,074 ibmiotf.device.Client INFO Connected successfully: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson
Gmail
Other favorites
Node-RED Dashboard...
Downloads
25°C
ENG 20:02

6. Flow Chart



7. Observations & Results




IBM
Not secure
ai2.appinventor.mit.edu/#4808438841212928
Screen1
SMART FARMING
TEMPERATURE
HUMIDITY
SOIL MOISTURE
MOTOR ON
MOTOR OFF
Non-visible components
Web1 Clock1 Web2
smart farmer 4.jpeg
tractor_field_art_14....jpg
smart farmer 3.jpeg
smart farmer 2.jpeg
Show all


MIT App Inventor
Service Details - IBM Cloud
Node-RED : node-red-hdyfv-20
Node-RED Dashboard
https://node-red-hdyfv-2022-10-01.eu-gb.mybluemix.net/ui/#!/1?socketid=ZgBLuLWNfw0sYpeTAAAZ
Gmail
YouTube
Maps
New Tab
Other favorites
FARMING MEASURE DATA
Farming Measure Data
Temperature
110
108
106
104
102
100
98
96
94
92
90
20:01:33
20:01:53
20:02:13
20:02:33
20:02:53
20:03:13
20:03:34


Humidity
91
%
0
100


Moisture
110
100
90
80
70
60
50
40
30
20
20:01:33
20:02:03
20:02:33
20:03:03
20:03:54
Switchboard
MOTOR SWITCH ON
MOTOR SWITCH OFF
Node-RED Dashboard...
Downloads
ibmiotpublishsubscri...
Python 3.7.0 Shell
Pollut...
ENG
20:03

8. Advantages & Disadvantages Advantages:

- Farms can be monitored and controlled remotely.
- Increase in convenience to farmers.
- Less labor cost.
- Better standards of living.

Disadvantages:

- Lack of internet/connectivity issues.
- Added cost of internet and internet gateway infrastructure.
- Farmers wanted to adapt the use of Mobile App.

9. Conclusion

Thus the objective of the project to implement an IoT system in order to help farmers to control and monitor their farms has been implemented successfully.

10. Bibliography

IBM cloud reference: https://cloud.ibm.com/

IoT simulator : https://watson-iot-sensor-simulator.mybluemix.net/

OpenWeather : https://openweathermap.org/