PROJECT DEVELOPMENT PHASE

SPRINT-3

Date	9 November 2022
Team ID	PNT2022TMID00340
Project Name	Hazardous Area Monitoring for Industrial Plant powered by IoT

CODE:


```
#include "DHT.h"
                                        // Library for dht22
#include <WiFi.h>
                                       //library for wifi
#include <PubSubClient.h>
                                      //library for MQtt
#define DHTPIN 15
                                      // what pin we're connected to
#define DHTTYPE DHT22
                                     // define type of sensor DHT 11
                                    //GAS SENSOR MQ-02
#define GAS_SENSOR 2
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of dht
connected
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
#define ORG "zfcm7n"
                                          //IBM ORGANITION ID
#define DEVICE TYPE "ESP32 Controller"
                                                    //Device type mentioned in
ibm watson IOT Platform
#define DEVICE_ID "ibmA-4"
Platform
#define TOKEN "GRT14P*Zvcm4PBiOft"
String data3;
float h, t;
int val;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";
char subscribetopic[] = "iot-2/cmd/command/fmt/String";
                                                          // cmd REPRESENT
command type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";
                                                          // authentication
method
char token[] = TOKEN;
```


```
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined
client id by passing parameter like server id, portand wificredential
const int DHT_PIN = 15;
void setup()
  Serial.begin(115200);
  Serial.println();
 wificonnect();
 mqttconnect();
void loop()
 val = digitalRead(GAS SENSOR);
 h = dht.readHumidity();
  t = dht.readTemperature();
  Serial.print("Temparature:");
  Serial.println(t);
  Serial.print("Humidity:");
  Serial.println(h);
  Serial.print("Gas Sensor:");
  Serial.println(val);
  PublishData(t, h, val);
  delay(1000);
  if (!client.loop())
   mqttconnect();
  delay(1000);
                     .....retrieving to Cloud */
void PublishData(float temp, float humid, int vol)
  mqttconnect();
  String payload = "{\"Temperature\":";
  payload += temp;
  payload += "," "\"Humidity\":";
  payload += humid;
  payload += ",""\"Gas Sensor\":";
  payload += val;
  payload += "}";
  Serial.print("Sending payload: ");
```

```
Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str()))
   Serial.println("Publish ok");// if it successfully upload data on the cloud then
it will print publish ok in Serial monitor or else it will print publish failed
 else
   Serial.println("Publish failed");
void mqttconnect()
 if (!client.connected())
   Serial.print("Reconnecting client to ");
   Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token))
     Serial.print(".");
     delay(500);
   initManagedDevice();
   Serial.println();
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the
connection
 while (WiFi.status() != WL_CONNECTED)
   delay(500);
   Serial.print(".");
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
void initManagedDevice()
```

```
if (client.subscribe(subscribetopic))
   Serial.println((subscribetopic));
   Serial.println("subscribe to cmd OK");
   Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++)</pre>
    //Serial.print((char)payload[i]);
   data3 += (char)payload[i];
 Serial.println("data: " + data3);
 if (data3 == "lighton")
   Serial.println(data3);
   Serial.println(data3);
 data3 = "";
```

WOKIWI SIMULATION:







Note: The slide switch input is given as dummy to Gas sensor

IBM WATSON PLATFORM -


DEVICE EVENT LOG:



DEVICE EVENT PAYLOAD:




IBM CLOUDANT DB LOG:



NODE-RED APP →

DESIGN FLOW:



WEB UI:

