

Assignment-4

Student Name	M.Sudarvizhi
Register Number	810419106062
Project Name	Real-Time River Water Quality Monitoring and Control System

Question-1:

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events.

Upload document with wokwi share link and images of IBM cloud.

CODE:

```
#include <WiFi.h>
#include <PubSubClient.h>
void callback(char* subscribtopic, byte* payload, unsigned int
payloadLength);
#define ORG "49x4b9"
#define DEVICE_TYPE "esp32"
#define DEVICE_ID "97043"
#define TOKEN "7993276080"
String data3;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/Data/fmt/json";
char subscribtopic[] = "iot-2/cmd/test/fmt/String";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server, 1883, callback ,wifiClient);
const int trigPin = 5;
const int echoPin = 18;
#define SOUND_SPEED 0.034
long duration;
float distance;
void setup() {
  Serial.begin(115200);
  pinMode(trigPin, OUTPUT);
  pinMode(echoPin, INPUT);
  wificonnect();
  mqttconnect();
}
```

```

void loop()
{
  digitalWrite(trigPin, LOW);
  delayMicroseconds(2);
  digitalWrite(trigPin, HIGH);
  delayMicroseconds(10);
  digitalWrite(trigPin, LOW);
  duration = pulseIn(echoPin, HIGH);
  distance = duration * SOUND_SPEED/2;
  Serial.print("Distance (cm): ");
  Serial.println(distance);
  if(distance<100)
  {
    Serial.println("ALERT!!");
    delay(1000);
    PublishData(distance);
    delay(1000);
    if (!client.loop()) {
      mqttconnect();
    }
  }
  delay(1000);
}

void PublishData(float dist) {
  mqttconnect();
  String payload = "{\"Distance\":\"";
  payload += dist;
  payload += "\",\"ALERT!!\":\"\"Distance less than 100cms\"";
  payload += "\"}";
  Serial.print("Sending payload: ");
  Serial.println(payload);
  if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");
  } else {
    Serial.println("Publish failed");
  }
}

void mqttconnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
    while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(500);
    }
    initManagedDevice();
    Serial.println();
  }
}

```


```

}
void wificonnect()
{
  Serial.println();
  Serial.print("Connecting to ");
  WiFi.begin("Wokwi-GUEST", "", 6);
  while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  }
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++)
  {
    data3 += (char)payload[i];
  }
  Serial.println("data: "+ data3);
  data3="";
}

```

Wokwi Link: <https://wokwi.com/projects/347310895770108498>

Output and Simulation :




The screenshot displays the Wokwi IDE interface. On the left, the sketch.ino file contains the following code:

```
1 #include <WiFi.h>
2 #include <PubSubClient.h>
3 void callback(char* topic, byte* payload, unsigned int length) {
4   #define ORG "92zbfc"
5   #define DEVICE_TYPE "esp32"
6   #define DEVICE_ID "12345"
7   #define TOKEN "12345678"
8   String data3;
9   char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
10  char publishTopic[] = "iot-2/evt/Data/fmt/json";
11  char subscribTopic[] = "iot-2/cmd/test/fmt/String";
12  char authMethod[] = "use-token-auth";
13  char token[] = TOKEN;
14  char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
15  WiFiClient wifiClient;
16  PubSubClient client(server, 1883, callback, wifiClient);
17  const int trigPin = 5;
18  const int echoPin = 18;
19  #define SOUND_SPEED 0.034
20  long duration;
21  float distance;
22  void setup() {
23    Serial.begin(115200);
24    pinMode(trigPin, OUTPUT);
25    pinMode(echoPin, INPUT);
26    wificonnect();
27    mqttconnect();
28  }
29  void loop()
30  {
31    digitalWrite(trigPin, LOW);
```

The simulation window on the right shows an Ultrasonic Distance Sensor connected to an ESP32. The distance is 99cm. The console output shows the following messages:

```
100cms"}
Publish ok
Distance (cm): 98.94
ALERT!!
Sending payload: {"Distance":98.94,"ALERT!!":"Distance less than
100cms"}
Publish ok
```

Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events.



The screenshot shows the IBM Watson IoT Platform console. The 'Recent Events' tab is selected for a device with ID 12345. The events list shows three entries with the payload {"Distance": 98.94, "ALERT!!": "Distance less than 100cms"}.

Time	Value	Format	Last Received
Data	{"Distance": 98.94, "ALERT!!": "Distance less than 100cms"}	json	a few seconds ago
Data	{"Distance": 98.94, "ALERT!!": "Distance less than 100cms"}	json	a few seconds ago
Data	{"Distance": 98.94, "ALERT!!": "Distance less than 100cms"}	json	a few seconds ago