```
In [1]:
         import keras
         from keras.preprocessing.image import ImageDataGenerator
         #Define the parameters/arguments for ImageDataGenerator class
In [2]:
         train datagen=ImageDataGenerator(rescale=1./255, shear range=0.2, rotation range=180, zoom range
         test datagen=ImageDataGenerator(rescale=1./255)
         #Applying ImageDataGenerator functionality to trainset
In [3]:
         x train=train datagen.flow from directory(r'C:\Users\dhine\Downloads\archive\Dataset\Dataset\
                                                    target size=(128,128),
                                                    batch size=32,
                                                    class_mode='binary')
         Found 436 images belonging to 2 classes.
         #Applying ImageDataGenerator functionality to testset
In [4]:
         x test=test datagen.flow from directory(r'C:\Users\dhine\Downloads\archive\Dataset\Dataset\te
                                                  target size=(128,128),
                                                  batch size=32,
                                                  class mode='binary')
         Found 121 images belonging to 2 classes.
In [5]:
         #import model building libraries
         #To define Linear initialisation import Sequential
         from keras.models import Sequential
         #To add Layers import Dense
         from keras.layers import Dense
         #To create Convolution kernel import Convolution2D
         from keras.layers import Convolution2D
         #import Maxpooling layer
         from keras.layers import MaxPooling2D
         #import flatten layer
         from keras.layers import Flatten
         import warnings
         warnings.filterwarnings('ignore')
In [7]: #initializing the model
         model=Sequential()
         #add convolutional layer
In [8]:
         model.add(Convolution2D(32,(3,3),input_shape=(128,128,3),activation='relu'))
         #add maxpooling layer
         model.add(MaxPooling2D(pool_size=(2,2)))
         #add flatten layer
         model.add(Flatten())
         #add hidden Layer
In [9]:
         model.add(Dense(150,activation='relu'))
         #add output layer
         model.add(Dense(1,activation='sigmoid'))
         #configure the learning process
In [10]:
         model.compile(loss='binary_crossentropy',optimizer="adam",metrics=["accuracy"])
In [11]:
         #Training the model
         model.fit_generator(x_train,steps_per_epoch=14,epochs=10,validation_data=x_test,validation_st
```

```
loss: 1.3686 - val_accuracy: 0.5950
     Epoch 2/10
     loss: 0.2423 - val_accuracy: 0.8926
     Epoch 3/10
     _loss: 0.1323 - val_accuracy: 0.9669
     Epoch 4/10
     loss: 0.1082 - val_accuracy: 0.9669
     Epoch 5/10
     l_loss: 0.1145 - val_accuracy: 0.9669
     Epoch 6/10
     14/14 [================== - 111s 8s/step - loss: 0.1938 - accuracy: 0.9037 - val
     loss: 0.1030 - val accuracy: 0.9669
     Epoch 7/10
     loss: 0.0831 - val_accuracy: 0.9752
     Epoch 8/10
     loss: 0.1073 - val_accuracy: 0.9669
     Epoch 9/10
     loss: 0.0754 - val_accuracy: 0.9835
     Epoch 10/10
     loss: 0.0601 - val accuracy: 0.9835
     <keras.callbacks.History at 0x2546507bf10>
Out[11]:
In [12]:
     model.save("forest1.h5")
In [13]: #import load_model from keras.model
     from keras.models import load model
     #import image class from keras
     from tensorflow.keras.preprocessing import image
     #import numpy
     import numpy as np
     #import cv2
     import cv2
In [15]: #Load the saved model
     model = load_model("forest1.h5")
     img=image.load_img(r'C:\Users\dhine\Downloads\archive\Dataset\Dataset\test_set\with fire\skyn
In [16]:
     x=image.img to array(img)
     res = cv2.resize(x, dsize=(128, 128), interpolation=cv2.INTER_CUBIC)
     #expand the image shape
     x=np.expand dims(res,axis=0)
In [17]: pred=model.predict(x)
     1/1 [=======] - 5s 5s/step
In [18]:
     pred
     array([[1.]], dtype=float32)
Out[18]:
In [ ]:
```

Epoch 1/10