

#### Assignment -4

Assignment Date	27 /10/2022
Student Name	Nirmal .S
Student Roll Number	142219106066
Team ID	PNT2022TMID21781
Maximum Marks	2 Marks

#### Question-1:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less 100 cms send “alert” to ibm cloud and display in device recent events.

#### Solution:

```
#include <WiFi.h>//library for wifi
```

```
#include <PubSubClient.h>//library for MQTT
```

```
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
```

```
//-----credentials of IBM Accounts-----
```

```
#define ORG "za7x6f"//IBM ORGANITION ID
```

```
#define DEVICE_TYPE "rj46"//Device type mentioned in ibm watson IOT Platform
```

```
#define DEVICE_ID "raj46"//Device ID mentioned in ibm watson IOT Platform
```

```
#define TOKEN "R0Q4uhcOcCD0hnom)K"
```

```
//Token String data3; float dist;
```

```
//----- Customise the above values -----char server[] = ORG
```

```
".messaging.internetofthings.ibmcloud.com";// Server Name
```

```
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and  
format in which data to be send
```

```
char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command
```

```
type AND COMMAND IS TEST OF FORMAT STRING char authMethod[] = "use-  
token-auth";// authentication method
```

```

char token[] = TOKEN; char clientId[] = "d:" ORG ":"
DEVICE_TYPE ":" DEVICE_ID;//client id

//-----

WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the predefined client id by
passing parameter like server id,portand wificredential

int LED = 4;
int trig = 5;
int echo =
18; void
setup()
{
Serial.begin(115200);
pinMode(trig,OUTPUT
T);
pinMode(echo,INPUT
); pinMode(LED,
OUTPUT); delay(10);
wificonnect();
mqttconnect();
}
void loop()// Recursive Function
{
digitalWrite(trig,LOW);
digitalWrite(trig,HIGH);
delayMicroseconds(10);
digitalWrite(trig,LOW);
float dur =

```

```

pulseIn(echo,HIGH); float
dist = (dur * 0.0343)/2;
Serial.print ("Distancein cm");
Serial.println(dist);

```

```

PublishData(dist)
; delay(1000);
if (!client.loop())
{
mqttconnect();
}
}
/*.....retrieving to Cloud.....*/

```

```

void PublishData(float dist) {
mqttconnect();//function call for connecting to
ibm
/*    creating the String in in form JSon to update the data to
ibm cloud
*/ String
object; if
(dist <100)
{
digitalWrite(LED,HIGH);
Serial.println("object is near");
object = "Near";
}
else
{

```

```

    digitalWrite(LED,LOW);
    Serial.println("no object found");
    object = "No";
}

String payload =
"\distance\":"; payload +=
dist; payload += ","
"\object\":"; payload +=
object; payload += "\"}";

    Serial.print("Sending payload: ");
    Serial.println(payload); if
(client.publish(publishTopic, (char*)
payload.c_str())) {

    Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print
publish ok in Serial monitor or else it will print publish failed

    } else {

        Serial.println("Publish failed");

    }
}

void mqttconnect() {
if (!client.connected())
{

    Serial.print("Reconnecting client to ");
    Serial.println(server); while
(!!!client.connect(clientId, authMethod, token)) {
    Serial.print("."); delay(500);

    }

    initManagedDevice();

    Serial.println();

}

}

```

```

void wificonnect() //function defination for wificonnect
{
    Serial.println();
    Serial.print("Connecting to ");
    WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the
connection while (WiFi.status() != WL_CONNECTED) {    delay(500);
    Serial.print(".");
}
    Serial.println("");
    Serial.println("WiFi connected");
    Serial.println("IP address: ");
    Serial.println(WiFi.localIP());
}

void initManagedDevice() { if
(client.subscribe(subscribetopic))
{
    Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
} else {
    Serial.println("subscribe to cmd FAILED");
}
}


void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
    Serial.print("callback invoked for
topic: ");
    Serial.println(subscribetopic); for (int
i = 0; i < payloadLength; i++) {
//Serial.print((char)payload[i]);    data3
+= (char)payload[i];

```

```
}  
data3="";  
}
```

Reference:

<https://wokwi.com/projects/347322163482591827>



- 

- 

- 

- 

- 

### Device Actions

The recent events listed show the live stream of data that is coming and going from this device.

Event	Value	Format	Last Received
Data	{"distance":59.51,"object":"Near"}	json	a few seconds ago
Data	{"distance":59.51,"object":"Near"}	json	a few seconds ago
Data	{"distance":2.01,"object":"Near"}	json	a few seconds ago
Data	{"distance":347.01,"object":"No"}	json	a few seconds ago
Data	{"distance":403.49,"object":"No"}	json	a few seconds ago

0 Simulations running