

The IBM logo is displayed in white text on a blue arrow-shaped background, which is part of a larger blue vertical bar on the left side of the page.

LITERATURE SURVEY

SMART FARMER – IOT
ENABLED SMART FARMING
APPLICATION

Team Details

Team Id :- PNT2022TMID22163

1. SENDHIL KANNAN
2. VAILANGARI MEERA
3. THARUN TEJA
4. VINAY

VINAY

A stylized graphic of a plant with several thin, curved lines representing stems or grass, located in the bottom left corner of the page.

Literature Survey on “Smart Farmer – IOT Enabled Smart Farming Application”

Reference	Technologies used	Advantages	Disadvantages
[1]	Microcontroller: CC3200 Chip, MCU Communication Technologies: MMS, Wi-Fi Module Sensors: Camera, Temperature Sensor, Humidity Sensor	<ul style="list-style-type: none"> Sends the information about humidity and temperature in air of field to farmer. Uses MMS technology to send captured images. 	<ul style="list-style-type: none"> MMS adds extra cost No automatic support system
[2]	Microcontroller: ATMEGA328P Cloud server: Adafruit Server Communication Technologies: Wi-Fi Sensors: Soil Moisture Sensor	<ul style="list-style-type: none"> Controlling the actions of motor pump (ON/OFF) based on the threshold value. 	<ul style="list-style-type: none"> No sprinkles No smart drains No automatic support system
[3]	Microcontroller: Arduino Cloud server: ThingSpeak Sensors: Light Intensity, pH, Electrical Conductivity, Water Temperature, Relative Humidity	<ul style="list-style-type: none"> Hydroponic System Bayesian Network Model System has manual and automatic mode 	<ul style="list-style-type: none"> Extremely computationally expensive model
[4]	Microcontroller: Arduino UNO Cloud server: ThingSpeak Communication Technologies: Wi-Fi Sensors: Water Level Sensor, Moisture Sensor	<ul style="list-style-type: none"> Farmers can monitor their fields remotely Irrigation control system 	<ul style="list-style-type: none"> Lack of automated decision support system
[5]	Microcontroller: Arduino Sensors: Temperature Sensor, Humidity Sensor, Soil Moisture Sensor	<ul style="list-style-type: none"> Data regarding sensors stored on server and user can view via GUI application. 	<ul style="list-style-type: none"> Decision making is rely on user or farmer No automatic support system

REFERENCES :

- [1] Prathibha S., Hongal A., and Jyothi M. (2017). IOT Based Monitoring System in Smart Agriculture. 2017 International Conference on Recent Advances in Electronics And Communication Technology (ICRAECT). doi: 10.1109/icraect.2017.52.
- [2] Lahande P., and Mathpathi D. (2018). IOT Based Smart Irrigation System. International Journal of Trend in Scientific Research and Development Volume-2(Issue-5), pp. 359-362. doi: 10.31142/ijtsrd15827.
- [3] Alipio M., Dela Cruz A., Doria J., and Fruto R. (2019). On the design of Nutrient Film Technique hydroponics farm for smart agriculture. Engineering in Agriculture, Environment and Food, 12(3), pp.315- 324. doi: 10.1016/j.eaef.2019.02.008.
- [4] Benyezza H., Bouhedda M., Djellout K., and Saidi A. (2018). Smart Irrigation System Based Thingspeak and Arduino. International Conference on Applied Smart Systems (ICASS). doi: 10.1109/icass.2018.8651993.
- [5] Kiani F., and Seyyedabbasi A. (2018). Wireless Sensor Network and Internet of Things in Precision Agriculture. International Journal of Advanced Computer Science and Applications, 9(6). doi: 10.14569/ijacsa.2018.090614.