

PROJECT DEVELOPMENT PHASE

SPRINT-2

DATE	15-11-2022
TEAMID	PNT2022TMID32019
PROJECT TITTLE	IOT based safety gadget for childsafety monitoring and notification

NOTIFICATION CODE:

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQTT

void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);

//-----credentials of IBM Accounts-----

#define ORG "tzwanu"//IBM ORGANITION ID
#define DEVICE_TYPE "Node_Mcu"//Device type mentioned in ibm watson IOT
Platform
#define DEVICE_ID "54321"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "87654321"
String data3;
float dist;
//----- Customise the above values -----
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
event perform and format in which data to be send
char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command
type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id

//-----
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parameter like server id,portand
wificredential

int LED = 4;
int trig = 5;
int echo = 18;
```

PROJECT DEVELOPMENT PHASE

SPRINT-2

```
void setup()
{
  Serial.begin(115200);
  pinMode(trig,OUTPUT);
  pinMode(echo,INPUT);
  pinMode(LED, OUTPUT);
  delay(10);
  wificonnect();
  mqttconnect();
}
void loop()// Recursive Function
{

  digitalWrite(trig,LOW);
  digitalWrite(trig,HIGH);
  delayMicroseconds(10);
  digitalWrite(trig,LOW);
  float dur = pulseIn(echo,HIGH);
  float dist = (dur * 0.0343)/2;
  Serial.print ("Distancein cm");
  Serial.println(dist);

  PublishData(dist);
  delay(1000);
  if (!client.loop()) {
    mqttconnect();
  }
}

/*.....retrieving to
Cloud.....*/

void PublishData(float dist) {
  mqttconnect();//function call for connecting to ibm
  /*
    creating the String in in form JSon to update the data to ibm cloud
  */
  String object;
  if (dist <100)
  {
    digitalWrite(LED,HIGH);
    Serial.println("object is near");
    object = "Near";
  }
  else
  {
    digitalWrite(LED,LOW);
```

PROJECT DEVELOPMENT PHASE

SPRINT-2

```
Serial.println("no object found");
object = "No";
}

String payload = "{\"distance\":";
payload += dist;
payload += "," " \"object\":";
payload += object;
payload += "\"}";

Serial.print("Sending payload: ");
Serial.println(payload);

if (client.publish(publishTopic, (char*) payload.c_str())) {
    Serial.println("Publish ok");// if it sucessfully upload data on the cloud
    then it will print publish ok in Serial monitor or else it will print publish
    failed
} else {
    Serial.println("Publish failed");
}
}

void mqttconnect() {
    if (!client.connected()) {
        Serial.print("Reconnecting client to ");
        Serial.println(server);
        while (!client.connect(clientId, authMethod, token)) {
            Serial.print(".");
            delay(500);
        }

        initManagedDevice();
        Serial.println();
    }
}

void wificonnect() //function defination for wificonnect
{
    Serial.println();
    Serial.print("Connecting to ");

    WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
    the connection
    while (WiFi.status() != WL_CONNECTED) {
        delay(500);
    }
}
```

PROJECT DEVELOPMENT PHASE

SPRINT-2

```
        Serial.print(".");
    }
    Serial.println("");
    Serial.println("WiFi connected");
    Serial.println("IP address: ");
    Serial.println(WiFi.localIP());
}

void initManagedDevice() {
    if (client.subscribe(subscribetopic)) {
        Serial.println((subscribetopic));
        Serial.println("subscribe to cmd OK");
    } else {
        Serial.println("subscribe to cmd FAILED");
    }
}

void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
    Serial.print("callback invoked for topic: ");
    Serial.println(subscribetopic);
    for (int i = 0; i < payloadLength; i++) {
        //Serial.print((char)payload[i]);
        data3 += (char)payload[i];
    }
    // Serial.println("data: "+ data3);
    // if(data3=="Near")
    // {
    // Serial.println(data3);
    // digitalWrite(LED,HIGH);

    // }


    // else
    // {
    // Serial.println(data3);
    // digitalWrite(LED,LOW);

    // }
    data3="";
}
```

PROJECT DEVELOPMENT PHASE

SPRINT-2

SIMULATION:



PROJECT DEVELOPMENT PHASE

SPRINT-2

CLOUD NOTIFICATION OUTPUT:

The screenshot displays the IBM Watson IoT Platform interface. The top navigation bar includes 'Browse', 'Action', 'Device Types', and 'Interfaces'. A sidebar on the left contains icons for various functions. The main content area shows the details for a specific device.

Device ID	Status	Device Type	Class ID	Date Added
54321	Connected	Node_Mcu	Device	Nov 8, 2022 9:52 PM

Below the device details, there is a section for 'Recent Events' with a table showing live data streams.

Event	Value	Format	Last Received
Data	{"distance":403.49,"object":"","No"}	json	a few seconds ago
Data	{"distance":403.49,"object":"","No"}	json	a few seconds ago
Data	{"distance":403.45,"object":"","No"}	json	a few seconds ago
Data	{"distance":403.47,"object":"","No"}	json	a few seconds ago
Data	{"distance":403.49,"object":"","No"}	json	a few seconds ago

An 'Activate Windows' watermark is visible in the bottom right corner of the screenshot.