| Team ID | PNT2022TMID32053 |
|---------------|--|
| Date | 13 November 2022 |
| Project Title | IoT Based Safety Gadget for Child Safety Monitoring and Notification |

Sprint 2 is about **LOGIN and NOTIFIACATION** of the IoT device in Parent's Web Application for getting information about Child's Status.


```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MOtt
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
 //----credentials of IBM Accounts-----
#define ORG "o6i6hl"//IBM ORGANITION ID
#define DEVICE TYPE "ESP32"//Device type mentioned in ibm watson IOT Platform
#define DEVICE ID "Nodemcu"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "Dps+?21X5ge6?1bRDz"
String data3;
float dist;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and format in which data to be send
char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
```


```
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the predefined client id by passing parameter like server
id, portand wificredential
int LED = 4;
int trig = 5;
int echo = 18;
void setup()
Serial.begin(115200);
pinMode(trig,OUTPUT);
pinMode(echo, INPUT);
pinMode(LED, OUTPUT);
delay(10);
wificonnect();
mqttconnect();
void loop()// Recursive Function
 digitalWrite(trig,LOW);
 digitalWrite(trig,HIGH);
 delayMicroseconds(10);
 digitalWrite(trig,LOW);
  float dur = pulseIn(echo,HIGH);
  float dist = (dur * 0.0343)/2;
  Serial.print ("Distancein cm");
  Serial.println(dist);
  PublishData(dist);
  delay(1000);
  if (!client.loop()) {
    mqttconnect();
```

```
.....*/
void PublishData(float dist) {
 mqttconnect();//function call for connecting to ibm
 String object;
 if (dist <100)
   digitalWrite(LED,HIGH);
  Serial.println("object is near");
  object = "Near";
 else
  digitalWrite(LED, LOW);
  Serial.println("no object found");
  object = "No";
 String payload = "{\"distance\":";
 payload += dist;
 payload += "," "\"object\":\"";
 payload += object;
 payload += "\"}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
```

```
if (client.publish(publishTopic, (char*) payload.c_str())) {
   Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it will print publish ok in Serial
 } else {
   Serial.println("Publish failed");
void mqttconnect() {
 if (!client.connected()) {
   Serial.print("Reconnecting client to ");
   Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
     Serial.print(".");
     delay(500);
    initManagedDevice();
    Serial.println();
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
 while (WiFi.status() != WL_CONNECTED) {
   delay(500);
   Serial.print(".");
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
```

```
void initManagedDevice() {
 if (client.subscribe(subscribetopic)) {
   Serial.println((subscribetopic));
   Serial.println("subscribe to cmd OK");
 } else {
    Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
 for (int i = 0; i < payloadLength; i++) {</pre>
    data3 += (char)payload[i];
// digitalWrite(LED,HIGH);
// Serial.println(data3);
data3="";
```





Link: https://wokwi.com/projects/348382996059914834