

IBM NALAIYA THIRAN 2022-23 PROJECT REPORT

SIGNS WITH SMART CONNECTIVITY FOR BETTER ROAD SAFETY

TEAM ID -PNT2022TMID51225

1. INTRODUCTION

1.1 Project Overview

The goal of this project is to replace the static signboards with smart connected sign boards to get the speed limitations from a web app using weather API and update it automatically based on the weather conditions, set diversions through API and warn drivers for school zones and hospital zones

1.2 Purpose

To replace the static signboards, smart connected sign boards are used.

- These smart connected sign boards get the speed limitations from a web app using weather API and update automatically.
- Based on the weather changes the speed may increase or decrease.
- Traffic diversion signs are displayed.
- Messages indicating school ,hospital, police station zones are also displayed.

2. LITERATURE SURVEY

2.1 Existing problem

a) Digital Notice Board Based on IOT

This project presents a digital notice board using IoT module. The idea behind this project is to provide its users with a simple, fast and reliable way to put up important notices in an LED where the user can send a message to be displayed in the LED. The message can be sent through

an android application designed in this project, through the IoT module. So, notices can be put up in an LED display from any location in the world. It uses a microcontroller for system control, IoT based technology for communication and sends the message through the android

application. The project consists of Arduino UNO board, IoT module, an LED, and an android application for user interface with the hardware. This device can be used anywhere irrespective of the place of deployment provided mobile network connectivity is available. This is a project that displays messages that the user desires, on an LED Display Matrix. The Display consists of 256 LED lights, sequentially arranged in 8 rows and 32 columns (8*32). Apart from the display, the project consists of a Node MCU controller which helps the system to connect to the Wi-Fi. This system makes use of Google Assistant to accept speech inputs from user, through user's Android smartphone. User needs to login into their Google account. A USB cable acts as the power cable for the system. The speech input is converted into a text display in an alphanumeric format which is predefined. The displayed message will either scroll or remain static, based on the size of display and length of message. This project can widely use in offices, schools, educational institutions as well as government and corporate offices to display important notices and messages. This can prove to help users save a lot of time as against the use of traditional pin and paper notice display.

b) Internet of Things Based Notifications Using Smart Notice Board

Conventional Notice Board employs manual display and monitoring with papers and ledgers. The Target users are unaware of information displayed on the notice board. The objective of the project is to display the message on the notice board from anywhere and anytime, that even provides broadcast alerts to the target users. The system was designed and developed using the Internet of Things. Arduino board integrates the display unit, Mobile App and SMS Agent through Internet. The message to be displayed on the notice board is sent through a mobile app to the board with Arduino. As soon as the message is displayed, SMS alert is sent to the target users. A system of efficient Notice Board display controlled through the Internet is accomplished and presented in this paper.

c) An IoT based Smart Monitoring System for Vehicles

There is increased adoption of penalty and fine for traffic rule violators in the public sector but there is a tendency for people to evade from those imposed fines and restrictions for their own safety. Our system will completely monitor all the traffic violations namely over speeding, rash driving, drunken driving, driving without a seat belt, and so on right from the starting of the car. There is an increasing demand to develop a system to check passengers without coming out of the vehicle. A new system for the police force to check the vehicle's details with a smart device placed in the vehicle. The device is equipped with speed monitoring, Alcohol detection, Seat belt checking, etc. If any violation is detected the controller sends an emergency data to the cloud, thus the vehicle is in continuous monitoring mode, and RTO will get updates about the vehicles which are violating rules. Alcoholic breath sensor will continuously monitor the driver's breath, speed sensor will be connected with the speedometer and checks for over speeding, Seat belt sensor will warn the driver if he/she is not using the seat belt, vehicle details including license, pollution details, insurance, etc. will be uploaded to the server or cloud. If any of the above things are violated, automatically defaulter will be imposed fines and the details will be sent to the Motor vehicle department.

d) Congestion Adaptive Traffic Light Control and Notification Architecture Using Google Maps APIs :

Controlling of traffic signals optimally helps in avoiding traffic jams as vehicle volume density changes on temporally short and spatially small scales. Nowadays, due to embedded system

development with the rising standards of computational technology, condense electronics boards as well as software packages, system can be developed for controlling cycle time in real time. At present, the traffic control systems in India lack intelligence and act as an open-loop control system, with no feedback or sensing network, due to the high costs involved. This paper aims to improve the traffic control system by integrating different technologies to provide intelligent feedback to the existing network with congestion status adapting to the changing traffic density patterns. The system presented in this paper aims to sense real-time traffic congestion around the traffic light using Google API crowdsource data and hence avoids infrastructure cost of sensors. Subsequently, it manipulates the signal timing by triggering and conveying information to the timer control system. Generic information processing and communication hardware system designed in this paper has been tested and found to be functional for a pilot run in real time. Both simulation and hardware trials show the transmission of required information with an average time delay of 1.2 seconds that is comparatively very small considering cycle time.

Mishra, Sumit Kumar, Devanjan Bhattacharya and Ankit K. Gupta. "Congestion Adaptive Traffic Light Control and Notification Architecture Using Google Maps APIs." Data 3 (2018): 67.

a) An IoT based Weather Information Prototype Using WeMos :

The Internet of Things (IOT) describes the interconnection of devices and people through the traditional internet and social networks for various day-to-day applications like weather monitoring, healthcare systems, smart cities, irrigation field, and smart lifestyle. IOT is the new revolution of today's internet world which monitors live streaming of the entire world's status like temperature, humidity, thunderstorm, earthquake, floods etc. that can stagger an alarm to human life. This paper proposes a low-cost weather monitoring system which retrieves the weather condition of any location from the cloud database management system and shows the output on an OLED display. The proposed system uses an ESP8266-EX microcontroller based Wemos D1 board and it is implemented on Arduino platform which is used to retrieve the data from the cloud. The main objective of this paper is to view weather conditions of any location and allows to access the current data of any station.

R. K. Kodali and A. Sahu, "An IoT based weather information prototype using WeMos," 2016 2nd International Conference on Contemporary Computing and Informatics (IC3I), 2016, pp.612-616, doi: 10.1109/IC3I.2016.7918036.

b) IOT Based Weather Monitoring and Reporting System Project

The IOT based Weather Monitoring and Reporting System project is used to get Live reporting of weather conditions. It will Monitor temperature, humidity, moisture and rain level. Suppose Scientists/nature analysts want to monitor changes in a particular environment like volcano or a rain-forest. And these people are from different places in the world. In this case, SMS based weather

monitoring system has some limitations. Since it sends SMS to few numbers. And time for sending SMS increases as the number of mobile numbers increases. In order to know the information about weather of a particular place then they have to visit that particular sites. Where everyone can see it.

Anita M. Bhagat ,Ashwini G. Thakare ,Kajal A. Molke , Neha S. Muneshwar ,Prof. V. Choudhary IOT Based Weather Monitoring and Reporting System ,2019 .

a) Incorporating Weather Updates for Public Transportation Users of Recommendation Systems:

This work presents a system for augmenting the functionality of Yelp-like recommendation sites by enabling users to search for places bounded by travel-time when using public transportation, and modifying recommendations based on updated weather conditions. Using public transport, although is cheaper and efficient, entails that only fixed places of boarding/exiting may be used which, in turn, implies walking to (from) a particular location from (to) a given station. Given the impact of the weather on the mood and activities, preferences for a certain type of services may need to be dynamically adjusted based on the current weather or the near-future forecast, modulo travel-routes to preferred locations. In this work, we develop a model to predict a user's preferred mode of transport (car, or public transit) from their old check-ins and incorporate the weather context into

the recommendation process. We use event-based modeling to control the extent of walking depending on user-defined tolerance information and live weather conditions. We implemented a web application (both desktop and mobile platforms), utilizing existing tools such as Google Maps Direction API and OpenWeatherMap API for retrieving real-time information.

b) System Natural Data is now becoming more valuable in a day to get real-time data for natural data:

Physical monitoring of the environment allows for the identification of areas suitable for agriculture, industry, and other purposes. In this article, the Arduino-UNO microcontroller- based board is used for the data acquisition strategy and the use of analog and digital sensors. Temperature, humidity, light intensity and gas concentrations can be monitored in real-time [4] [9-12] [13-16].

c) The impact of daily weather on daily travel trips :


It is of increasing social interest - climate change and increasing scarcity, understanding the climatic implications of travel behavior, especially walking and biking. Recently, various courses are travel, health, and biometeorology.

1.1 Problem Statement Definition

To replace the static signboards with smart connected sign boards to get the speed limitations from a web app using weather API and update it automatically based on the weather conditions, set diversions through API and warn drivers for school zones and hospital zones.

3. IDEATION & PROPOSED SOLUTION

3.1 Empathy Map Canvas




<https://github.com/IBM-EPBL/IBM-Project-13896-1659534693/blob/main/Project%20Design%20And%20Planning/Ideation%20Phase/Empathy%20Map.pdf>

1.1 Ideation & Brainstorming

<https://github.com/IBM-EPBL/IBM-Project-13896-1659534693/blob/main/Project%20Design%20And%20Planning/Ideation%20Phase/Brainstorming.pdf>

Step-1: Team Gathering, Collaboration and Select the Problem Statement



Conducting a brainstorm

Executing a brainstorm isn't unique; holding a productive brainstorm is. Great brainstorms are ones that set the stage for fresh and generative thinking through simple guidelines and an open and collaborative environment. Use this when you're just kicking-off a new project and want to hit the ground running with big ideas that will move your team forward.

⌚ 15 minutes to prepare
⌚ 30-60 minutes to collaborate
👤 3-8 people recommended

➕ Before you collaborate

A little bit of preparation goes a long way with this session. Here's what you need to do to get going.

⌚ 15 minutes

➡ Choose your best "How Might We" Questions

Create 5 HMW statements before the activity to propose them to the team.

⚙ Set the stage for creativity and inclusivity

Go over the brainstorming rules and keep them in front of your team while brainstorming to encourage collaboration, optimism, and creativity.

1. **Encourage wild ideas** (If none of the ideas sound a bit ridiculous, then you are filtering yourself too much.)
2. **Defer judgement** (This can be as direct as harsh words or as subtle as a condescending tone or talking over one another.)
3. **Build on the ideas of others** ("I want to build on that idea" or the use of "yes, and...")
4. **Stay focused on the topic at hand**
5. **Have one conversation at a time**
6. **Be visual** (Draw and/or upload to show ideas, whenever possible.)
7. **Go for quantity**

📖 Interested in learning more?

Check out the Meet: Think Kit website for additional tools and resources to help your team collaborate, innovate and move ideas forward with confidence.

[Open the website →](#)

➡ Choose your best "How Might We" Questions

Share the top 5 brainstorm questions that you created and let the group determine where to begin by selecting one question to move forward with based on what seems to be the most promising for idea generation in the areas you are trying to impact.

⌚ 10 minutes

QUESTION

what do we incorporate to make it a smart signboard

QUESTION


how helpful is the smart signboards

QUESTION

In what minimum ways it can be achieved

QUESTION

what can be done

Step-2: Brainstorm, Idea Listing and Grouping**1.1 Proposed Solution**

S. NO	PARAMETER	DESCRIPTION
1.	Problem Statement (Problem to be solved)	To avoid road accidents caused by collisions, over speeding of vehicles due to adverse weather conditions.
2.	Idea / Solution description	The project approach focuses on to digitalizing the already existing static signboards to smart signboards using a interface where people are able to see about whether the indications and such information. this information can be accessed from open weather map and we can display the updates on the user interface on a timely basis. The smart display gets the speed limitations from a web app using weather API and update periodically. based on the weather changes, the user is alerted on the suggested speed limits.

3.	Novelty / Uniqueness	Sign boards are converted to digital display where APIs and online services are integrated in new and interesting ways. Open Weather Map is an online service that provides global weather data, forecasts and historical weather data for any geographical location.
4.	Social Impact / Customer Satisfaction	Suggests the speed limits for the user to follow based on the weather which can be helpful in reducing any possible accident.
5.	Business Model (Revenue Model)	It doesn't cost much for implementation (unless it is for use in a largescale because we obtain the required information to display and integrate it with an interface which can be achieved by programming accordingly with the help of IOT.
6.	Scalability of the Solution	This project is highly feasible and can later on be further updated with other additional features as well.

1.1 Problem Solution fit

Define CS, fit into CC Focus on CS, fit into CC	1. CUSTOMER SEGMENT(S) Passenger who wants to travel safely irrespective of type of transport on the roads.	6. CUSTOMER CONSTRAINTS Proper network connection. Data Accuracy. Availability of proper devices. Fear of budget.	5. AVAILABLE SOLUTIONS By replacing the static signboards, smart connected signboards are used. Based on traffic and fatal situations. Smart Connectivity has enabled for road and people safety with the help of digital signboard, openweather api and web application used to user can know the weather conditions anywhere. IOT based Signs with smart connectivity for better road safety is more effective for people.
	2. JOBS-TO-BE-DONE / PROBLEMS Provide better safety for travelers by providing information about the weather conditions speed limitations and nearby places.	9. PROBLEM ROOT CAUSE Lack of proper awareness about road safety and no proper knowledge about traffic rules.	7. BEHAVIOUR User can use this technology and gain information about traffic and weather conditions etc and travel accordingly.
Focus on JAP, fit into BE, understand RC Focus on JAP, fit into BE, understand RC	3. TRIGGERS Over speed driving, rash driving, violation of rules, failure to understand signs, fatigue, alcohol and inclement weather that causes the possible accidents. As the result it also affects the public, work life and these problems can be reduced by using smart connectivity signboards or user interface.	10. YOUR SOLUTION To come up with a solution using smart linked sign boards as an alternative to static signboards. With the help of a weather API, these intelligent connected sign boards automatically update with the current speed limits. The speed may rise or fall in response to variations in the weather. The display of diversion signs is determined by traffic and potentially fatal situations. There are also signs that warns of hospitals, schools ahead.	8. CHANNELS of BEHAVIOUR Online: Notify the information about of weather / traffic in web application. The departments can receive direct emails or messages from customers. (Officers on nearby patrol). Offline: Following directions is one of the main tasks for the traveler, but they can utilize the smartboard signs to check the state of the road from wherever they are.
	4. EMOTIONS: BEFORE / AFTER Road ways traffic causes a lot of problems in daily life, it affects daily lives of workers, can't reach the destination on time, affects work life, increases the rate of accidents and other problems. In order to overcome this we implement smart connectivity for better road safety to avoid traffic and decrease speed limit while raining, thus reducing possible accidents.		

1. REQUIREMENT ANALYSIS

1.1 Functional requirement


S. NO	FUNCTIONAL REQUIREMENTS (EPIC)	SUB REQUIREMENTS (STORY/SUB-TASK)
1.	User Visibility	Sign Boards should be made with LED's which are bright colored and are capable of attracting the driver attention but it should also not be too distracting or blinding cause it may lead to accidents.
2.	User Need	The smart sign boards should be placed frequently in places it is needed and less in places where it is not needed much to avoid confusion for the user during travel.
3.	User Understanding	For better understanding of the driver, the signs should be big, clear and legible and it can also include illustrations which will make it easily understandable to the driver.
4.	User Convenience	The display should be big enough that it should even be visible from far distance clearly.

1.1 Non-Functional requirements

S. NO	NON-FUNCTIONAL REQUIREMENTS	DESCRIPTION
1.	Usability	It should be able to Upgrade and Update when there is a need for it.
2.	Security	It should have good security system so that no other person is able to hack and display
3.	Reliability	It should be able to display to information correctly and error-free.
4.	Performance	It should be able to automatically update itself when certain weather or traffic problem occurs.
5.	Availability	It should be available 24/7 so that it can be beneficial to the customer i.e the driver.
6.	Scalability	It should be able to easily change and upgrade according to change and need in requirement.


4. PROJECT DESIGN

4.1 Data Flow Diagrams




1.1 Solution & Technical Architecture

SOLUTION ARCHITECTURE



TECHNICAL ARCHITECTURE:



1.1 User Stories

	Functional requirements(epic)	User story number	User story/task	Acceptance criteria	priority
User 1	User visibility/usability	USN-1	To display speed limitation on the smart sign boards.	Can view the speed limitations	High
User 2		USN-2	To increase or decrease the speed according to the weather conditions.	Can see the changes corresponding to the weather	High
	Interface	USN-3	As a user the interface or signboard should be simple and easily readable.	Can view the interface easily.	High
	Data	USN-4	Display the data regarding the weather changes.	Weather changes are displayed.	High

	Data	USN-5	Display the zones (sensitive) nearby such as schools, hospitals.	Nearby zones are displayed.	High
Administrator (officials)	Problem solving/fault clearance	USN-6	As an official who is in charge for the proper functioning of the sign boards have to maintain it through periodic monitoring.	Officials can monitor the sign boards for proper functioning.	Medium

5. PROJECT PLANNING & SCHEDULING

a. Sprint Planning & Estimation

sprint	Functional requirements	User story number	User story /task	Story points	priority	Team members
Sprint 1	IDE	USN-1	Installing all the software which are required like python IDE.	2	Low	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshinie R.Sankareswari B.Monika
Sprint 1	Resources	USN-2	Initialization Create and initialize accounts in various public APIs like Open Weather API.	5	Low	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshinie R.Sankareswari B.Monika
Sprint 1		USN-3	Write a Python program that outputs results given the inputs like weather.	13	Medium	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshinie R.Sankares

						wari B.Monika
Sprint 2		USN-4	Checking the simulation with conditions and Coding.	5	Medium	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshinie R.Sankareswari B.Monika
Sprint 2	software	USN-5	Working with IBM Watson IOT and Node Red integration.	2	High	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshinie R.Sankareswari B.Monika
Sprint 2			Test the above created IOT device s and workflow.	13	High	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshinie R.Sankareswari B.Monika
Sprint 3	Application development	USN-6	Using MIT App Inventor create an App.	13	Medium	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshinie R.Sankareswari B.Monika
Sprint 3			Integrate the MIT app with node -red.	5	Medium	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshinie R.Sankareswari B.Monika


Sprint 3			Testing the Application.	2	Medium	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshini R.Sankareswari B.Monika
Sprint 4	Interface	USN-7	Displaying speed Limitations.	2	Medium	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshini R.Sankareswari B.Monika
Sprint 4			Displaying traffic diversion Signs depending on the road conditions.	5	Medium	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshini R.Sankareswari B.Monika
Sprint 4			Testing of the user interface with the software.	13	Medium	V.Rithiga S.Angelin Sukirtha M.Snekapriyatharshini R.Sankareswari B.Monika

b. Sprint Delivery Schedule


sprint	Total story points	duration	Sprint start date	Sprint end date(planned)	Story points completed (as on planned end date)	Sprint release date (actual)
Sprint-1	20	6 days	24 Oct 2022	25 Oct 2022	20	25 Oct 2022
Sprint-2	20	6 days	31 Oct 2022	05 Nov 2022	20	05 Nov 2022
Sprint-3	20	6 days	07 Nov 2022	12 Nov 2022	20	12 Nov 2022
Sprint-4	20	6 days	14 Nov2022	19 Nov 2022	20	19 Nov 2022

c.) Reports from JIRA

Sprint -3 :




Sprint - 4 :




Burndown Chart for Sprint – 3:

6. CODING & SOLUTIONING (Explain the features added in the project along with code)




6. CODING & SOLUTIONING (Explain the features added in the project along with code)



6.1 Feature 1 -GET WEATHER DETAILS FOR GIVEN LOCATION

This part of Node RED flow accepts an http GET end point, from which the location, uid, info are passed. Message parser sets the required APIKEY for OpenWeatherAPI for the next block. This data is then passed onto Decision Maker which makes all the decisions regarding the message to be output at the display and sends it as a http response. This data is displayed at the microcontroller. Thus a lot of battery is saved due to lesser processing time.



6.2 Feature 2- GET SPEED LIMITATIONS, MESSAGES, SIGNS

The Node RED flow obtains the data published to the cloud such as speed limitations, messages such as warnings about the zones (schools, hospitals, police stations), signs such as diversions, U- turns etc, and displays them in the dashboard.

7. TESTING

7.1 Test Cases

- TEST CASE 1

Temperature': 303.03, 'Humidity': 51, 'Pressure': 1010, 'Message': 'SLOW DOWN , SCHOOL IS NEAR', 'Sign': '', 'Speed': '', 'Visibility': 'Clear Weather'

- TEST CASE 2

Temperature': 303.03, 'Humidity': 51, 'Pressure': 1010, 'Message': '', 'Sign': 'Left Diversion <-', 'Speed': 'SLOW DOWN , Speed Limit Exceeded', 'Visibility': 'Clear Weather'

- TEST CASE 3

Temperature': 303.03, 'Humidity': 51, 'Pressure': 1010, 'Message': 'SLOW DOWN , HOSPITAL NEARBY', 'Sign': 'Left Diversion <-', 'Speed': '', 'Visibility': 'Clear Weather'

- TEST CASE 4

Temperature': 303.03, 'Humidity': 51, 'Pressure': 1010, 'Message': 'NEED HELP, POLICE STATION NEARBY', 'Sign': 'U Turn', 'Speed': 'Moderate Speed', 'Visibility': 'Clear Weather'.

7.2 User Acceptance Testing

Dynamic speed & diversion variations based on the weather and traffic helps user to avoid traffic and have a safe journey home. The users would welcome this idea to be implemented everywhere.

8. RESULTS

8.1 Performance Metrics

The performance of the website varies based on the software chosen for implementation . Built upon NodeJS, a light and high performance engine, NodeRED is capable of handling upto 10,000 requests per second. Moreover, since the system is horizontally scalable, a even higher demand of customers can be served.

9. ADVANTAGES & DISADVANTAGES

- **ADVANTAGES**

- Lower battery consumption since processing is done mostly by Node RED servers in the cloud.
- Cheaper and low requirement micro controllers can be used since processing requirements are reduced.
- Longer lasting systems.
- Dynamic Sign updation.
- School/Hospital Zone alerts

- **DISADVANTAGES**

- The size of the display determines the requirement of the micro controller
- Dependent on OpenWeatherAPI and hence the speed reduction is same for a large area in the scale of cities.

10. CONCLUSION

Our project is capable of serving as a replacement for static signs for a comparatively lower cost and can be implemented in the very near future. This will help reduce a lot of accidents, traffics and maintain a peaceful environment.

11. FUTURE SCOPE

Introduction of intelligent road sign groups in real life scenarios could have great impact on increasing the driving safety by providing the end-user with the most accurate information regarding the current road and traffic conditions. Even displaying the information of a suggested driving speed and road surface condition (temperature, icy, wet or dry surface) could result in smoother traffic flows and, what is more important, in increasing a driver's awareness of the road situation.

12. APPENDIX

Source Code :

```
import wiotp.sdk.device
import time
import random
import requests, json

myConfig = {
    "identity": {
        "orgId": "ojfcbe",
        "typeId": "sulan",
        "deviceId": "1234"
    },
    "auth": {
        "token": "RsCA-twpue)2)c8j&r"
    }
}

def myCommandCallback(cmd):
    print("Message received from IBM IoT Platform: %s" % cmd.data['command'])
    m=cmd.data['command']

client = wiotp.sdk.device.DeviceClient(config=myConfig, logHandlers=None)
client.connect()

BASE_URL = "https://api.openweathermap.org/data/2.5/weather?"
CITY = "Coimbatore"
URL = BASE_URL + "q=" + "Coimbatore" + "&appid=" +
"fbcb52a2a6c7bbea1396de2b6b17ea8a"

while True:
    response = requests.get(URL)
    if response.status_code == 200:
        data = response.json()
        main = data['main']

        temperature = main['temp']
        humidity = main['humidity']
        pressure = main['pressure']
        report = data['visibility']
```

```
repo=random.randint(0,5)
if repo==1:
    prt="SLOW DOWN , SCHOOL IS NEAR"
elif repo==3:
    prt="SLOW DOWN , HOSPITAL NEARBY"
elif repo==5:
    prt="NEED HELP, POLICE STATION NEARBY"
else:
    prt=""
speed=random.randint(0,150)
if speed>=100:
    prt3="SLOW DOWN , Speed Limit Exceeded"
elif speed>=60 and speed<100:
    prt3="Moderate Speed"
else:
    prt3="Usual speed limit"
sign=random.randint(0,5)
if sign==1:
    prt2="Right Diversion ->"
elif sign==3:
    prt2="Left Diversion <-"
elif sign==5:
    prt2="U Turn"
else:
    prt2=""
if temperature<=50:
    prt4="Fog Ahead, Drive Slow"
else:
    prt4="Clear Weather"

else:
    print("Error in the HTTP request")
myData={'Temperature':temperature,'Humidity':humidity,'Pressure':pressure,
'Message':prt, 'Sign':prt2, 'Speed':prt3, 'Visibility':prt4}
client.publishEvent(eventId="status",    msgFormat="json",    data=myData,    qos=0,
onPublish=None)
```

```
print("Published data Successfully: %s", myData)
client.commandCallback = myCommandCallback
time.sleep(5)
client.disconnect()
```

GitHub Link

GitHub link -<https://github.com/IBM-EPBL/IBM-Project-13896-1659534693>

