



**Sprint-4**  
**Signs with Smart Connectivity for Better Road Safety**

Team ID	PNT2022TMID12332
Project Name	Signs with smart connectivity for Better road safety

## Node RED flow :



```
// get Direction given UID
msg.payload = global.get(String(msg.payload.uid)); return
msg;


// get UID msg.payload =
msg.payload.uid; return msg;

// get Location msg.payload =
msg.payload.location; return msg;

// get Visibility msg.payload =
msg.payload.visibility; return msg;

// get Temperature msg.payload =
msg.payload.temperature;
return msg;
```

**getSpeed API flow :**



```

weatherObj = JSON.parse(JSON.stringify(msg.payload));
localityObj      =      global.get("data");      var
suggestedSpeedPercentage = 100;

var   preciseObject   =   {   temperature   :
    weatherObj.main.temp - 273.15, location :
    localityObj.location,      visibility   :
    weatherObj.visibility/100,      uid      :
    localityObj.uid,
    direction : global.get("direction") };

msg.payload = preciseObject; return

msg;

weatherObj = JSON.parse(JSON.stringify(msg.payload));
localityObj      =      global.get("data");      var
suggestedSpeedPercentage = 100;

var   preciseObject   =   {   temperature   :
    weatherObj.main.temp - 273.15,
    weather : weatherObj.weather.map(x=>x.id).filter(code => code<700),
    visibility : weatherObj.visibility/100 };

if(preciseObject.visibility<=40) suggestedSpeedPercentage
    -=30

switch(String(preciseObject.weather)[-1]) // https://openweathermap.org/weather-
conditions refer weather codes meaning here
{ case "0" : suggestedSpeedPercentage -=10;break; case
    "1" : suggestedSpeedPercentage -=20;break; case "2"
    :
    suggestedSpeedPercentage -=30;break; }


msg.payload = preciseObject;

var doNotHonk = 0;
if(localityObj.hospitalZone=="1"||localityObj.schoolZone=="1")
    doNotHonk = 1;

var      returnObject      =      {      suggestedSpeed      :
    localityObj.usualSpeedLimit*(suggestedSpeedPercentage/100), doNotHonk :
    doNotHonk
    }
msg.payload = String(returnObject.suggestedSpeed) + " kmph \n\n" +
(returnObject.doNotHonk==1?"Do Not Honk":"" ) + "$" +
global.get(String(localityObj.uid));

return msg;


```



```
global.set(String(msg.payload.uid),msg.payload.dir);
```

```
return msg;
```

### Circuit Diagram :



### ESP 32 CODE :

```
#include <WiFi.h> #include
<HTTPClient.h> #include
<Adafruit_GFX.h>
#include <Adafruit_ILI9341.h>
#include <string.h>

const char* ssid = "Wokwi-GUEST";
const char* password = "";

#define TFT_DC 2
#define TFT_CS 15
Adafruit_ILI9341 tft = Adafruit_ILI9341(TFT_CS, TFT_DC);

String myLocation = "Chennai,IN"; String usualSpeedLimit
= "70"; // kmph

int schoolZone = 32; int hospitalZone
= 26;
```

```
int uid = 2504; // ID Unique to this Micro Contoller String getString(char
x)
{
    String s(1, x); return
    s;
}
```

```
String stringSplitter1(String fullString,char delimiter='$')
{
    String returnString = "";
    for(int i = 0; i<fullString.length();i++) { char c
        = fullString[i]; if(delimiter==c) break;
        returnString+=String(c);
    }
    return(returnString);
}
```

```
String stringSplitter2(String fullString,char delimiter='$')
{
    String returnString = ""; bool flag
    = false;
    for(int i = 0; i<fullString.length();i++) { char c =
        fullString[i]; if(flag)
        returnString+=String(c); if(delimiter==c)
        flag = true;
    }
    return(returnString);
}
```

```
void rightArrow()
{ int refX = 50;
    int refY = tft.setCursorY() + 40;

    tft.fillRect(refX,refY,100,20,ILI9341_RED);
    tft.fillTriangle(refX+100,refY-
30,refX+100,refY+50,refX+40+100,refY+10,ILI9341_RED);
}
```

```
void leftArrow()
{ int refX = 50;
    int refY = tft.setCursorY() + 40;

    tft.fillRect(refX+40,refY,100,20,ILI9341_RED); tft.fillTriangle(refX+40,refY-
30,refX+40,refY+50,refX,refY+10,ILI9341_RED);
}
```

```
void upArrow()
{ int refX = 125;
    int refY = tft.setCursorY() + 30;
```

```

tft.fillTriangle(refX-
40,refY+40,refX+40,refY+40,refX,refY,ILI9341_RED); tft.fillRect(refX-
15,refY+40,30,20,ILI9341_RED); }

```

```

String APICall() {
    HTTPClient http;

    String url = "https://node-red-grseb-2022-11-05-test.eu-
gb.mybluemix.net/getSpeed?";
    url += "location="+myLocation+"&";
    url += "schoolZone="+digitalRead(schoolZone)+(String)"&"; url +=
    "hospitalZone="+digitalRead(hospitalZone)+(String)"&"; url +=
    "usualSpeedLimit="+usualSpeedLimit+(String)"&";
    url += "uid="+uid;
    http.begin(url.c_str());
    httpStatusCode = http.GET();

    if (httpStatusCode>0) {
        String payload = http.getString(); http.end(); return(payload);
    } else {
        Serial.print("Error code: ");
        Serial.println(httpStatusCode);
    } http.end();
}

```

```

void myPrint(String contents) {
    tft.fillScreen(ILI9341_BLACK);
    tft.setCursor(0, 20);
    tft.setTextSize(4);
    tft.setTextColor(ILI9341_RED);
    //tft.println(contents);

    tft.println(stringSplitter1(contents)); String c2
    = stringSplitter2(contents); if(c2=="s") //
    represents Straight
    { upArrow();
    }
    if(c2=="l") // represents left
    { leftArrow();
    }
    if(c2=="r") // represents right
    { rightArrow();
    }
}

```

```

void setup() {
    WiFi.begin(ssid, password, 6);

    tft.begin();
    tft.setRotation(1);
}

```

```
tft.setTextColor(ILI9341_WHITE);
tft.setTextSize(2);
tft.print("Connecting to WiFi");

while (WiFi.status() != WL_CONNECTED)
{
    delay(100);
    tft.print(".");
}


tft.print("\nOK! IP="); tft.println(WiFi.localIP());
}

void loop() { myPrint(APICall());
    delay(100);
}
```



## Output :

### Node RED Dashboard :



## Wokwi Output :

The Wokwi simulation output shows the following code and visual representation:

```
1 #include <WiFi.h>
2 #include <HTTPClient.h>
3 #include <Adafruit_GFX.h>
4 #include <Adafruit_ILI9341.h>
5 #include <string.h>
6
7 const char* ssid = "Wokwi-GUEST";
8 const char* password = "";
9
10 #define TFT_DC 2
11 #define TFT_CS 15
12 Adafruit_ILI9341 tft = Adafruit_ILI9341(TFT_CS, TFT_DC);
13
14 String myLocation = "Chennai,IN";
15 String usualSpeedLimit = "70"; // kmph
16
17 int schoolZone = 32;
18 int hospitalZone = 26;
19
20 int uid = 2504;
21
22 String getString(char x)
23 {
24   String s(1, x);
25   return s;
26 }
27
28 String stringsplitter(String fullString, char delimiter)
29 {
30   String returnString = "";
31   for(int i = 0; i < fullString.length(); i++)
32   {
33     char c = fullString[i];
34     if(c == delimiter)
35     {
36       returnString += getString(c);
37       returnString += "\n";
38     }
39     else
40     {
41       returnString += c;
42     }
43   }
44   return returnString;
45 }
```

The visual representation shows an ESP32 microcontroller connected to an ILI9341 display. The display shows the text: "Connecting to WiFi OK! IP=10.10.0.2".

