# ASSIGNMENT-1 PLASMA DONAR APPLICATION

# app.py

fromflaskimportFlask,render_template
app =Flask(name
)@app.r
oute("/")
defhome():
returnrender_template("home.html")
@app.route("/about")
defabout():
returnrender_template("about.html")
@app.route("/sign_up")
defsign_up():
returnrender_template("sign_up.html")
@app.route("/sign_in")
defsign_in():
returnrender_template("sign_in.html")
ifname=="main
":app.run()

### base.html

```
<!doctypehtml>
<htmllang="en">
 <head>
  <!--Required metatags-->
  <metacharset="utf-8">
  <meta name="viewport" content="width=device-width, initial-</pre>
scale=1,shrink-to-fit=no">
  <!--BootstrapCSS-->
  link
rel="stylesheet"href="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/css/bo
otstrap.min.css" integrity="sha384-
ggOyR0iXCbMQv3Xipma34MD+dH/1fQ784/j6cY/iJTQUOhcWr7x9JvoRxT2
MZw1T"crossorigin="anonymous">
  {%blockhead%}{%endblock%}
 </head>
 <body>
  <navclass="navbarnavbar-expand-lgbg-light">
    <divclass="container-fluid">
     <aclass="navbar-brand"href="#">Navbar</a>
     <button class="navbar-toggler" type="button" data-bs-
toggle="collapse"data-bs-target="#navbarNav" aria-controls="navbarNav"
aria-expanded="false"aria-label="Togglenavigation">
      <spanclass="navbar-toggler-icon"></span>
     </button>
     <divclass="collapsenavbar-collapse"id="navbarNav">
      <ulclass="navbar-nav">
```

```
<aclass="nav-linkactive"aria-current="page"href="/">Home</a>
        cli class="nav-item">
         <aclass="nav-link"href="/about">About</a>
        <aclass="nav-link"href="/sign_up">SingUp</a>
        cli class="nav-item">
         <aclass="nav-link"href="/sign_in">SignIn</a>
       </div>
    </div>
   </nav>
  <!--OptionalJavaScript -->
  <!--jQueryfirst,thenPopper.js,thenBootstrapJS-->
  <script src="https://code.jquery.com/jquery-</pre>
3.3.1.slim.min.js"integrity="sha384-
q8i/X+965DzO0rT7abK41JStQIAqVgRVzpbzo5smXKp4YfRvH+8abtTE1Pi6j
izo"crossorigin="anonymous"></script>
  <scriptsrc="https://cdnjs.cloudflare.com/ajax/libs/popper.js/1.14.7/umd/popp</pre>
er.min.js" integrity="sha384-
UO2eT0CpHqdSJQ6hJty5KVphtPhzWj9WO1clHTMGa3JDZwrnQq4sF86dIH
NDz0W1"crossorigin="anonymous"></script>
  <scriptsrc="https://stackpath.bootstrapcdn.com/bootstrap/4.3.1/js/bootstra</pre>
p.min.js" integrity="sha384-
```

JjSmVgyd0p3pXB1rRibZUAYoIIy6OrQ6VrjIEaFf/nJGzIxFDsf4x0xIM+B07jR M"crossorigin="anonymous"></script>

```
{%block body%}{%endblock%}
</body>
</html>
```

## home.html

```
{%extends'base.html'%}

{%blockhead%}


<title>Home</title>
{%endblock%}

{%blockbody%}]

<h4>ThisisHomePage</h4>
{%endblock%}
```

### **Output:**

77\*F Mostly cloudy



^ ♠ ☐ ENG ♠ Φ D 10:43 PM 22-09-2022

# About.html

```
{%extends'base.html'%}

{%blockhead%}


<title>About</title>
{%endblock%}

{%blockbody%}

<h4>ThisisAboutPage</h4>

{%endblock%}
```


## **Output:**



### sign up.html:

```
{%extends'base.html'%}
{%blockhead%}
 <title>SignUp</title>
{%endblock%}
{%blockbody%}
<center><h2>SignUpForm</h2></center>
 <form>
  <divclass="mb-3">
    <labelfor="name"class="form-label">Name</label>
    <inputtype="email"class="form-control"id="name">
  </div>
  <divclass="mb-3">
    <labelfor="email"class="form-label">Emailaddress</label>
    <inputtype="email"class="form-control"id="email">
  </div>
  <divclass="mb-3">
    <labelfor="pwd"class="form-label">Password</label>
    <inputtype="password"class="form-control"id="pwd">
  </div>
  <divclass="mb-3">
    <labelfor="cpwd"class="form-label">Emailaddress</label>
    <inputtype="password"class="form-control"id="cpwd">
  </div>
  <center><button type="submit" class="btn btn-</pre>
primary">SignUp</button></center>
 </form>
{%endblock%}
```

#### **Output:**



## Sign in.html:

## **Output:**

