NOTIFICATION AND STORE DATA

#include <wifi.h>//library for wifi</wifi.h>
#include <pubsubclient.h>//library for</pubsubclient.h>
MQTT
void callback(char* subscribe topic, byte* payload, unsigned int payloadlength);
//credentials of IBM Account
#define ORG "frpi8s"// IBM ORGANIZATION ID
#define DEVICE_TYPE "NodeMCU"//DEVICE TYPE MENTIONED IN IOT WATSON
PLATFORM #define DEVICE_ID "12345"//DEVICE ID MENTIONED IN IOT WATSONPLATEFORM
#define TOKEN "12345678"//Token String data3;floatdist;
//customize the above valuechar server [] =ORG
".messaging.internetofthings.ibmcloud.com";//servername
char publish topic[]="ultrasonic/evt/Data/fmt/json";/*topic nameandtype
of event perform and formatin
which data to be send*/
charsubscribetopic[]="ultrasonic/cmd/test/fmt/String";/*cmd REPRESENT
Command tupe and
COMMAND IS TEST OF FORMAT STRING*/
<pre>char authMethod[]="use-token-auth";//authentication method char</pre>
token[]=TOKEN;
char clientid[]="d:" ORG ":" DEVICE_TYPE":" DEVICE_ID;//CLIENT ID
//
WiFiClient wifiClient;// creating an instance for wificlient PubSubClient client(server, 1883, callback, wifiClient);/*calling thepredefined
client id by passing parameter like server id, portand wificredential*/int LED =4;
int trig =5; int echo=18; void setup(){

```
Serial.begin(115200); pinMode(trig,OUTPUT); pinMode(echo,INPUT);
pinMode(LED,OUTPUT); delay(10); Serial.println(); wificonnect();
mattconnect():
void loop() { digitalWrite(trig,LOW); digitalWrite(trig,HIGH);
delayMicroseconds(10); digitalWrite(trig,LOW);
float dur=pulseIn(echo,HIGH); float dist=(dur * 0.0343)/2;
Serial.print("distance in
cm"); Serial.println(dist); PublishData(dist);
delay(1000);
if (!client.loop()){ mqttconnect();
}
}
/* ..... retriving to
cloud.
*/
void PublishData(float dist){ mqttconnect();//function call for connectingto ibm
/*creating the string in form of JSON to update the data to ibm cloud*/String
object;if(dist<100)
digitalWrite(LED,HIGH); Serial.println("no object is near");
object="Near";
else
digitalWrite(LED,LOW); Serial.println("no object found"); object="No";
String payload="{\"distance\":"; payload +=dist; payload
+="," "\"object\":\""; payload += object;payload +=
Serial.print("Sending payload: ");
Serial.println(payload);
if(client.publish(publishtopic, (char*) payload.c_str())){ Serial.println("Publish
ok");/* if its sucessfully upload data on the cloud then it will print publish ok in
serial monitor or else it will printpublish
failed*/
} else{
Serial.println("Publish failed");
```

```
}
void mqttconnect(){ if(!client.connected()){
Serial.print("Reconnecting client to "); Serial.println(server);
while(!!!client.connect(clientid,authMethod,
token)){ Serial.print("."); delay(500);
initManagedDevice();
Serial.println();
void wificonnect()//function defenition for wificonnect
Serial.println(); Serial.print("Connecting to "); WiFi.begin("vivo 1816",
"taetae95",6);//PASSING THE WIFI CREDIDENTIALS TO
ESTABLISH CONNECTION
while (WiFi.status() !=WL_CONNECTED){ delay(500);
Serial.print(".");
Serial.println(""); Serial.println("WiFi connected"); Serial.println("IP
address");
Serial.println(WiFi.localIP());
}
void initManagedDevice(){ if(client.subscribe(subscribetopic)){
Serial.println((subscribetopic)); Serial.println("subscribe to cmd OK");
Serial.println("subscribe to cmd failed");
}
void callback(char* subscribetopic,byte*payload,unsigned int
payloadLength)
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic); for(int i=0; i< payloadLength; i++){
//Serial.print((char)payload[i]); data3 +=(char)payload[i];
//Serial.println("dta: "+ data3);
//if(data3=="Near")
//{
//Serial.println(data3);
```

```
//digitalWrite(LED,HIGH);
//}
//else //{
//Serial.println(data3);
//digitalWrite(LED,LOW);//} data3="";
}
```

CIRCUIT DIAGRAM:



