## **SOURCE CODE**

TEAM ID	PNT2022TMID06149	
TOPIC	Smart Waste Management for	
	metropolitan cities	

## **CODE**

```
#include <WiFi.h>
#include <PubSubClient.h>
#include <LiquidCrystal I2C.h>
#include <ESP32Servo.h>
LiquidCrystal I2C lcd(0x27, 16, 2);
#define ORG "i5w9m5"
#define DEVICE TYPE "smart"
#define DEVICE ID "smartID"
#define TOKEN "123456789"
char server[] = ORG
".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/data/fmt/json";
char topic[] = "iot-2/cmd/led/fmt/String";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
//
WiFiClient wifiClient; // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);
#define echoPin 14
#define trigPin 12
#define led 2
Servo myservo;
long duration;
float distance;
void setup()
```

```
pinMode(12, OUTPUT);
  pinMode(14, INPUT);
  pinMode(2, OUTPUT);
  myservo.attach(13);
  Serial.begin(115200);
  lcd.init();
  lcd.backlight();
  lcd.setCursor(1, 0);
  lcd.print("");
  wifiConnect();
  mqttConnect();
}
float readcmCM()
digitalWrite(trigPin, LOW);
delayMicroseconds(2);
digitalWrite(trigPin, HIGH);
delayMicroseconds(10);
digitalWrite(trigPin, LOW);
duration = pulseIn(echoPin, HIGH);
return duration*0.034/2;
void loop()
lcd.clear();
publishData();
 delay(500);
if (!client.loop())
{
mqttConnect(); // function call to connect to IBM
}
/* -retrieving to cloud */
void wifiConnect()
{
Serial.print("Connecting to ");
Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
```

```
while (WiFi.status() != WL CONNECTED)
delay(500);
Serial.print(".");
Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
}
void mqttConnect()
if (!client.connected())
Serial.print("Reconnecting MQTT client to ");
Serial.println(server); while
(!client.connect(clientId, authMethod, token))
Serial.print(".");
delay(500);
initManagedDevice();
 Serial.println();
}
void initManagedDevice()
if (client.subscribe(topic))
Serial.println("IBM subscribe to cmd OK");
else
Serial.println("subscribe to cmd FAILED");
void publishData()
float cm = readcmCM();
if(distance>=100)
```

```
{
    Serial.println("distance:"+String(distance));
    digitalWrite(2, LOW);
    myservo.write(0);
  }
  else
  {
    Serial.println("ALERT!! The garbage has reached the
maximum capacity value");
    digitalWrite(2, HIGH);
    myservo.write(180);
  }
String payload = "{\"Warning!!\":\"";
payload += distance; payload += "left\" }";
Serial.print("\n");
Serial.print("Sending distance: "); Serial.println(cm);
 if(client.publish(publishTopic,(char*) payload.c_str()))
{
Serial.println("Publish OK");
}
else
Serial.println("Publish FAILED");
}
float inches = (cm / 2.54); //print on LCD
lcd.setCursor(0,0); lcd.print("Inches"); lcd.setCursor(4,0);
lcd.setCursor(12,0);
lcd.print("cm");
lcd.setCursor(1,1);
lcd.print(inches, 1);
lcd.setCursor(11,1);
lcd.print(cm, 1);
lcd.setCursor(14,1);
delay(1000);
lcd.clear(); }
```