## $\frac{\text{Delivery of Sprint-}}{\underline{2}}$

DATE	18 November 2022
TEAM ID	PNT2022TMID26856
PROJECT NAME	SMART WASTE MANAGEMENT FOR METROPOLITAN CITIES

## Code for Data Transfer from Sensors

#include <wifi.h></wifi.h>	// library for wifi
#include < Pub Sub Client. h> #include < Liquid Crystal_12 C. h > Liquid Crystal_12 C lcd(0x27, 20, 4);	// library for MQTT
// credentials of IBM Accounts	
#define ORG "ktymlx"  #define DEVICE_TYPE "new"  #define DEVICE_ID "09876"  #define TOKEN "Kamesh@2002"	// IBM organisation id // Device type mentioned in ibm watson iot platform // Device ID mentioned in ibm watson iot platform // Token
/ customise above values	<del></del>
	com"; // server name char publishTopic[] = "iot -2/evt/data/fmt/json"; char rpe and command is test format of strings char authMethod[] = "usetoken-
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;	//Client id
//	
WiFiClient wifiClient; PubSubClient client(server, 1883, wifiClient);	// creating instance for wificlient
#define ECHO_PIN 12 #define TRIG_PIN 13 float dist;	
void setup() { Serial begin(115200):	

pinMode(TRIG\_PIN, OUTPUT); pinMode(ECHO\_PIN, INPUT); //pir pin pinMode(4, INPUT); //ledpins pinMode(23, OUTPUT); pinMode(2, OUTPUT); pinMode(4, OUTPUT); pinMode(15, OUTPUT);

```
lcd.init(); lcd.backlight(); lcd.setCursor(1,
0); lcd.print(""); wifiConnect();
mqttConnect();
float readcmCM()
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2); digitalWrite(TRIG_PIN,
HIGH); delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW); int duration =
pulseIn(ECHO_PIN, HIGH); return
duration * 0.034 / 2;
void loop()
lcd.clear();
publishData(); delay(500);
if (!client.loop())
  {
   mqttConnect();
                                                                           // function call to connect to IBM
  }
                              _____-retrieving to cloud__
void wifiConnect()
Serial.print("Connecting to ");
Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
  {
   delay(500);
   Serial.print(".");
Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
void mqttConnect()
{
  if (!client.connected())
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
    (!client.connect(clientId, authMethod, token))
     {
       Serial.print("."); delay(500);
    initManagedDevice(); Serial.println();
void initManagedDevice()
  if (client.subscribe(topic))
    Serial.println("IBM subscribe to cmd OK");
```

```
else
        Serial.println("subscribe to cmd FAILED");
   void publishData()
   float cm = readcmCM();
    if(digitalRead(34))
                                                                           //PIR motion detection
     Serial.println("Motion
     Detected");
                     Serial.println("Lid
     Opened"); digitalWrite(15, HIGH);
   else
     digitalWrite(15, LOW);
   if(digitalRead(34)== true)
    if(cm <= 100)
                                                                        //Bin level detection
     digitalWrite(2, HIGH);
     Serial.println("High Alert!!!, Trash bin is about to be full");
     Serial.println("Lid Closed"); lcd.print("Full! Don't use"); delay(2000);
         lcd.clear();
                                digitalWrite(4,
                                                       LOW);
     digitalWrite(23, LOW);
   else if(cm > 150 && cm < 250)
     digitalWrite(4, HIGH);
     Serial.println("Warning!!, Trash is about to cross 50% of bin level"); digital Write(2,
     digital Write(23, LOW);
   else if(cm > 250 && cm <=400)
     digitalWrite(23, HIGH); Serial.println("Bin is
     available"); digitalWrite(2,LOW);
     digitalWrite(4, LOW);
     delay(10000); Serial.println("Lid Closed");
   else
    Serial.println("No motion detected");
   if(cm <= 100)
   digitalWrite(21,HIGH);
   String payload = "{\"High Alert!!\":\"";
   payload += cm; payload
   += "left\" }";
   Serial.print("\n");
   Serial.print("Sending payload: ");
   Serial.println(payload); if (client.publish(publishTopic, (char*) payload.c_str())) // if data is uploaded to cloud successfully, prints publish
ok or prints publish failed
   Serial.println("Publish OK");
```

```
}
}
if(cm <= 250)
{
digitalWrite(22,HIGH);
String payload = "{\"Warning!!\":\"";
payload += dist; payload += "left\" }";
Serial.print("\n");
Serial.print("Sending distance: "); Serial.println(cm); if(client.publish(publishTopic, (char*) payload.c_str()))
{
Serial.println("Publish OK");
}
else
{
Serial.println("Publish FAILED");
}
}
float inches = (cm / 2.54);  //print on LCD lcd.setCursor(0,0); lcd.print("Inches"); lcd.setCursor(4,0); lcd.setCursor(12,0); lcd.print("cm"); lcd.setCursor(1,1); lcd.print(inches, 1); lcd.setCursor(11,1); lcd.print(cm, 1); lcd.setCursor(14,1); delay(1000); lcd.clear();
}</pre>
```

## **Connection Diagram**

