#### IMPORT THE LIBRARIES

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
```

## READ DATASET AND DO PREPROCESSING

### **READ DATASET**

```
ag = pd.read_csv('/content/spam.csv',delimiter=',',encoding='latin-1')
ag.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy Available only	NaN	NaN	NaN
1	ham	Ok lar Joking wif u oni	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina	NaN	NaN	NaN
3	ham	U dun say so early hor U c already then say	NaN	NaN	NaN

## PREPROCESSING THE DATASET

ag.info()

<class 'pandas.core.frame.DataFrame'> RangeIndex: 5572 entries, 0 to 5571 Data columns (total 5 columns): Column Non-Null Count Dtype --- -----\_\_\_\_\_ 0 v1 5572 non-null object 5572 non-null 1 object 2 Unnamed: 2 50 non-null object Unnamed: 3 12 non-null 3 object

Unnamed: 4 6 non-null

object

dtypes: object(5)
memory usage: 217.8+ KB

```
X = ag.v2
Y = ag.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

X\_train,X\_test,Y\_train,Y\_test = train\_test\_split(X,Y,test\_size=0.15)

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences, maxlen=max_len)
```

# ADD LAYERS (LSTM, Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer.=.Dropout(0.5)(layer)
layer.=.Dense(1,name='out_layer')(layer)
layer.=.Activation('sigmoid')(layer)
model.=.Model(inputs=inputs,outputs=layer)
model.summary()
```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
<pre>activation_1 (Activation)</pre>	(None, 1)	0

\_\_\_\_\_\_

```
Total params: 96,337
Trainable params: 96,337
Non-trainable params: 0
```

\_\_\_\_\_

## COMPILE THE MODEL

```
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

### TRAIN AND FIT THE MODEL

model.fit(sequences\_matrix, Y\_train,batch\_size=128,epochs=10,validation\_split=0.2)

```
Epoch 1/10
   30/30 [================== ] - 12s 279ms/step - loss: 0.3311 - accuracy: 0
   Epoch 2/10
   Epoch 3/10
   30/30 [================== ] - 12s 417ms/step - loss: 0.0446 - accuracy: 0
   Epoch 4/10
   30/30 [================== ] - 10s 318ms/step - loss: 0.0348 - accuracy: 0
   Epoch 5/10
   30/30 [============== ] - 9s 304ms/step - loss: 0.0275 - accuracy: 0.
   Epoch 6/10
   Epoch 7/10
   30/30 [============== ] - 10s 348ms/step - loss: 0.0176 - accuracy: 0
   Epoch 8/10
   30/30 [================ ] - 9s 293ms/step - loss: 0.0147 - accuracy: 0.
   Epoch 9/10
   Epoch 10/10
   30/30 [================ ] - 12s 380ms/step - loss: 0.0098 - accuracy: 0
   <keras.callbacks.History at 0x7f8788200850>
                      一
           <>
               \bigcirc
                         <u>z</u>=
SAVE THE MODEL
                               SAVE THE MODEL
```

model.save('sms\_classifier.h5')

### PREPROCESSING THE DATASET

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = pad_sequences(test_sequences,maxlen=max_len)
```

## **TESTING THE MODEL**

Colab paid products - Cancel contracts here

✓ 0s completed at 11:04 PM