As our old twilio account has been expired. we have done again with the new twilio account (authentication id)

```
Image Preprocessing
#importing keras library
import keras
#importing the image data generator
from matplotlib import pyplot as plt
from keras.preprocessing.image import ImageDataGenerator
#Defining the parameter for image generator class
train datagen=ImageDataGenerator(rescale=1./255, shear range=0.2, rotati
on range=180,zoom range=0.2,horizontal flip=True)
test datagen=ImageDataGenerator(rescale=1./255)
#Applying image data generator functionality to train set
x train=train datagen.flow from directory(r'D:\IBM\Dataset\train set',
target size=(128,128),batch size=32,class mode='binary')
Found 436 images belonging to 2 classes.
#Applying image data generator functionality to test set
x test=test datagen.flow from directory(r'D:\IBM\Dataset\test set',
target size=(128, 128),batch size=32,class mode='binary')
Found 121 images belonging to 2 classes.
Model Building
#To define linear intialisation import Sequential
from keras.models import Sequential
#To add layers import Dense
from keras.layers import Dense
#To creat Convolution kernal import Convolution2D
from keras.layers import Convolution2D
#import Maxpooling layer
from keras.layers import MaxPooling2D
#import Flatten layer
from keras.layers import Flatten
import warnings
warnings.filterwarnings('ignore')
#initializing the model
model=Sequential()
#add convolution layer
model.add(Convolution2D(32,
(3,3),input shape=(128,128,3),activation='relu'))
#add maxpooling layer
```

model.add(MaxPooling2D(pool size=(2,2)))

model.add(Convolution2D(64,(3,3),activation='relu'))

#add convolution layer

```
#add maxpooling layer
model.add(MaxPooling2D(pool size=(2,2)))
#add convolution layer
model.add(Convolution2D(128,(3,3),activation='relu'))
#add maxpooling layer
model.add(MaxPooling2D(pool size=(2,2)))
#add convolution layer
model.add(Convolution2D(128,(3,3),activation='relu'))
#add maxpooling layer
model.add(MaxPooling2D(pool size=(2,2)))
#add flatten layer
model.add(Flatten())
model.add(Dense(512,activation='relu'))
model.add(Dense(1,activation='sigmoid'))
#configuring the learning process
model.compile(loss='binary crossentropy',optimizer="adam",metrics=["ac
curacy"])
#Training the model
r=model.fit(x train,epochs=10,validation data=x test)
Epoch 1/10
accuracy: 0.7018 - val loss: 0.2621 - val accuracy: 0.8760
Epoch 2/10
accuracy: 0.8716 - val loss: 0.0939 - val accuracy: 0.9917
Epoch 3/10
accuracy: 0.9243 - val loss: 0.0372 - val accuracy: 0.9917
Epoch 4/10
accuracy: 0.9450 - val loss: 0.0691 - val accuracy: 0.9669
Epoch 5/10
accuracy: 0.9427 - val loss: 0.0328 - val accuracy: 0.9917
Epoch 6/10
accuracy: 0.9358 - val loss: 0.0433 - val accuracy: 0.9917
Epoch 7/10
accuracy: 0.9335 - val loss: 0.0590 - val accuracy: 0.9752
Epoch 8/10
accuracy: 0.9358 - val loss: 0.0332 - val accuracy: 0.9917
Epoch 9/10
accuracy: 0.9289 - val loss: 0.0519 - val accuracy: 1.0000
Epoch 10/10
```

```
accuracy: 0.9106 - val loss: 0.0602 - val accuracy: 1.0000
#save the model
model.save("forestalert.h5")
Video Analysis
from twilio.rest import Client
#import load model from keras.model
from keras.models import load model
#import image from keras
from tensorflow.keras.preprocessing import image
import numpy as np
#import cv2
import cv2
#load the saved model
model=load model(r"forestalert.h5")
img=image.load img(r'D:\IBM\Dataset\test set\with fire\
Uttarakhand forest fire.jpeg')
x=image.img to array(img)
# res=cv2.resize(x,dsize=(150,150),interpolation=cv2.INTER CUBIC)
#expand the image shape
x=np.expand dims(x,axis=0)
from logging import WARNING
#import opency library
import cv2
#import numpy
import numpy as np
#import image function from keras
from keras.preprocessing import image
#import load model from keras
from keras.models import load model
#import client from twilio API
from twilio.rest import Client
#import playsound package
from playsound import playsound
import cv2
import numpy as np
from matplotlib import pyplot as plt
import tensorflow
from tensorflow.keras.preprocessing import image
from keras.models import load model
# Create a VideoCapture object and read from input file
# If the input is the camera, pass 0 instead of the video file name
video = cv2.VideoCapture(r'C:\Users\Dell\Downloads\Forest trees.mp4')
name=['no fire','with fire']
```

```
while(1):
 success,frame = video.read()
 cv2.imwrite("image.jpg",frame)
 img = tensorflow.keras.utils.load img("image.jpg", target size =
(128, 128))
 x = image.img_to_array(img)
 x = np.expand dims(x,axis = 0)
 pred = model.predict(x)
 pred = pred[0][0]
 if pred > 0.5:
   pred = 1
 else :
    pred = 0
 print(pred)
 cv2.putText(frame, "predicted class = "+str(name[pred]),
(50,50),cv2.FONT HERSHEY SIMPLEX,1,(255,255,255),1)
 if pred==1:
  account sid='ACab5b7ac22466b88a9cda7cf5414b750a'
  auth token='ala37c4aceac1ccf7b4a5a0b36bc62e9'
  client=Client(account sid,auth token)
  message=client.messages \
  .create(
      body='forest fire is detected, stay alert',
      #use twilio free number
      from = '+17088477470',
      #to number
      to='+918825826199')
  print(message.sid)
  print("Fire detected")
  print("SMS Sent!")
  from playsound import playsound
  playsound(r"C:\Users\Dell\Downloads\alarm.mp3")
  cv2.imshow('image',frame)
  if cv2.waitKey(0)\&0xFF == ord('a'):
        break
 else:
   print("No Danger")
   cv2.imshow('image',frame)
   if cv2.waitKey(0)\&0xFF == ord('a'):
        break
 video.release()
 cv2.destroyAllWindows()
1/1 [======= ] - 0s 37ms/step
0
No Danger
```

#### WITH FIRE

Here a video with forest fire is given as input

```
# Create a VideoCapture object and read from input file
# If the input is the camera, pass 0 instead of the video file name
video = cv2.VideoCapture(r'C:\Users\Dell\Downloads\fire in
forest.mp4'
name=['forest','with fire']
while(1):
 success,frame = video.read()
 cv2.imwrite("image.jpg",frame)
 img = tensorflow.keras.utils.load img("image.jpg", target size =
(128, 128)
 x = image.img to array(img)
 x = np.expand dims(x,axis = 0)
 pred = model.predict(x)
pred = pred[0][0]
 if pred > 0.5:
   pred = 1
 else :
    pred = 0
 print(pred)
 cv2.putText(frame, "predicted class = "+str(name[pred]),
(50,50),cv2.FONT_HERSHEY_SIMPLEX,1,(255,255,255),1)
 if pred==1:
  account sid='ACab5b7ac22466b88a9cda7cf5414b750a'
  auth token='ala37c4aceac1ccf7b4a5a0b36bc62e9'
  client=Client(account sid,auth token)
  message=client.messages \
  .create(
      body='forest fire is detected, stay alert',
      #use twilio free number
      from = '+17088477470',
      #to number
      to='+918825826199')
  print(message.sid)
  print("Fire detected")
  print("SMS Sent!")
  from playsound import playsound
```

## Output

#### With fire



### Without fire(forest)



# Fire prediction using Web camera

