IMPORT THE LIBRARIES

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
```

READ DATASET

```
ag = pd.read_csv('/content/spam.csv',delimiter=',',encoding='latin-1')
ag.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy Available only	NaN	NaN	NaN
1	ham	Ok lar Joking wif u oni	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina	NaN	NaN	NaN
3	ham	U dun say so early hor U c already then say	NaN	NaN	NaN

PREPROCESSING THE DATA

ag.info()

<class 'pandas.core.frame.DataFrame'> RangeIndex: 5572 entries, 0 to 5571 Data columns (total 5 columns): Non-Null Count Dtype # Column -----____ 0 5572 non-null object v1 1 5572 non-null object 2 Unnamed: 2 50 non-null object Unnamed: 3 12 non-null 3 object Unnamed: 4 6 non-null object dtypes: object(5)

memory usage: 217.8+ KB

```
X = ag.v2
Y = ag.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

Create Model and Add Layers (LSTM, Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
model = Model(inputs=inputs,outputs=layer)
model.summary()
```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
1stm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
<pre>activation_1 (Activation)</pre>	(None, 1)	0

Total params: 96,337 Trainable params: 96,337 Non-trainable params: 0

COMPILE THE MODEL

```
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

TRAIN AND FIT THE MODEL

```
model.fit(sequences_matrix, Y_train,batch_size=128,epochs=10,validation_split=0.2)
```

```
Epoch 1/10
30/30 [================== ] - 11s 282ms/step - loss: 0.2855 - accuracy: 0
Epoch 2/10
Epoch 3/10
30/30 [============= ] - 8s 271ms/step - loss: 0.0444 - accuracy: 0.
Epoch 4/10
30/30 [================ ] - 10s 319ms/step - loss: 0.0345 - accuracy: 0
Epoch 5/10
Epoch 6/10
30/30 [=============== ] - 8s 262ms/step - loss: 0.0226 - accuracy: 0.
Epoch 7/10
Epoch 8/10
Epoch 9/10
30/30 [============= ] - 8s 262ms/step - loss: 0.0107 - accuracy: 0.
Epoch 10/10
30/30 [================= ] - 8s 264ms/step - loss: 0.0103 - accuracy: 0.
<keras.callbacks.History at 0x7f07485f8e10>
```

SAVE THE MODEL

```
model.save('sms_classifier.h5')
```

PREPROCESSING THE TEST DATASET

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = pad_sequences(test_sequences,maxlen=max_len)
```

TESTING THE MODEL

```
print('Test set\n Loss: {:0.3f}\n Accuracy: {:0.3f}'.format(accr[0],accr[1]))
```

Test set Loss: 0.088 Accuracy: 0.982

Colab paid products - Cancel contracts here

✓ 0s completed at 20:22

×