ASSIGNMENT 4

Ultrasonic sensor simulation in Wokwi

```
Question:
```

Write a code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100cms send an "Alert" to

```
100cms send an "Alert" to
IBM cloud and display in the device recent events.
Code:
Sketch.ino:
#include <WiFi.h>
#include < PubSubClient.h>
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "9lxobn"//IBM ORGANITION ID
#define DEVICE_TYPE "ESP32PROJECT"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "ESP32"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "ESP32PROJECT" //Token
String data3;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/Data/fmt/json";
char subscribetopic[] = "iot-2/cmd/test/fmt/String";
char authMethod[] = "use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
```

PubSubClient client(server, 1883, callback ,wifiClient);


```
const int trigPin = 5;
const int echoPin = 18;
#define SOUND_SPEED 0.034
long duration;
float distance;
void setup() {
Serial.begin(115200);
pinMode(trigPin, OUTPUT);
pinMode(echoPin, INPUT);
wificonnect();
mqttconnect();
}
void loop()
{
digitalWrite(trigPin, LOW);
delayMicroseconds(2);
digitalWrite(trigPin, HIGH);
delayMicroseconds(10);
digitalWrite(trigPin, LOW);
duration = pulseIn(echoPin, HIGH);
distance = duration * SOUND_SPEED/2;
Serial.print("Distance (cm): ");
Serial.println(distance);
if(distance<100)
{
```

```
Serial.println("ALERT!!");
delay(1000);
PublishData(distance);
delay(1000);
if (!client.loop()) {
mqttconnect();
}
}
delay(1000);
}
void PublishData(float dist) {
mqttconnect();
String payload = "{\"Distance\":";
payload += dist;
payload += ",\"ALERT!!\":""\"Distance less than 100cms\"";
payload += "}";
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str())) {
Serial.println("Publish ok");
} else {
Serial.println("Publish failed");
}
}
void mqttconnect() {
```

```
if (!client.connected()) {
Serial.print("Reconnecting client to ");
Serial.println(server);
while (!!!client.connect(clientId, authMethod, token)) {
Serial.print(".");
delay(500);
}
initManagedDevice();
Serial.println();
}
}
void wificonnect()
{
Serial.println();
Serial.print("Connecting to ");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED) {
delay(500);
Serial.print(".");
}
Serial.println("");
Serial.println("WiFi connected");
Serial.println("IP address: ");
Serial.println(WiFi.localIP());
}
```

```
void initManagedDevice() {
if (client.subscribe(subscribetopic)) {
Serial.println((subscribetopic));
Serial.println("subscribe to cmd OK");
} else {
Serial.println("subscribe to cmd FAILED");
}
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic);
for (int i = 0; i < payloadLength; i++) {
//Serial.print((char)payload[i]);
data3 += (char)payload[i];
}
Serial.println("data: "+ data3);
data3="";
}
diagram.json:
"version": 1,
"author": "203 jayashree s",
"editor": "wokwi",
"parts": [
```

```
{ "type": "wokwi-esp32-devkit-v1", "id": "esp", "top": 23.33, "left": -106, "attrs": {} },
{ "type": "wokwi-hc-sr04", "id": "ultrasonic1", "top": -15.04, "left": 86.5, "attrs": {} }
],
"connections": [
[ "esp:TX0", "$serialMonitor:RX", "", [] ],
[ "esp:RX0", "$serialMonitor:TX", "", [] ],
["ultrasonic1:VCC", "esp:VIN", "red", ["v168.58", "h-279.11", "v-66"]],
[ "ultrasonic1:GND", "esp:GND.1", "black", [ "v0" ] ],
["ultrasonic1:TRIG", "esp:D5", "green", ["v0"]],
[ "ultrasonic1:ECHO", "esp:D18", "green", [ "v0" ] ]
]
}
libraries.txt:
# Wokwi Library List
# See https://docs.wokwi.com/guides/libraries
PubSubClient
Library Manager:
Installed Libraries:
PubSubClient
Wokwi simulation link:
https://wokwi.com/projects/347734035542312530
Circuit Diagram:
```



Output:

Wokwi output:

Connecting to ...

WiFi connected

IP address:

10.10.0.2

Reconnecting client to 9lxobn.messaging.internetofthings.ibmcloud.com

iot-2/cmd/test/fmt/String

subscribe to cmd OK

Distance (cm): 399.96

Distance (cm): 399.92

Distance (cm): 399.94

Distance (cm): 399.98

Distance (cm): 399.94

Distance (cm): 399.94

Distance (cm): 399.94

Distance (cm): 399.94

Distance (cm): 247.96

Distance (cm): 219.98

Distance (cm): 171.97

Distance (cm): 120.96

Distance (cm): 84.95

ALERT!!

Sending payload: {"Distance":84.95,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 78.98

ALERT!!

Sending payload: {"Distance":78.98,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 78.98

ALERT!!

Sending payload: {"Distance":78.98,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 89.98

ALERT!!

Sending payload: {"Distance":89.98,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 84.97

ALERT!!

Sending payload: {"Distance":84.97,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 86.96

ALERT!!

Sending payload: {"Distance":86.96,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 84.95

ALERT!!

Sending payload: {"Distance":84.95,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 84.95

ALERT!!

Sending payload: {"Distance":84.95,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 84.95

ALERT!!

Sending payload: {"Distance":84.95,"ALERT!!":"Distance less than 100cms"}

Publish ok


Distance (cm): 84.95

ALERT!!

Sending payload: {"Distance":84.95,"ALERT!!":"Distance less than 100cms"}

Publish ok

Wokwi Output Screen:



IBM cloud output:

