ProjectDevelopment-Deliveryof Sprint2

Date	5November2022
TeamID	PNT2022TMID30639
ProjectName	Project-IoTBasedSafetyGadgetfor
	ChildSafetyMonitoringand notification

LOGINandNOTIFIACATIONoftheIoTdeviceinParent'sWebApplicationforgettinginformationaboutChild'sStatus.

```
LOGIN:-
Coding, Output, Screenshot
<!DOCTYPEhtml>
<html><head>
<metaname="viewport"content="width=device-width,initial-scale=1">
<title>LoginPage</title>
<style>Body{fontfamily:Calibri,Helvetica,
       sansserif;background-color:#9FE2BF;
button{ backgroundcolor:#9FE2BF;
width:100%;
                      color:black;
padding:15px;
                 margin:10px0px;
border:none; cursor:pointer;
     }form{ border:
3pxsolid#f1f1f1;
```

```
input[type=text],input[type=password]
{ width:100%; margin:
8px0;padding:12px20px; display:inline-block; border:
2pxwhite;box-sizing:border-box;
button:hover
{opacity:0.7;
 .cancelbtn{ width:
auto;padding:10px
18px;margin:10px
5рх;
.container{ padding:
25px;backgroundcolor:#CCCCFF;
</style></head>
<body>
  <center><h1>LoginForm</h1></center>
  <form>
```

```
<divclass="container">
    <label>DeviceID/Number:</label>
      <inputtype="password"placeholder="EnterPassword"name="password"required>
      <label>E-Mail:</label>
      <inputtype="text"placeholder="EnterUsername"name="username"required>
      <label>Password:</label>
      <inputtype="password"placeholder="EnterPassword"name="password"required>
      <buttontype="submit">Login</button>
      <buttonclass="loginBtnloginBtn--facebook">LoginwithFacebook.</button>
      <buttonclass="loginBtnloginBtn--google">LoginwithGoogle./button>
      <inputtype="checkbox"checked">Rememberme
      <buttontype="button"class="cancelbtn">Cancel</button>Forgot<ahref="#">password?</a>
    </div>
 </form>
</body>
</html> OUTPUT:
```



NOTIFICATION:Coding,Output-Screenshot

#include<WiFi.h>//libraryforwifi#include<PubSubClient.h>//libraryforMQTTvoidcallback(ch ar*subscribetopic,byte*payload,unsignedintpayloadlength);

//----credentialsofIBMAccount-----

#defineORG"45z3o2"//IBMORGANIZATIONID

#defineDEVICE_TYPE"ESP32_Controller"//DEVICETYPEMENTIONEDINIOTWATSON

PLATFORM#defineDEVICE ID"bme2"//DEVICEIDMENTIONEDINIOTWATSONPLATEFORM


#define

```
TOKEN"OKZ+a@JfPWDOd6wBTi"//Tok
enStringdata3;floatdist;
//----customizetheabovevalue charserver[]=ORG
".messaging.internetofthings.ibmcloud.com";//servernamecharpublishtopic[]="ultrasonic/e
vt/Data/fmt/ison";/*topicnameandtypeofeventperformandformatinwhichdatatobe
send*/charsubscribetopic[]="ultrasonic/cmd/test/fmt/String";/*cmd REPRESENTCommandtupeand
COMMANDISTESTOFFORMATSTRING*/ charauthMethod[]="use-token-auth";//authentication methodchartoken[]=TOKEN;char
clientid[]="d:"ORG":"DEVICE TYPE":"DEVICE ID://CLIENTID
//
WiFiClientwifiClient;//creatinganinstanceforwificlient
PubSubClientclient(server,1883,callback,wifiClient);/*callingthepredefinedclientidby
passingparameterlikeserverid,portandwificredential*/intLED=4;inttrig=5;intecho=18;void
setup(){Serial.begin(115200);pinMode(trig,OUTPUT);pinMode(echo,INPUT);pinMode(LED,OUTPUT);
delay(10);Serial.println();wificonnect();mgttconnect();
voidloop()
{digitalWrite(trig,LOW);digital Write(trig,HIGH);delayMicrose
conds(10);digitalWrite(trig,LO W);floatdur=pulseIn(echo,HIG
H);floatdist=(dur*
0.0343)/2;Serial.print("distanc
```

```
eincm");
 Serial.println(dist);Publis
hData(dist);delay(1000);if
(!client.loop()){mqttconne ct();
/*.....*/voidPublishData(floatdist){mqttconnect();//functi
oncallforconnectingtoibm
String object; if (dis
t<100)
 digitalWrite(LED,HIGH);
Serial.println("noobjectisnear");object="Nea
r"; }
             else
{digitalWrite(LED,LOW);Serial.println("noobj ectfound");object="No";
 String payload="{\"distance\":";payload
+=dist;payload
+=",""\"object\":\"";payload+=object; payload+="\"}";
```

```
Serial.print("Sendingpayload:"); Serial.println(payload);
if(client.publish(publishtopic,(char*)payload.c str())){
 Serial.println("Publishok");
 }else{
  Serial.println("Publishfailed");
 }}voidmqttconnect(){i f(!client.connected()){
  Serial.print("Reconnectingclientto");
Serial.println(server); while(!!!client.connect(clientid,authMet hod,token)){Serial.print(".");
       delay(500);
  } initManagedDevice();
  Serial.println(); }}voidwificonnect()//functiondefenitionforwificonnect{
Serial.println();
Serial.print("Connectingto");
 WiFi.begin("vivo1816","taetae95",6);//PASSINGTHEWIFICREDIDENTIALSTOESTABLISH
CONNECTIONwhile(WiFi.status()!=WL CONNECTED){ delay(500);
  Serial.print(".");
 Serial.println("");Serial.println("
 WiFiconnected");Serial.println(
```

```
"IP
 address");Serial.println(WiFi.lo
calIP()); }void
initManagedDevice(){if(client.subsc ribe(subscribetopic)){Serial.println(
(subscribetopic));
  Serial.println("subscribetocmdOK");
 }else{
  Serial.println("subscribetocmdfailed");
}voidcallback(char*subscribetopic,byte*payload,unsignedintpayloadLength)
 Serial.print("callbackinvokedfortopic:");
Serial.println(subscribetopic);for(inti=0; i<payloadLength;i++){
//Serial.print((char)payload[i]);data3+=(char)paylo ad[i];
 //Serial.println(data3);
//digitalWrite(LED,LOW);//}data3="";
OUTPUT:
When child is not detected within the safezone with the help of IoT device\\
```



Childsstatusarenotifiedtoparentsdeviceusingcloudservice

