Project development phase

Sprint -4 Test case

Team ID	PNT2022TMID30704
Project Name	Virtual-Lifeguard for Swimming Pools to Detect the Active Drowning
Maximum Marks	4 Marks

```
#import necessary packages
import cv2
 import os
 import numpy as np
 from .utils import download_file
initialize = True
net = None
 dest_dir = os.path.expanduser('~') + os.path.sep + '.cvlib' + os.path.sep + 'object_detection' +
 os.path.sep + 'yolo' + os.path.sep + 'yolov3'
 classes = None
 #colors are BGR instead of RGB in python
 COLORS = [0,0,255], [255,0,0]

def populate_class_labels():
#we are using a pre existent classifier which is more reliable and more efficient than one
#we could make using only a laptop
    #The classifier should be downloaded automatically when you run this script
    class_file_name = 'yolov3_classes.txt'
    class_file_abs_path = dest_dir + os.path.sep + class_file_name
    url = 'https://github.com/Nico31415/Drowning-Detector/raw/master/yolov3.txt'
    if not os.path.exists(class_file_abs_path):
       download_file(url=url, file_name=class_file_name, dest_dir=dest_dir)
    f = open(class_file_abs_path, 'r')
    classes = [line.strip() for line in f.readlines()]
return classes
 def get_output_layers(net)
```

```
    #the number of output layers in a neural network is the number of possible
    #things the network can detect, such as a person, a dog, a tie, a phone...
    layer_names = net.getLayerNames()

    output_layers = [layer_names[i[0] - 1] for i in net.getUnconnectedOutLayers()]

    return output_layers


def draw_bbox(img, bbox, labels, confidence, Drowning, write_conf=False):

    global COLORS
    global classes

    if classes is None:
        classes = populate_class_labels()

    for i, label in enumerate(labels):

        #if the person is drowning, the box will be drawn red instead of blue
        if label == 'person' and Drowning:
            color = COLORS[0]
            label = 'DROWNING'
        else:
            color = COLORS[1]

        if write_conf:
            label += ' ' + str(format(confidence[i] * 100, '.2f')) + '%'
```

```
        #you only need to points (the opposite corners) to draw a rectangle. These points
        #are stored in the variable bbox
        cv2.rectangle(img, (bbox[i][0],bbox[i][1]), (bbox[i][2],bbox[i][3]), color, 2)

        cv2.putText(img, label, (bbox[i][0],bbox[i][1]-10), cv2.FONT_HERSHEY_SIMPLEX, 0.5, color, 2)

    return img

def detect_common_objects(image, confidence=0.5, nms_thresh=0.3):

    Height, Width = image.shape[:2]
    scale = 0.00392

    global classes
    global dest_dir

    #all the weights and the neural network algorithm are already preconfigured
    #as we are using YOLO

    #this part of the script just downloads the YOLO files
    config_file_name = 'yolov3.cfg'
    config_file_abs_path = dest_dir + os.path.sep + config_file_name

    weights_file_name = 'yolov3.weights'
     weights_file_abs_path = dest_dir + os.path.sep + weights_file_name

    url = 'https://github.com/Nico31415/Drowning-Detector/raw/master/yolov3.cfg'

    if not os.path.exists(config_file_abs_path):
        download_file(url=url, file_name=config_file_name, dest_dir=dest_dir)
```

```
url = 'https://pjreddie.com/media/files/yolov3.weights'

if not os.path.exists(weights_file_abs_path):
    download_file(url=url, file_name=weights_file_name, dest_dir=dest_dir)




global initialize
global net

if initialize:
    classes = populate_class_labels()
    net = cv2.dnn.readNet(weights_file_abs_path, config_file_abs_path)
    initialize = False

blob = cv2.dnn.blobFromImage(image, scale, (416,416), (0,0,0), True, crop=False)

net.setInput(blob)

outs = net.forward(get_output_layers(net))

class_ids = []
confidences = []
boxes = []

for out in outs:
    for detection in out:
        scores = detection[5:]
        class_id = np.argmax(scores)
        max_conf = scores[class_id]
        if max_conf > confidence:
```

```
        center_x  =  int(detection[0]  *  Width)
        center_y = int(detection[1] * Height)w
        = int(detection[2] * Width)
        h = int(detection[3] * Height)x
        = center_x - w / 2
        y = center_y - h / 2 class_ids.append(class_id)
        confidences.append(float(max_conf))
        boxes.append([x, y, w, h])


indices = cv2.dnn.NMSBoxes(boxes, confidences, confidence, nms_thresh)

bbox  =  []
label  =  []
conf = []

for i in indices:
    i = i[0]
    box = boxes[i]x
    = box[0]
    y = box[1] w
    = box[2]h =
    box[3]
    bbox.append([round(x), round(y), round(x+w), round(y+h)])
    label.append(str(classes[class_ids[i]]))
    conf.append(confidences[i])

return bbox, label, conf
```