```
#include <WiFi.h>
                              // library for wifi
#include < PubSubClient.h >
                                   // library for MQTT
#include <LiquidCrystal_I2C.h>
LiquidCrystal_I2C lcd(0x27, 20, 4);
//----- credentials of IBM Accounts -----
                                // IBM organisation id
#define ORG "wgsy43"
#define DEVICE_TYPE "NodeMCU"
                                       // Device type mentioned in ibm watson iot platform
#define DEVICE_ID "12345"
                               // Device ID mentioned in ibm watson iot platform
#define TOKEN "12345678"
                             // Token
//----- customise above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
                                                                  // server name
char publishTopic[] = "iot-2/evt/data/fmt/json";
                                                         // topic name and type of event
perform and format in which data to be send
char topic[] = "iot-2/cmd/led/fmt/String";
                                                       // cmd Represent type and command is
test format of strings
char authMethod[] = "use-token-auth";
                                                       // authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;
                                                             //Client id
WiFiClient wifiClient;
                                             // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);
#define ECHO_PIN 12
```

```
#define TRIG_PIN 13
float dist;
void setup()
{
Serial.begin(115200);
pinMode(LED_BUILTIN, OUTPUT);
pinMode(TRIG_PIN, OUTPUT);
 pinMode(ECHO_PIN, INPUT);
//pir pin
 pinMode(4, INPUT);
//ledpins
pinMode(23, OUTPUT);
pinMode(2, OUTPUT);
pinMode(4, OUTPUT);
 pinMode(15, OUTPUT);
lcd.init();
lcd.backlight();
lcd.setCursor(1, 0);
lcd.print("");
wifiConnect();
mqttConnect();
}
float readcmCM()
{
```

```
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
int duration = pulseIn(ECHO_PIN, HIGH);
return duration * 0.034 / 2;
}
void loop()
{
      lcd.clear();
publishData();
delay(500);
if (!client.loop())
 {
  mqttConnect();
                                // function call to connect to IBM
 }
}
/* -----*/
void wifiConnect()
{
Serial.print("Connecting to ");
Serial.print("Wifi");
```

```
WiFi.begin("Wokwi-GUEST", "", 6);
 while (WiFi.status() != WL_CONNECTED)
  {
   delay(500);
   Serial.print(".");
  }
 Serial.print("WiFi connected, IP address: ");
 Serial.println(WiFi.localIP());
}
void mqttConnect()
 {
  if (!client.connected())
   {
    Serial.print("Reconnecting MQTT client to ");
    Serial.println(server);
    while (!client.connect(clientId, authMethod, token))
     {
      Serial.print(".");
      delay(500);
     }
    initManagedDevice();
    Serial.println();
   }
void initManagedDevice()
 {
  if (client.subscribe(topic))
   {
    Serial.println("IBM subscribe to cmd OK");
```

```
}
  else
    Serial.println("subscribe to cmd FAILED");
   }
 }
void publishData()
{
 float cm = readcmCM();
                                     //pir motion detection
 if(digitalRead(34))
 {
  Serial.println("Motion Detected");
  Serial.println("Lid Opened");
  digitalWrite(15, HIGH);
 }
 else
  digitalWrite(15, LOW);
 }
if(digitalRead(34)== true)
{
 if(cm <= 100)
                                         //Bin level detection
 {
  digitalWrite(2, HIGH);
  Serial.println("High Alert!!!,Trash bin is about to be full");
  Serial.println("Lid Closed");
```

```
lcd.print("Full! Don't use");
 delay(2000);
 lcd.clear();
 digitalWrite(4, LOW);
 digitalWrite(23, LOW);
}
else if(cm > 150 && cm < 250)
{
 digitalWrite(4, HIGH);
 Serial.println("Warning!!,Trash is about to cross 50% of bin level");
 digitalWrite(2, LOW);
 digitalWrite(23, LOW);
}
else if(cm > 250 && cm <=400)
 digitalWrite(23, HIGH);
 Serial.println("Bin is available");
 digitalWrite(2,LOW);
 digitalWrite(4, LOW);
}
 delay(10000);
 Serial.println("Lid Closed");
}
else
{
 Serial.println("No motion detected");
}
```

```
if(cm <= 100)
{
digitalWrite(21,HIGH);
String payload = "{\"HighAlert\":\"";
payload += cm;
payload += "\" }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))
// if data is uploaded to cloud successfully, prints publish ok else prints publish failed
Serial.println("Publish OK");
}
}
if(cm > 150 && cm < 250)
{
digitalWrite(22,HIGH);
String payload = "{\"warning\":\"";
payload += cm;
payload += "\" }";
Serial.print("\n");
Serial.print("Sending distance: ");
```

```
Serial.println(cm);
if(client.publish(publishTopic, (char*) payload.c_str()))
Serial.println("Publish OK");
}
else
{
Serial.println("Publish FAILED");
}
}
if(cm > 250 \&\& cm <=400)
digitalWrite(21,HIGH);
String payload = "{\"Bin_is_available\":\"";
payload += cm;
payload += "\" }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str()))
// if data is uploaded to cloud successfully, prints publish ok else prints publish failed
{
Serial.println("Publish OK");
}
```