ASSIGNMENT -4

Distance Detection Using Ultrasonic Sensor

Assignment Date	19 October 2022
Student Name	PRASAD.M
Student Roll Number	1901140
Maximum Marks	2 Marks

Question-1:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to ibm cloud and display in device recent events.

WOKWI LINK :
https://wokwi.com/projects/345964118720643668 **C ODE:**

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt


void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);

//-------credentials of IBM Accounts------
#define ORG "f59trs"//IBM ORGANITION ID
#define DEVICE_TYPE "ultrasonicsensor"//Device type mentioned in ibm
watson IOT Platform
#define DEVICE_ID "distancedetection"//Device ID mentioned in ibm watson
IOT Platform
#define TOKEN "AlGMGaaF01nawa1QA3"
//Token String data3; float dist;

//-------- Customise the above values --------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server
Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
event perform and format in which data to be send char subscribetopic[] =
"iot-2/cmd/test/fmt/String";// cmd  REPRESENT command type AND
COMMAND IS TEST OF FORMAT STRING char authMethod[] = "use-
token-auth";// authentication method char token[] = TOKEN; char clientId[]
= "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id

//-----------------------------------------
WiFiClient wifiClient; // creating the instance for wificlient
```

```
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parameter like server id,portand
wificredential
 int LED = 4; int
trig = 5; int echo
= 18; void
setup()
{
Serial.begin(115200);
pinMode(trig,OUTPUT);
pinMode(echo,INPUT);
pinMode(LED, OUTPUT);
delay(10); wificonnect();
mqttconnect();
} void loop()// Recursive Function
{   digitalWrite(trig,LOW);
digitalWrite(trig,HIGH);
delayMicroseconds(10);
digitalWrite(trig,LOW);   float dur =
pulseIn(echo,HIGH);   float dist = (dur
* 0.0343)/2;
  Serial.print ("Distancein cm");
  Serial.println(dist);


  PublishData(dist);
delay(1000);   if
(!client.loop()) {
mqttconnect();
  }
}



/*.....retrieving to
Cloud.....*/

void PublishData(float dist) {   mqttconnect();//function call for
connecting to ibm
  /*      creating the String in in form JSon to update the data to ibm cloud
  */
  String object;
```

```
  if (dist <100)
  {
    digitalWrite(LED,HIGH);
    Serial.println("object is near");     object =
"Near";
  }   else
{
    digitalWrite(LED,LOW);
    Serial.println("no object found");     object = "No";
  }

  String payload = "{\"distance\":";
payload += dist;   payload += ","
"\"object\":\"";   payload += object;
payload += "\"}";


  Serial.print("Sending payload: ");
  Serial.println(payload);


  if (client.publish(publishTopic, (char*) payload.c_str())) {
Serial.println("Publish ok");// if it sucessfully upload data on the cloud then it
will print publish ok in Serial monitor or else it will print publish failed
  } else {
    Serial.println("Publish failed");
  }
   } void mqttconnect()
{
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");     Serial.println(server);
    while (!!!client.connect(clientId, authMethod, token)) {
Serial.print(".");       delay(500);
    }
     initManagedDevice();
     Serial.println();
  }
}
```

```
void wificonnect() //function defination for wificonnect {
  Serial.println();
  Serial.print("Connecting to ");

  WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to
establish the connection   while (WiFi.status() != WL_CONNECTED) {
delay(500);
    Serial.print(".");
  }
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}  void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {     Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}  void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength)
{

  Serial.print("callback invoked for topic: ");   Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {
//Serial.print((char)payload[i]);     data3 +=
(char)payload[i];
  }

//   Serial.println("data: "+ data3);
//   if(data3=="Near")
//   {
// Serial.println(data3);
// digitalWrite(LED,HIGH);

//   }

//   else
//   {
// Serial.println(data3);
```

```
// digitalWrite(LED,LOW);

//    }
data3="";


}
```

OUTPUT :

When object is not near to the ultrasonic sensor



Data sent to the IBM cloud device when the object is far



When object is nearer to the ultrasonic sensor



Data sent to the IBM cloud device when the object is near



https://wokwi.com/projects/345964118720643668