

Project Development Phase
Delivery of Sprint-2

TEAM ID	PNT2022TMID04297
PROJECT NAME	Smart Waste Management System For Metropolitan Cities

CODE:

```
#include <WiFi.h> //library for wifi
#include <PubSubClient.h> //library for MQTT
#include <LiquidCrystal_I2C.h>
LiquidCrystal_I2C lcd(0x27, 20, 4);
// credentials of IBM Accounts -
#define ORG "w5zj5y" //IBM organisation id
#define DEVICE_TYPE "abcde" // Device type mentioned in ibm watson iot platform
#define DEVICE_ID "1234" // Device ID mentioned in ibm watson iot platform
#define TOKEN "h_LkD2kKybTFkwyNSp" // Token
// customise above values -
char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // server name
char publishTopic[] = "iot-2/evt/data/fmt/json";
char topic[] = "iot-2/cmd/led/fmt/String"; // cmd Represent type and command is test format of strings
char authMethod[] = "use-token-auth"; // authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID; //Client id
//
WiFiClient wifiClient; // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient);
#define ECHO_PIN 12
#define TRIG_PIN 13
float dist;
void setup()
{
  Serial.begin(115200);
  pinMode(LED_BUILTIN, OUTPUT);
  pinMode(TRIG_PIN, OUTPUT);
  pinMode(ECHO_PIN, INPUT);
  //pir pin
  pinMode(4, INPUT);
  //ledpins
  pinMode(23,OUTPUT);
  pinMode(2,OUTPUT);
  pinMode(4,OUTPUT);
  pinMode(15,OUTPUT);

  lcd.init();
  lcd.backlight();
  lcd.setCursor(1,0);
  lcd.print("");
  wifiConnect();
```

```

mqttConnect();
}
float readcmCM()
{
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2);
digitalWrite(TRIG_PIN,HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
int duration =pulseIn(ECHO_PIN, HIGH);
return duration * 0.034 / 2;
}
void loop()
{
lcd.clear();
publishData();
delay(500);
if (!client.loop())
{
mqttConnect(); //function call to connect to IBM
}
}
/* -retrieving to cloud */
void wifiConnect()
{
Serial.print("Connecting to ");
Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
{
delay(500);
Serial.print(".");
}
Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
}
void mqttConnect()
{
if (!client.connected())
{
Serial.print("Reconnecting MQTT client to ");
Serial.println(server);
while(!client.connect(clientId, authMethod, token))
{
Serial.print(".");
delay(500);
}
initManagedDevice();
Serial.println();
}
}

```

```

void initManagedDevice()
{
if (client.subscribe(topic))
{
Serial.println("IBM subscribe to cmd OK");
}
else
{
Serial.println("subscribe to cmd FAILED");
}
}
void publishData()
{
float cm = readcmCM();
if(digitalRead(34)) //PIR motion detection
{
Serial.println("Motion Detected");
Serial.println("Lid Opened");
digitalWrite(15, HIGH);
}
else
{
digitalWrite(15, LOW);
}
if(digitalRead(34)== true)
{
if(cm <= 100) //Bin level detection
{
digitalWrite(2, HIGH);
Serial.println("High Alert!!!,Trash bin is about to be full");
Serial.println("Lid Closed");
lcd.print("Full! Don't use");
delay(2000);
lcd.clear();
digitalWrite(4, LOW);
digitalWrite(23, LOW);
}
else if(cm > 150 && cm < 250)
{
digitalWrite(4, HIGH);
Serial.println("Warning!!,Trash is about to cross 50% of bin level");
digitalWrite(2,LOW);
digitalWrite(23, LOW);
}
else if(cm > 250 && cm <=400)
{
digitalWrite(23, HIGH);
Serial.println("Bin is available");
digitalWrite(2,LOW);
digitalWrite(4, LOW);
}
}
}

```

```

delay(10000);
Serial.println("Lid Closed");
}
else
{
Serial.println("No motion detected");
}
if(cm <= 100)
{
digitalWrite(21,HIGH);
String payload = "{\"High Alert!!\":\":";
payload += cm;
payload += "left\" }";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c_str())) // if data is uploaded to cloud
successfully,prints publish ok or prints publish failed
{
Serial.println("Publish OK");
}
}
if(cm <= 250)
{
digitalWrite(22,HIGH);
String payload = "{\"Warning!!\":\":";
payload += dist;
payload += "left\" }";
Serial.print("\n");
Serial.print("Sending distance: ");
Serial.println(cm);
if(client.publish(publishTopic,(char*) payload.c_str()))
{
Serial.println("Publish OK");
}
else
{
Serial.println("Publish FAILED");
}
}
float inches = (cm / 2.54); //print on LCD
lcd.setCursor(0,0);
lcd.print("Inches");
lcd.setCursor(4,0);
lcd.setCursor(12,0);
lcd.print("cm");
lcd.setCursor(1,1);
lcd.print(inches, 1);
lcd.setCursor(11,1);
lcd.print(cm, 1);
lcd.setCursor(14,1);

```

```
delay(1000);  
lcd.clear();  
}
```

OUTPUT:

