

# Smart Waste Management

---

## Literature survey:

- ✚ Mohd Helmy Abd Wahab, Aeslina Abdul Kadir, Mohd Razali Tomari and Mohamad Hairol Jabbar proposed a Smart Recycle Bin that caters for recycling glass, paper, aluminium can and plastic products. It automatically evaluates the value of the wastes thrown accordingly and provide 3R card. The recycle system enables collection of points for performing a disposal activity into designated recycle bins. Such system encourages recycling activities by allowing the points to be redeemable for products or services. The system records the data related to the disposal activities, disposed material, identification of the user and points collected by the user. The user has to touch his card to the specified RFID reader at the recycle bin. Recycle bin doors open and user puts waste one by one. A microcontroller processes information about his user ID and number of wastes and send to a database server. The data base server calculates the user points and updates it. The system provides user login to an online system to check his total points
- ✚ Mohammad Aazam, Marc St-Hilaire, Chung-Horng Lung, Ioannis Lambadaris (2016) provides the idea of sensors-based waste bins, capable of notifying waste level status. An automatic waste bin and make use of cloud computing paradigm to evolve a more robust and effective smart waste management mechanism. Waste management is linked to different stakeholders, including recyclers, importers and exporters, food industry, healthcare, research, environment protection and related organizations, and tourism industry Mohammad Aazam et al proposed Cloud SWAM, in which each bin is equipped with sensors to notify its waste level. Different bins for each category of waste, namely: organic, plastic/paper/bottle, and metal. In this way, each type of waste is already separated and through the status, it is known that how much of waste is collected and of what type. The availability of data stored in the cloud can be useful for different entities and stakeholders in different ways. Analysis and planning can start from as soon as waste starts gathering and up to when recycling and import/export related matters are conducted. The system Cloud SWAM provides Timely waste collection. Timely and efficient way of collecting waste leads to better health, hygiene, and disposal. The system provides shortest path to the location of waste bins. So the collectors can plan a better and fuel efficient route. Recycling and disposal by the system s uses separate smart bins for each type of waste. So the stakeholders will be able to see through the cloud and analyse type of waste and its magnitude. So they can do better arrangements and efficient ways of recycling can be adopted in a dynamic way. Resource management by Cloud SWAM is based on the waste generation trends of a particular city and/or area, resources can be effectively managed since the data is available live through the cloud. Food industry planning can done through the Cloud SWAM. Food industry can plan according to the trends of a certain locality. In this way, not only waste material can be minimized, but also, food trends and habits of an area can be coped in a much more operative way. Taxation

with Cloud SWAM keeping track of each kind of waste, better taxation and fine imposition can be performed on unnecessary waste generation. Big Data practices can be used to reduce waste generation and improve its management. Various healthcare stakeholders can take benefit from the gathered waste management data and foresee what type of diseases a particular locality is more prone to and how to prevent from certain types of insects and bugs from breeding. Waste-based energy production means generating energy from waste in the form of electricity or heat.

- 🌈 Keerthana b et al designed internet of bins for trash management in India. The smart TRASH management system using sensor, microcontroller and other modules ensures emptying of dustbins appropriately when the garbage level reaches its maximum. Two threshold limits are set for the bins and an alert message is sent to the van that collects the trash if the waste amount reaches these thresholds. The system further allows the people to drop down the trash bags into the bins till it reaches the threshold limit .It waits for the acknowledgment from the van to clear off the bin and if the acknowledgment is not received it is sent again when it reaches threshold limit and the bin gets locked. When bin gets locked it displays the message "Overloaded". Then the dustbin will be monitored for a specific time and when not cleared within certain time limit, then a message will be sent to the higher authority who can take appropriate action
- 🌈 Fachmin F olianto, Yong Sheng Low and Wai Leong Yeow proposed Smart bin system has 3 –tier architecture. The ultra sound sensor installed in every Smartbin senses bin fullness and report readings and sensor statuses. The sensor reading is transmitted to the gateway nod which is installed in every sensor cluster. It forwards the information to the backend server. The analytics module in the back end server analyses data collected by the bin sub system. The analytics module processes fullness readings, compares against predefined rules, and generates event upon exceeding threshold. The bin sub-system sends information to the workstation and it shows meaningful information to users through a graphical user interface.
- 🌈 Belal Chowdhury and Morshed U. Chowdhury designed five layer architecture for RFID and sensor based waste management system. The layers are named as physical layer, middleware layer, process layer, data access layer and user interface layer. The physical layer consists of the actual RFID hardware components and it includes RFID waste tag, reader and antennas. Middleware layer is acting as the interface between the RFID reader, load cell sensor and waste management service providers (i.e., waste collectors, and municipalities) IT system. The important element of RFID and load cell sensor systems is middleware layer, which is viewed as the central nervous system from the waste management system perspective. This layer enables waste management service provider's (e.g., waste collector) a quick connectivity with RFID readers and load cell sensors and also the layer lowers the volume of information that waste management system applications need to process, by grouping and filtering raw RFID and load cell data from readers and sensors respectively. An application-level interface is provided by middleware layer for managing RFID readers, and load cell sensors for processing large volumes of waste data for their applications. The middleware layer is responsible for monitoring physical layer components. The Process Layer provides RFID and sensor based waste management system (business) processes that provide real-time integration into their existing systems.

Also this layer enables data mapping, formatting, business rule execution and service interactions with databases. The data access layer is consisting of a RDBMS (Relational Database Management System) and applications that allow waste management service providers to create an RFID and sensor "events". This data access layer interacts with the SQL server and includes a data query/loading approach using SQL and customized data (i.e., customer/household information) that are presented to the waste management service provider (i.e., waste collector) for fast and accurate waste (e.g., garbage, recycling, and green) identification. Finally, the user interface layer is composed of an extensible GUI (graphical user interface), which allows RFID devices (e.g., waste tag, reader) and load cell sensors in a uniform, user-friendly way to work seamlessly in a Windows environment.

Mohd Helmy Abd Wahab, Aeslina Abdul Kadi