

ASSIGNMENT-4

Date	30 October 2022
Team ID	PNT2022TMID39619
Name	Surya M
Student Roll Number	510619104072
Maximum Marks	2 Marks

Problem Statement:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cm send "alert" to IBM cloud and display in device recent events.

CODE :

```
1 #include <WiFi.h> //library for wifi
2 #include <PubSubClient.h> //library for mqtt
3
4
5 void callback(char* topic, byte* payload, unsigned int payloadLength);
6
7 //----- credentials of IBM Accounts -----
8
9 #define ORG "4h0u1p" //IBM ORG/UNITID ID
10 #define DEVICE_TYPE "ULTRASONIC" //Device type mentioned in the Watson IoT Platform
11 #define DEVICE_ID "DISTANCEDETECT" //Device ID mentioned in the Watson IoT Platform
12 #define TOKEN "w00s7PRj25egWdta" //Token
13 String data3;
14 float dist;
15
16
17 //----- Customize the above values -----
18 char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // Server Name
19 char publishTopic[] = "iot-2/evt/data/rst/json"; // Topic name and type of event perform and format in which data to be send
20 char subscribeTopic[] = "iot-2/cmd/test/rst/string"; // cmd REPRESENT command type AND COMMAND IS TEXT OR COMPAT STRING
21 char authMethod[] = "one-token-auth"; // authentication method
22 char token[] = TOKEN;
23 char clientId[] = "dt:" ORG ":" DEVICE_TYPE ":" DEVICE_ID //client id
24
25
26 //-----
27 WiFiClient wifiClient; // creating the instance for wifiClient
28 PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined client id by passing parameter like server id,port and wifi credentials
29
30 int LED = 4;
31 int trig = 5;
32 int echo = 18;
33 void setup()
34 {
35   Serial.begin(115200);
```

esp32-blink.ino • diagram.json • libraries.txt • Library Manager ▾

```

36 pinMode(trig,OUTPUT);
37 pinMode(echo,INPUT);
38 pinMode(LED, OUTPUT);
39 delay(10);
40 wificonnect();
41 mqttconnect();
42 }
43 void loop()// Recursive Function
44 {
45
46     digitalWrite(trig,LOW);
47     digitalWrite(trig,HIGH);
48     delayMicroseconds(10);
49     digitalWrite(trig,LOW);
50     float dur = pulseIn(echo,HIGH);
51     float dist = (dur * 0.0343)/2;
52     Serial.print ("Distance in cm");
53     Serial.println(dist);
54
55
56     PublishData(dist);
57     delay(1000);
58     if (!client.loop()) {
59         mqttconnect();
60     }
61 }
62
63
64
65 /*.....Retrieving to Cloud.....*/
66
67 void PublishData(float dist) {
68     mqttconnect();//function call for connecting to ibm
69     /*
70     |   creating the String in in form JSON to update the data to ibm cloud

```

```

70     |   creating the String in in form JSON to update the data to ibm cloud
71     */
72     String object;
73     if (dist < 100)
74     {
75         digitalWrite(LED,HIGH);
76         Serial.println("object is near");
77         object = "Near";
78     }
79     else
80     {
81         digitalWrite(LED,LOW);
82         Serial.println("no object found");
83         object = "No";
84     }
85
86     String payload = "{\"distance\":";
87     payload += dist;
88     payload += "," " \"object\":";
89     payload += object;
90     payload += "\"}";
91
92
93     Serial.print("Sending payload: ");
94     Serial.println(payload);
95
96
97
98

```


```
99
100 if (client.publish(publishTopic, (char*) payload.c_str())) {
101     Serial.println("Publish ok");// If it successfully upload data on the cloud then it will print publish ok in Serial monitor or else it will print publish failed
102 } else {
103     Serial.println("Publish failed");
104 }
105
106 void mqttconnect() {
107     if (!client.connected()) {
108         Serial.print("Reconnecting client to ");
109         Serial.println(server);
110         while (!client.connect(clientId, authmethod, token)) {
111             Serial.print(".");
112             delay(500);
113         }
114
115         initManagedDevice();
116         Serial.println();
117     }
118 }
119 void wificonnect() //function definition for wificonnect
120 {
121     Serial.println();
122     Serial.print("connecting to ");
123
124     WiFi.begin("Wool-QWERT", "");//passing the wifi credentials to establish the connection
125     while (WiFi.status() != WL_CONNECTED) {
126         delay(500);
127         Serial.print(".");
128     }
129     Serial.println("");
130     Serial.println("wifi connected");
131     Serial.println("IP address: ");
132     Serial.println(WiFi.localIP());
```

```
123
124   WiFi.begin("wokwi-GUEST", "", 6); // passing the wifi credentials to establish the connection
125   while (WiFi.status() != WL_CONNECTED) {
126       delay(500);
127       Serial.print(".");
128   }
129   Serial.println("");
130   Serial.println("WiFi connected");
131   Serial.println("IP address: ");
132   Serial.println(WiFi.localIP());
133 }
134
135 void initManagedDevice() {
136     if (client.subscribe(subscribetopic)) {
137         Serial.println(subscribetopic);
138         Serial.println("subscribe to cmd OK");
139     } else {
140         Serial.println("subscribe to cmd FAILED");
141     }
142 }
143
144 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
145 {
146     Serial.print("callback invoked for topic: ");
147     Serial.println(subscribetopic);
148     for (int i = 0; i < payloadLength; i++) {
149         // Serial.print((char)payload[i]);
150         data3 += (char)payload[i];
151     }
152 }
153
154 // Serial.println("data: " + data3);
155 // if(data3=="Near")
156 // {
157 // Serial.println(data3);
158 // }
```

```
esp32-blink.ino • diagram.json • libraries.txt • Library Manager
142 }
143
144 void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
145 {
146
147     Serial.print("callback invoked for topic: ");
148     Serial.println(subscribetopic);
149     for (int i = 0; i < payloadLength; i++) {
150         //Serial.print((char)payload[i]);
151         data3 += (char)payload[i];
152     }
153
154     // Serial.println("data: "+ data3);
155     // if(data3=="Near")
156     // {
157     // Serial.println(data3);
158     // digitalWrite(LED,HIGH);
159
160     // }
161
162     // else
163     // {
164     // Serial.println(data3);
165     // digitalWrite(LED,LOW);
166
167     // }
168     data3="";
169
170
171 }
```

OUTPUT:

when object is near to the ultrasonic sensor



Data sent to the IBM Cloud Device when the object is near