

### SPRINT-3

Date	15 November 2022
Team ID	PNT2022TMID48307
Project Name	Industry Specific Intelligence Fire Management System

```
#include <WiFi.h>
#include <Wire.h>
#include <SPI.h>
#include "ThingSpeak.h"
#include
<WiFiClient.h>

unsigned long myChannelNumber = 2;    const char *
myWriteAPIKey = "25V40ZAPI6KIZFGY";  int LED_PIN =
32;
// the current reading from the input pin    int
BUZZER_PIN= 12;
const int  mq2 = 4;    int
value = 0;

//Flame int flame_sensor_pin = 10 ;
// initializing pin 10 as the sensor digital output pin int flame_pin = HIGH ; // current
state of sensor

char ssid[] = "SABITHA";
char pass[] = "SABITHA";
WiFiClient client;
#define PIN_LM35 39
#define ADC_VREF_mV 3300.0
#define ADC_RESOLUTION 4096.0
#define RELAY_PIN 17
```

```

#define RELAY_PIN1 27
void setup()
{
  Serial.begin(115200);
  pinMode(RELAY_PIN, OUTPUT);
  pinMode(RELAY_PIN1, OUTPUT);
  Serial.print("Connecting to ");
  Serial.println(ssid);  WiFi.begin(ssid, pass);
  int wifi_ctr = 0;
  while (WiFi.status() != WL_CONNECTED)
  {
    delay(1000);    Serial.print(".");
  }
  Serial.println("WiFi connected");
  ThingSpeak.begin(client);  pinMode(LED_PIN,
  OUTPUT);  pinMode(mq2, INPUT);  pinMode
  ( flame_sensor_pin , INPUT );
  // declaring sensor pin as input pin for Arduino  pinMode(BUZZER_PIN, OUTPUT);
}

void temperature()
{
  int adcVal = analogRead(PIN_LM35);  float
  milliVolt = adcVal *
  (ADC_VREF_mV / ADC_RESOLUTION);
  float tempC = milliVolt / 10;
  Serial.print("Temperature: ");
  Serial.print(tempC);    Serial.print("°C");  if(tempC
  > 60)
  {
    Serial.println("Alert");
    digitalWrite(BUZZER_PIN, HIGH);
  // turn on
  } else
  {

```

```

    digitalWrite(BUZZER_PIN, LOW);
// turn on
}
    int x = ThingSpeak.writeField(myChannelNumber,1, tempC, myWriteAPIKey);
}
void GasSensors()
{
    //mq2

    int gassensorAnalogmq2 = analogRead(mq2);
    Serial.print("mq2 Gas Sensor: ");
    Serial.print(gassensorAnalogmq2);
    Serial.print("\t");
    Serial.print("\t");
    Serial.print("\t");

    if (gassensorAnalogmq2 > 1500)
    {
        Serial.println("mq2Gas");    Serial.println("Alert");
        digitalWrite(RELAY_PIN1, HIGH);
        // turn on fan 10 seconds  delay(100);
    } else
    {
        Serial.println("No mq2Gas");
        digitalWrite(RELAY_PIN1,
LOW);
        // turn off fan 10 seconds  delay(100);

    }

    Int a = ThingSpeak.writeField(myChannelNumber,4,gassensorAnalogmq2,
myWriteAPIKey);

}

void flamesensor()

```

```

{ flame_pin = digitalRead ( flame_sensor_pin ) ;
// reading from the sensor if
(flame_pin == LOW )
// applying condition
{
Serial.println ( " ALERT: FLAME IS DETECTED" ) ;
digitalWrite (BUZZER_PIN, HIGH ) ;
// if state is high, then turn high the BUZZER
} else
{
Serial.println ( " NO FLAME DETECTED " ) ;
digitalWrite (BUZZER_PIN , LOW ) ;
// otherwise turn it low
} int value = digitalRead(flame_sensor_pin);
// read the analog value from sensor  if
(value ==LOW)
{
Serial.print("FLAME");
digitalWrite(RELAY_PIN, HIGH);
} else
{
Serial.print("NO FLAME");
digitalWrite(RELAY_PIN, LOW);
}
} void loop()
{
temperature(); GasSensors(); flamesensor();
}

```