Assignment-4

Write a code and make connections in wokwi for ultrasonic sensor. When ever distance Is less than 100cm send "alert" to ibm cloud and display in device recent events.

Solution:

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
                  // what pin we're connected to
#define EchoPIN 4
#define TrigPIN 2
#define LED 5
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "8p2x1c"//IBM ORGANITION ID
#define DEVICE_TYPE "ABCDE"//Device type mentioned in ibm watson IOT
Platform
#define DEVICE ID "1234"//Device ID mentioned in ibm watson IOT
Platform
#define TOKEN "12345678" //Token
String data3;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";//
Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and
type of event perform and format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";//
cmd REPRESENT command type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
float dist,dur;
String data;
//....-
```

```
WiFiClient wifiClient; // creating the instance for wificlient PubSubClient client(server, 1883, callback ,wifiClient); //calling the predefined client id by passing parameter like server id,portand wificredential
```

```
void setup()// configureing the ESP32
 Serial.begin(115200);
 pinMode(TrigPIN, OUTPUT);
 digitalWrite(TrigPIN, LOW);
 pinMode(EchoPIN, INPUT);
 pinMode(LED,OUTPUT);
 delay(10);
 Serial.println();
 wificonnect();
 mqttconnect();
}
void loop()// Recursive Function
{
 digitalWrite(TrigPIN, HIGH);
 delayMicroseconds(10);
 digitalWrite(TrigPIN, LOW);
 dur = pulseIn(EchoPIN, HIGH);
 dist= dur *0.034 / 2;
if(dist<100)</pre>
 {
    data="alert";
    digitalWrite(LED,HIGH);
  }
 else{
    data="safe";
    digitalWrite(LED,LOW);
 }
 PublishData(dist);
 delay(1000);
 if (!client.loop()) {
    mqttconnect();
 }
}
```

```
/*....retrieving to
Cloud.....*/
void PublishData(float dist) {
 mqttconnect();//function call for connecting to ibm
    creating the String in in form JSon to update the data to ibm
cloud
 */
 String payload = "{\"distance\":";
 payload += dist;
 payload += "," "\"msg\":\"";
 payload += data;
 payload += "\"}";
 Serial.print("Sending payload: ");
 Serial.println(payload);
 if (client.publish(publishTopic, (char*) payload.c_str())) {
   Serial.println("Publish ok");// if it successfully upload data on
the cloud then it will print publish ok in Serial monitor or else it
will print publish failed
  } else {
   Serial.println("Publish failed");
}
void mqttconnect() {
 if (!client.connected()) {
   Serial.print("Reconnecting client to ");
   Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
     Serial.print(".");
     delay(500);
   }
    initManagedDevice();
    Serial.println();
 }
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
```

```
WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to
establish the connection
  while (WiFi.status() != WL_CONNECTED) {
    delay(500);
    Serial.print(".");
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
  }
}
void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength)
{
}
            Editing Ultrasonic Distance Sensor
            Distance:
           Publish ok
           Sending payload: {"distance":93.98, "msg": "alert"}
           Publish ok
           Sending payload: {"distance":93.98, "msg": "alert"}
           Publish ok
            Sending payload: {"distance":93.98,"msg":"alert"}
```

Publish ok

```
#include <WiFi.h>//library for wifi
2
   #include <PubSubClient.h>//library for MQtt
    #define EchoPIN 4
                          // what pin we're connected to
3
    #define TrigPIN 2
4
5
    #define LED 5
    //DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of dht connected
    void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
8
9
    //----credentials of IBM Accounts-----
10
11
12
    #define ORG "8p2xlc"//IBM ORGANITION ID
13
    #define DEVICE_TYPE "ABCDE"//Device type mentioned in ibm watson IOT Platform
14
    #define DEVICE_ID "1234"//Device ID mentioned in ibm watson IOT Platform
15
    #define TOKEN "12345678"
                                 //Token
    String data3;
16
17
18
19
20
    //----- Customise the above values ------
    char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
21
22
    char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and format in which data
    char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT command type AND COMMAND IS TEST OF FORM
23
    char authMethod[] = "use-token-auth";// authentication method
24
25
    char token[] = TOKEN;
26
    char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
27
    float dist, dur;
28
    String data;
29
    //-----
    WiFiClient wifiClient; // creating the instance for wificlient
30
31
    PubSubClient client(server, 1883, callback ,wifiClient); //calling the predefined client id by passing parameter
32
33
    void setup()// configureing the ESP32
34
35
36
      Serial.begin(115200);
37
       pinMode(TrigPIN, OUTPUT);
38
       digitalWrite(TrigPIN, LOW);
39
       pinMode(EchoPIN, INPUT);
       pinMode(LED,OUTPUT);
40
41
      delay(10);
42
      Serial.println();
```

WokwiLink: https://wokwi.com/projects/347662137833816659

IBM Cloud

Device Recent Events

	Device ID	Status	Device Type	Class ID	Date Added	Descriptive Location
٧	1234	 Connected 	ABCDE	Device	Nov 7, 2022 6:13 PM	
	Identity	Device Information	Recent Events	State L	ogs	

The recent events listed show the live stream of data that is coming and going from this device.

Event	Value	Format	Last Received	
Data	["distance":93.99,"msg":"alert"]	json	a few seconds ago	
Data	{"distance":93.98,"msg":"alert"}	json	a few seconds ago	
Data	{"distance":93.98,"msg":"alert"}	json	a few seconds ago	