

▼ 1. Required libraries are imported

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
import keras
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import to_categorical, pad_sequences
from keras.callbacks import EarlyStopping
%matplotlib inline
```

2. Read dataset and pre-processing

```
df = pd.read_csv('/content/archive.zip',delimiter=',',encoding='latin-1')
df.head()
```

	v1	v2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy.. Available only ...	NaN	NaN	NaN
1	ham	Ok lar... Joking wif u oni...	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina...	NaN	NaN	NaN
3	ham	U dun say so early hor... U c already then say...	NaN	NaN	NaN


```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
```

```
df.shape
```

```
(5572, 2)
```

```
#plot the ham and spam messages to understand the distribution
df['v1'].value_counts().plot(kind='bar')
plt.xlabel('Label')
plt.title('Number of ham and spam messages')
```

Text(0.5, 1.0, 'Number of ham and spam messages')



```
X = df.v2
Y = df.v1
#label encoding for Y
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

3. Train-test split

```
#split into train and test sets
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.20)
```

4. Tokenizer

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = keras.utils.pad_sequences(sequences,maxlen=max_len)
```

5. Add Layers(LSTM, Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer)
layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer)
layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer)
layer = Activation('sigmoid')(layer)
```

6. Create Model

```
model = Model(inputs=inputs,outputs=layer)
```

7. Compile the Model

```
model.summary()
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])
```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	[(None, 150)]	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)	(None, 256)	0
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
activation_1 (Activation)	(None, 1)	0
Total params: 96,337		
Trainable params: 96,337		
Non-trainable params: 0		

8. Fit the Mode

```
model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,validation_split=0.2,callbacks
```

```
Epoch 1/10
28/28 [=====] - 10s 256ms/step - loss: 0.3522 - accuracy: 0
Epoch 2/10
28/28 [=====] - 7s 239ms/step - loss: 0.1025 - accuracy: 0.9
<keras.callbacks.History at 0x7f31fc774550>
```



9. Save the Mode

```
model.save('spam_lstm_model.h5')
```

10. Test the Model

```
#processing test data
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = keras.utils.pad_sequences(test_sequences,maxlen=max_len)
```

```
#evaluation of our model
accr = model.evaluate(test_sequences_matrix,Y_test)
print('Test set\n Loss: {:.3f}\n Accuracy: {:.3f}'.format(accr[0],accr[1]))
```

```
35/35 [=====] - 1s 19ms/step - loss: 0.0554 - accuracy: 0.987
Test set
Loss: 0.055
Accuracy: 0.987
```

[Colab paid products](#) - [Cancel contracts here](#)

✓ 0s completed at 10:04 PM

