#### Project Design Phase-II Functional Requirement Template

Date	11 November 2022
Team ID	PNT2022TMID45510
Project Name	Project – Real -Time Communication System Powered by AI For Specially Abled
Maximum Marks	2 Marks

# <u>Functional Requirements:</u>

- Here, the Desktop along with the Camera is presented as black box.
- Deaf/Dumb is the person, who will show different signs based on the type ofinformation being conveyed.
- Normal Person is the passive user of the desktop.

### The <u>System requirements</u> that are required are specified below,

- Deaf/Dumb person should be able to perform a sign that represents digit/number.
- Deaf/Dumb person should be able to perform a sign that represents a character.
- Deaf/Dumb person should be able to perform a sign, where group of charactersforms a word.
- Deaf/Dumb person should be able to perform a sign, where group of words formssentence.
- Especially Deaf people especially should be able to see the translation of signs totext format.
- Dumb person should be able to understand the conversion of text into voice mode.
- Normal users should be able to understand the corresponding information conveyed by disabled through sign language.

# **Default Operation:**

- Users of the app face the camera and perform the concerned hand sign to conveyinformation.
- System/Desktop analyses the sign made by the user.
- Once analysis gets finished, then the concerned signs together are shown as a textbased and also through voice.

## **Unexpected Operations:**

- Desktop indicates that the user's hand sign is not within the frame or in Region of Interest (ROI).
  - 1. Users of the app show the hand sign towards the camera.
  - 2. Desktop shows that the sign is not within ROI.
  - **3.** Still User, make sure to present his/her sign within frame.
  - **4.** At last, Desktop finally detects the hand sign.

### • Signs are not recognized

- **1.** Excepts the signs that are trained and included in the dataset, the Desktop will never detect the sign rather than this.
- **2.** User Performs the sign and sees that after 50ms, the concerned letteroccupies the space of text.
- Speech/Voice assistant is implemented

Speech assistant is to be implemented in order to convert the output textinto voice.