Assignment -4

ESP32 Programming with IBM Cloud

Assignment Date	25 October 2022
Student Name	PADMAPRIYA B
Student Roll Number	2116191001059
Maximum Marks	2 Marks

Question-1:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100cms send "alert" to ibm cloud and display in device recent events.

Upload document with wokwi share link and images of ibm cloud.


Solution:


```
#include <WiFi.h>//library for wifi
#include < PubSubClient.h > //library for MQtt
#define ECHO_GPIO 12
#define TRIGGER_GPIO 13
#define MAX_DISTANCE_CM 100 // Maximum of 5 meters
#include "Ultrasonic.h"
Ultrasonic ultrasonic(13, 12);
int distance;
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength);
//----credentials of IBM Accounts-----
#define ORG "5jil5s"//IBM ORGANITION ID
#define DEVICE_TYPE "abcd"//Device type mentioned in ibm watson IOT Platform
#define DEVICE_ID "12345"//Device ID mentioned in ibm watson IOT Platform
#define TOKEN "@TcizfW(zVdn9iXU5h"
String data3;
float h, t;
//---- Customise the above values -----
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of event perform and
format in which data to be send
char subscribetopic[] = "iot-2/cmd/command/fmt/String";// cmd REPRESENT command type
AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
```


```
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;//client id
//----
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback, wifiClient); //calling the predefined client id by
passing parameter like server id, portand wificredential
void setup()// configureing the ESP32
 Serial.begin(115200);
 delay(10);
 Serial.println();
 wificonnect();
 mqttconnect();
void loop()// Recursive Function
 distance = ultrasonic.read(CM);
 if(distance < 100){
 Serial.print("Distance in CM: ");
 Serial.println(distance);
 PublishData(distance);
 delay(1000);
 if (!client.loop()) {
  mqttconnect();
 }
 }
 delay(1000);
}
/*....retrieving to Cloud.....*/
void PublishData(float temp) {
 mqttconnect();//function call for connecting to ibm
   creating the String in in form JSon to update the data to ibm cloud
 String payload = "{\"Alert Distance:\":";
 payload += temp;
 payload += "}";
```


```
}
void mqttconnect() {
 if (!client.connected()) {
  Serial.print("Reconnecting client to ");
  Serial.println(server);
  while (!!!client.connect(clientId, authMethod, token)) {
   Serial.print(".");
   delay(500);
  }
  initManagedDevice();
   Serial.println();
 }
}
void wificonnect() //function defination for wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish the connection
 while (WiFi.status() != WL_CONNECTED) {
  delay(500);
  Serial.print(".");
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
}
void initManagedDevice() {
if (client.subscribe(subscribetopic)) {
  Serial.println((subscribetopic));
  Serial.println("subscribe to cmd OK");
  Serial.println("subscribe to cmd FAILED");
 }
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
 Serial.print("callback invoked for topic: ");
 Serial.println(subscribetopic);
```


```
for (int i = 0; i < payloadLength; i++) {
    //Serial.print((char)payload[i]);
    data3 += (char)payload[i];
}
Serial.println("data: "+ data3);
if(data3=="lighton")
{
Serial.println(data3);
}
else
{
Serial.println(data3);
}
data3="";
}</pre>
```











Wokwi share link:

https://wokwi.com/projects/348767887336407636