```
#include <dht.h>
#define dht_apin A0                          // Analog Pin 0 is connected to DHT sensor
#define mqt_apin A1                          // Analog Pin 1 is connected to MQT 135 sensor
dht DHT;
int sensorValue;
void setup(){
Serial.begin(9600);                          //Serial port to communicate with Python code
Serial1.begin(9600);          //Serial port to communicate with Wearable device through Bluetooth (HC-05)
delay(500);                                  //Delay to let system boot
}
void loop(){
DHT.read11(dht_apin);                        // read analog input pin 0(DHT11)
sensorValue = analogRead(mqt_apin);          // read analog input pin 1 (MQ135)
CodeSerial.print("Current humidity = ");      //SendHumidity status to Python
Serial.print(DHT.humidity);
Serial.print("%  ");                          //Send Temperature status to Python Code
Serial.print("temperature = ");
Serial.print(DHT.temperature);
Serial.println("C  ");                       //Send AirQuality sensor value to Python code
Serial.print("AirQua=");
Serial.print(sensorValue, DEC);
Serial.println(" PPM");   //Send signals to the Wearable
Serial1.println("H T A");
Serial1.println(DHT.humidity);
Serial1.println(DHT.temperature);
Serial1.println(sensorValue, DEC);
delay(100);                                  // wait 100 milliseconds for next reading
}
```