Sprint 4

Team ID	PNT2022TMID27334
Project Name	Personal Assistance for Seniors Who Are Self
	Reliant

Code for Simulation:

```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
#include <LiquidCrystal I2C.h>
#include "DHT.h"// Library for dht11
#define DHTPIN 15 // what pin we're connected to
#define DHTTYPE DHT11 // define type of sensor DHT 11
#define LED 2
DHT dht (DHTPIN, DHTTYPE);// creating the instance by passing pin and typr of
dht connected void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength);
//----credentials of IBM Accounts-----
#define ORG "64yf7x"//IBM ORGANITION ID
#define DEVICE_TYPE "b11m3edevicetype"//Device type mentioned in ibm watson
IOT Platform
#define DEVICE ID "b11m3edeviceid"//Device ID mentioned in ibm watson IOT
#define TOKEN "-&EMtr71-v-Gz2G))e"
                                      //Token
String data3=""; int buzz= 13;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
event perform and format in which data to be send char subscribetopic[] =
"iot-2/cmd/command/fmt/String";// cmd REPRESENT command type AND COMMAND IS
TEST OF FORMAT STRING char authMethod[] = "use-token-auth";// authentication
method char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;//client id
LiquidCrystal_I2C lcd(0x27,16,2);
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parameter like server id, portand
wificredential
```

```
void setup()// configureing the
ESP32
{
 Serial.begin(115200);
dht.begin();
            pinMode(buzz,
OUTPUT);
pinMode(LED,OUTPUT);
delay(10);
Serial.println();
wificonnect();
mqttconnect();
} void loop()// Recursive
Function
{ if (!client.loop())
     mqttconnect();
 }
}
/*....retrieving to
Cloud....*/
void PublishData(float temp, float humid) {
mqttconnect();//function call for connecting to ibm
  } void mqttconnect() {
if (!client.connected()) {
   Serial.print("Reconnecting client to ");
Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
Serial.print(".");
                  delay(500);
   }
    initManagedDevice();
    Serial.println();
 } } void wificonnect() //function defination for
wificonnect
 Serial.println();
 Serial.print("Connecting to ");
 WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
the connection while (WiFi.status() != WL_CONNECTED) { delay(500);
   Serial.print(".");
 }
 Serial.println("");
 Serial.println("WiFi connected");
 Serial.println("IP address: ");
 Serial.println(WiFi.localIP());
```

```
} void
initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
    Serial.println("subscribe to cmd FAILED");
} void callback(char* subscribetopic, byte* payload, unsigned int
payloadLength)
  Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {</pre>
//Serial.print((char)payload[i]);
+= (char)payload[i];
 }
  Serial.println("Medicine Name: "+ data3);
if(data3 != "")
 {
    lcd.init();
         lcd.print(data3);
digitalWrite(LED,HIGH);
tone(buzz, 100, 1000);
delay(2000);
digitalWrite(LED,LOW);
noTone(buzz);
delay(1000);
  }
  else
digitalWrite(LED,LOW);
data3="";
}
```

Output:

