TEAM ID.PNT2022TMID17554

PROJECT NAME: DemandEst - AI powered Food Demand Forecaster

Team Leader

RMSLE: 99.04866931366767

Save The Model

Pickle is used for serializing and de-serializing Python object structures, also called marshalling or flattening. Serialization refers to the process of converting an object in memory to a byte stream that can be stored on disk or sent over a network. Later on, this character stream can then be retrieved and de-serialized back to a Python object.Here, DT is our decision tree model saving as fdemand.pkl file. Wb is the write binary in bytes.

In [132]:
```
import pickle
pickle.dump(DT,open('fdemand.pkl','wb'))
```

Team Member 1

RMSLE: 99.04866931366767

Save The Model

Pickle is used for serializing and de-serializing Python object structures, also called marshalling or flattening. Serialization refers to the process of converting an object in memory to a byte stream that can be stored on disk or sent over a network. Later on, this character stream can then be retrieved and de-serialized back to a Python object.Here, DT is our decision tree model saving as fdemand.pkl file. Wb is the write binary in bytes.

In [132]:
```
import pickle
pickle.dump(DT,open('fdemand.pkl','wb'))
```

Team Member 2

RMSLE: 99.04866931366767

Save The Model

Pickle is used for serializing and de-serializing Python object structures, also called marshalling or flattening. Serialization refers to the process of converting an object in memory to a byte stream that can be stored on disk or sent over a network. Later on, this character stream can then be retrieved and de-serialized back to a Python object.Here, DT is our decision tree model saving as fdemand.pkl file. Wb is the write binary in bytes.

In [132]:
```
import pickle
pickle.dump(DT,open('fdemand.pkl','wb'))
```

Team Member 3

RMSLE: 99.04866931366767

Save The Model

Pickle is used for serializing and de-serializing Python object structures, also called marshalling or flattening. Serialization refers to the process of converting an object in memory to a byte stream that can be stored on disk or sent over a network. Later on, this character stream can then be retrieved and de-serialized back to a Python object.Here, DT is our decision tree model saving as fdemand.pkl file. Wb is the write binary in bytes.

In [132]:
```
import pickle
pickle.dump(DT,open('fdemand.pkl','wb'))
```