

TEAM ID: PNT2022TMID17554

PROJECT NAME: DemandEst - AI powered Food Demand Forecaster Team

Leader

The screenshot displays a Jupyter Notebook environment with two visible code cells. The first cell, labeled 'In [115]:', contains Python code for importing LabelEncoder and applying it to 'center_type', 'category', and 'cuisine' columns of a dataset named 'trainfinal'. The second cell, labeled 'In [116]:', shows the output of 'trainfinal.head()', which is a table of the first two rows of the dataset. The notebook interface includes a top bar with 'jupyter Code (autosaved)' and a 'Logout' button. The bottom bar shows 'Connecting to kernel' and 'Not Trusted' status. The second code cell is partially visible at the bottom of the image.

Label Encoding

Typically, any structured dataset includes multiple columns with combination of numerical as well as categorical variables. A machine can only understand the numbers. It cannot understand the text. That's essentially the case with Machine Learning algorithms too.

We need to convert each text category to numbers in order for the machine to process those using mathematical equations. Label Encoding is a popular encoding technique for handling categorical variables implemented using the scikit-learn library in python. In this technique, each label is assigned a unique integer based on alphabetical ordering.

```
In [115]: from sklearn.preprocessing import LabelEncoder

lb1 = LabelEncoder()
trainfinal['center_type'] = lb1.fit_transform(trainfinal['center_type'])
lb2 = LabelEncoder()
trainfinal['category'] = lb1.fit_transform(trainfinal['category'])
lb3 = LabelEncoder()
trainfinal['cuisine'] = lb1.fit_transform(trainfinal['cuisine'])
```

In the above code we have selected text class categorical columns for performing label encoding.

```
In [116]: trainfinal.head()
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	nur
0	1379560	1	647	56	2	2.0	0	3	136.83	152.29	0	0	
1	1018704	2	647	56	2	2.0	0	3	135.83	152.29	0	0	

```
trainfinal['center_type'] = lb1.fit_transform(trainfinal['center_type'])
lb2 = LabelEncoder()
trainfinal['category'] = lb1.fit_transform(trainfinal['category'])
lb3 = LabelEncoder()
trainfinal['cuisine'] = lb1.fit_transform(trainfinal['cuisine'])
```

In the above code we have selected text class categorical columns for performing label encoding.

```
In [116]: trainfinal.head()
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	nur
0	1379560	1	647	56	2	2.0	0	3	136.83	152.29	0	0	
1	1018704	2	647	56	2	2.0	0	3	135.83	152.29	0	0	
2	1196273	3	647	56	2	2.0	0	3	132.92	133.92	0	0	
3	1116527	4	647	56	2	2.0	0	3	135.86	134.86	0	0	
4	1343872	5	647	56	2	2.0	0	3	146.50	147.50	0	0	


After performing label encoding, alphabetical classes- "Center type, Category and City code are converted to numeric values.

Finally display number of rows and columns of trainfinal using shape()

```
In [117]: trainfinal.shape
```

```
Out[117]: (456548, 13)
```

Team Member 1



Label Encoding

Typically, any structured dataset includes multiple columns with combination of numerical as well as categorical variables. A machine can only understand the numbers. It cannot understand the text. That's essentially the case with Machine Learning algorithms too.

We need to convert each text category to numbers in order for the machine to process those using mathematical equations. Label Encoding is a popular encoding technique for handling categorical variables implemented using the scikit-learn library in python. In this technique, each label is assigned a unique integer based on alphabetical ordering.

```
In [115]: from sklearn.preprocessing import LabelEncoder


lb1 = LabelEncoder()
trainfinal['center_type'] = lb1.fit_transform(trainfinal['center_type'])
lb2 = LabelEncoder()
trainfinal['category'] = lb1.fit_transform(trainfinal['category'])
lb3 = LabelEncoder()
trainfinal['cuisine'] = lb1.fit_transform(trainfinal['cuisine'])
```

In the above code we have selected text class categorical columns for performing label encoding.

```
In [116]: trainfinal.head()
```

```
Out[116]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	nur
0	1379560	1	647	56	2	2.0	0	3	136.83	152.29	0	0	
1	1018704	2	647	56	2	2.0	0	3	135.83	152.29	0	0	



Label Encoding

Typically, any structured dataset includes multiple columns with combination of numerical as well as categorical variables. A machine can only understand the numbers. It cannot understand the text. That's essentially the case with Machine Learning algorithms too.

We need to convert each text category to numbers in order for the machine to process those using mathematical equations. Label Encoding is a popular encoding technique for handling categorical variables implemented using the scikit-learn library in python. In this technique, each label is assigned a unique integer based on alphabetical ordering.

```
In [115]: from sklearn.preprocessing import LabelEncoder

lb1 = LabelEncoder()
trainfinal['center_type'] = lb1.fit_transform(trainfinal['center_type'])
lb2 = LabelEncoder()
trainfinal['category'] = lb1.fit_transform(trainfinal['category'])
lb3 = LabelEncoder()
trainfinal['cuisine'] = lb1.fit_transform(trainfinal['cuisine'])
```

In the above code we have selected text class categorical columns for performing label encoding.

```
In [116]: trainfinal.head()
```

```
Out[116]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	nur
0	1379560	1	647	56	2	2.0	0	3	136.83	152.29	0	0	
1	1018704	2	647	56	2	2.0	0	3	135.83	152.29	0	0	
2	1196273	3	647	56	2	2.0	0	3	132.92	133.92	0	0	
3	1116527	4	647	56	2	2.0	0	3	135.86	134.86	0	0	
4	1343872	5	647	56	2	2.0	0	3	146.50	147.50	0	0	

After performing label encoding, alphabetical classes- "Center type, Category and City code are converted to numeric values.

Finally display number of rows and columns of trainfinal using shape()

```
In [117]: trainfinal.shape
```

```
Out[117]: (456548, 13)
```

Team Member 2

Label Encoding

Typically, any structured dataset includes multiple columns with combination of numerical as well as categorical variables. A machine can only understand the numbers. It cannot understand the text. That's essentially the case with Machine Learning algorithms too.

We need to convert each text category to numbers in order for the machine to process those using mathematical equations. Label Encoding is a popular encoding technique for handling categorical variables implemented using the scikit-learn library in python. In this technique, each label is assigned a unique integer based on alphabetical ordering.

```
In [115]: from sklearn.preprocessing import LabelEncoder

lb1 = LabelEncoder()
trainfinal['center_type'] = lb1.fit_transform(trainfinal['center_type'])
lb2 = LabelEncoder()
trainfinal['category'] = lb1.fit_transform(trainfinal['category'])
lb3 = LabelEncoder()
trainfinal['cuisine'] = lb1.fit_transform(trainfinal['cuisine'])
```

In the above code we have selected text class categorical columns for performing label encoding.

```
In [116]: trainfinal.head()
```

```
Out[116]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	nur
0	1379560	1	647	56	2	2.0	0	3	136.83	152.29	0	0	
1	1018704	2	647	56	2	2.0	0	3	135.83	152.29	0	0	

```
trainfinal['center_type'] = lb1.fit_transform(trainfinal['center_type'])
lb2 = LabelEncoder()
trainfinal['category'] = lb1.fit_transform(trainfinal['category'])
lb3 = LabelEncoder()
trainfinal['cuisine'] = lb1.fit_transform(trainfinal['cuisine'])
```

In the above code we have selected text class categorical columns for performing label encoding.

```
In [116]: trainfinal.head()
```

```
Out[116]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	nur
0	1379560	1	647	56	2	2.0	0	3	136.83	152.29	0	0	
1	1018704	2	647	56	2	2.0	0	3	135.83	152.29	0	0	
2	1196273	3	647	56	2	2.0	0	3	132.92	133.92	0	0	
3	1116527	4	647	56	2	2.0	0	3	135.86	134.86	0	0	
4	1343872	5	647	56	2	2.0	0	3	146.50	147.50	0	0	


After performing label encoding, alphabetical classes- "Center type, Category and City code are converted to numeric values.

Finally display number of rows and columns of trainfinal using shape()

```
In [117]: trainfinal.shape
```

```
Out[117]: (456548, 13)
```

Team Member 3



The screenshot shows a Jupyter Notebook interface with the following content:

Label Encoding

Typically, any structured dataset includes multiple columns with combination of numerical as well as categorical variables. A machine can only understand the numbers. It cannot understand the text. That's essentially the case with Machine Learning algorithms too.

We need to convert each text category to numbers in order for the machine to process those using mathematical equations. Label Encoding is a popular encoding technique for handling categorical variables implemented using the scikit-learn library in python. In this technique, each label is assigned a unique integer based on alphabetical ordering.


```
In [115]: from sklearn.preprocessing import LabelEncoder

lb1 = LabelEncoder()
trainfinal['center_type'] = lb1.fit_transform(trainfinal['center_type'])
lb2 = LabelEncoder()
trainfinal['category'] = lb1.fit_transform(trainfinal['category'])
lb3 = LabelEncoder()
trainfinal['cuisine'] = lb1.fit_transform(trainfinal['cuisine'])
```

In the above code we have selected text class categorical columns for performing label encoding.

```
In [116]: trainfinal.head()
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	nur
0	1379560	1	647	56	2	2.0	0	3	136.83	152.29	0	0	
1	1018704	2	647	56	2	2.0	0	3	135.83	152.29	0	0	



The screenshot shows the continuation of the Jupyter Notebook with the following content:

```
trainfinal['center_type'] = lb1.fit_transform(trainfinal['center_type'])
lb2 = LabelEncoder()
trainfinal['category'] = lb1.fit_transform(trainfinal['category'])
lb3 = LabelEncoder()
trainfinal['cuisine'] = lb1.fit_transform(trainfinal['cuisine'])
```

In the above code we have selected text class categorical columns for performing label encoding.

```
In [116]: trainfinal.head()
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	nur
0	1379560	1	647	56	2	2.0	0	3	136.83	152.29	0	0	
1	1018704	2	647	56	2	2.0	0	3	135.83	152.29	0	0	
2	1196273	3	647	56	2	2.0	0	3	132.92	133.92	0	0	
3	1116527	4	647	56	2	2.0	0	3	135.86	134.86	0	0	
4	1343872	5	647	56	2	2.0	0	3	146.50	147.50	0	0	

After performing label encoding, alphabetical classes- "Center type, Category and City code are converted to numeric values.

Finally display number of rows and columns of trainfinal using shape()

```
In [117]: trainfinal.shape
```

```
Out[117]: (456548, 13)
```