Assignment Date	10 October 2022
Student Name	Shankar J
Student Roll Number	2116190801159
Maximum Marks	2 Marks

Index page:

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <link rel="stylesheet" href="{{ url_for('static', filename='style.css')}}">
    <title>Home</title>
</head>
<body>

    <h2 class="home">Home Page</h2>

    <div class="space">
    <a class="text" href="/about"> About </a>
    <a class="text" href="/signin"> Log In </a>
    <a class="text" href="/signup"> Sign Up </a>
    </div>

</body>
</html>
```

Sign in page:

```html
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.2.1/dist/css/bootstrap.mi n.css" rel="stylesheet"
```

```
    integrity="sha384-
iYQeCzEYFbKjA/T2uDLTpkwGzCiq6soy8tYaI1GyVh/UjpbCx/TYkiZhlZB6+fz T"
crossorigin="anonymous">
    <link rel="stylesheet" href="{{ url_for('static', filename='style.css')}}">
    <title>Sign In</title>
</head>
<body>

    <div class="space">
     <a class="text" href="/"> Home </a>
     <a class="text" href="/about"> About </a>
     <a class="text" href="/signup"> Sign Up </a>
    </div>
    <h2 class="home">Log In</h2>

 <div class="signin">
   <form>
    <div class="form-group">
       <label  for="exampleInputEmail1">Email</label>
       <input  type="email"  class="form-control"   id="exampleInputEmail1"
aria-describedby="emailHelp" placeholder="Enter email">
      </div> <br>

     <div class="form-group">
        <label  for="exampleInputEmail1">password</label>
        <input         type="password"          class="form-control"
id="exampleInputEmail1"    aria-describedby="emailHelp"    placeholder="Enter
password">
       </div>
       <br>

     <button type="submit" class="btn btn-primary">Submit</button>
   </form>
</div>

</body>
</html>
```

Sign up Page:

```
<!DOCTYPE html>
<html lang="en">
```

```html
<head>
    <meta charset="UTF-8">
    <meta http-equiv="X-UA-Compatible" content="IE=edge">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.2.1/dist/css/bootstrap.mi n.css" rel="stylesheet"
    integrity="sha384-
iYQeCzEYFbKjA/T2uDLTpkwGzCiq6soy8tYaI1GyVh/UjpbCx/TYkiZhlZB6+fz T"
crossorigin="anonymous">
    <link rel="stylesheet" href="{{ url_for('static', filename='style.css')}}">
    <title>Sign Up</title>
</head>
<body>

    <div class="space">
    <a class="text" href="/"> Home </a>
    <a class="text" href="/about"> About </a>
    <a class="text" href="/signin"> Log In </a>
    </div>

    <h2 class="home">Sign Up</h2>

    <div class="signup">
    <form>
      <div class="form-group">
        <label for="Name">Name</label>
        <input class="form-control" type="text" name="Name" placeholder="Enter Name">
      </div><br>

    <div class="form-group">
      <label for="exampleInputEmail1">Email</label>
      <input type="email" class="form-control" id="exampleInputEmail1" aria-describedby="emailHelp" placeholder="Enter email">
    </div><br>

    <div class="form-group">
      <label for="exampleInputEmail1">password</label>
      <input type="password" class="form-control" id="exampleInputEmail1" aria-describedby="emailHelp" placeholder="Enter password">
```

```html
      </div><br>

      <div class="form-group">
        <label for="exampleInputEmail1">Re - password</label>
        <input              type="password"              class="form-control"
id="exampleInputEmail1"      aria-describedby="emailHelp"      placeholder="Enter
password">
      </div><br>

      <button type="submit" class="btn btn-primary">Submit</button>
    </form>

    </div>

  </body>
  </html>
```

: **Style code :**

```css
@import url('https://fonts.googleapis.com/css2?family=Poppins:wght@100;200;300;
400;500;600;700&display=swap');
*{
    font-family: 'Poppins', sans-serif;top:
    0;
    margin: 0;
}
body{
    background-
image:url("https://cdn.discordapp.com/attachments/99932152357796661
3/1023800785215176865/img.png") ;
}
.home{
    font-size: 25px;
    text-align: center;
    margin-top: 10px;
    color: black;
}

.text{
    text-decoration: none;
    font-size: 20px;
```

```css
    color: rgb(128, 42, 207);
    margin-left: 10px;
    margin-right: 10px;
    margin-top: 10px;
}
p{
    margin-left: 25px;
    margin-top: 10px;
    color:rgb(122, 2, 42);
    font-size: 20px;
}
.signin, .signup{
    height: 50vh;
    width: 50vw;
    margin-top: 10px;
    margin-left: 25px;
}
.space{
    margin-top:15px;
    text-align: right;
    margin-right: 10px;
```

App python :

```python
from flask import Flask
from flask import render_templateapp

= Flask(_name_)

@app.route('/')def
main():
    return  render_template('index.html')

@app.route('/about') def
about():
    return  render_template('about.html')

@app.route('/signin') def
signin():
    return render_template('signin.html')

@app.route('/signup')
```

```python
def signup():
    return  render_template('signup.html')

if _name_ == "_main_":
    app.run()
```

Source file:

```python
from flask import Flask,redirect,url_for,render_template,requestimport
ibm_boto3
from ibm_botocore.client import Config, ClientError

COS_ENDPOINT = "https://s3.jp-tok.cloud-object-storage.appdomain.cloud" # Current list avaiable at
https://control.cloud-object-storage.cloud.ibm.com/v2/endpoints
COS_API_KEY_ID = "xVWVt8tjo5lL5eY-jii6RAZu4IAfMrRQY2uaD0_-9LZj"
COS_INSTANCE_CRN = "crn:v1:bluemix:public:iam-
identity::a/37641ef4661f44a7bfab12af5b4ba6fe::serviceid:ServiceId-dd1803b4-6727-46a8-b09c- 1e921e8211c6"

# Create resource
cos = ibm_boto3.resource("s3",
    ibm_api_key_id=COS_API_KEY_ID,
    ibm_service_instance_id=COS_INSTANCE_CRN,
    config=Config(signature_version="oauth"),
    endpoint_url=COS_ENDPOINT
)

app=Flask(_name_)

def get_item(bucket_name, item_name):
    print("Retrieving item from bucket: {0}, key: {1}".format(bucket_name, item_name))try:
        file = cos.Object(bucket_name, item_name).get() print("File
        Contents: {0}".format(file["Body"].read()))
    except ClientError as be:
        print("CLIENT ERROR: {0}\n".format(be))
    except Exception as e:
        print("Unable to retrieve file contents: {0}".format(e))


def get_bucket_contents(bucket_name):
    print("Retrieving bucket contents from: {0}".format(bucket_name))try:
        files = cos.Bucket(bucket_name).objects.all()
        files_names = []
        for file in files:
            files_names.append(file.key)
            print("Item: {0} ({1} bytes).".format(file.key, file.size))
        return files_names
    except ClientError as be:
        print("CLIENT ERROR: {0}\n".format(be))
    except Exception as e:
        print("Unable to retrieve bucket contents: {0}".format(e))

def delete_item(bucket_name, object_name):try:
```

```python
            cos.delete_object(Bucket=bucket_name, Key=object_name) print("Item:
            {0} deleted!\n".format(object_name))
        except ClientError as be:
            print("CLIENT ERROR: {0}\n".format(be))
        except Exception as e:
            print("Unable to delete object: {0}".format(e))

def multi_part_upload(bucket_name, item_name, file_path):
    try:
        print("Starting file transfer for {0} to bucket: {1}\n".format(item_name, bucket_name))# set 5
        MB chunks
        part_size = 1024 * 1024 * 5

        # set threadhold to 15 MB
        file_threshold = 1024 * 1024 * 15

        # set the transfer threshold and chunk size transfer_config =
        ibm_boto3.s3.transfer.TransferConfig(
            multipart_threshold=file_threshold,
            multipart_chunksize=part_size
        )


        with open(file_path, "rb") as file_data: cos.Object(bucket_name,
            item_name).upload_fileobj(
                Fileobj=file_data,
                Config=transfer_config
            )

        print("Transfer for {0} Complete!\n".format(item_name))except
    ClientError as be:
        print("CLIENT ERROR: {0}\n".format(be))
    except Exception as e:
        print("Unable to complete multi-part upload: {0}".format(e))


@app.route('/')def
index():
    files = get_bucket_contents('jeeva-bucket1') return

    render_template('index.html', files = files)

@app.route('/uploader', methods = ['GET', 'POST'])def
upload():
    if request.method == 'POST':
        bucket=request.form['bucket']
        name_file=request.form['filename'] f =
        request.files['file']
        multi_part_upload(bucket,name_file,f.filename)
        return 'file uploaded successfully'

    if request.method == 'GET':
        return  render_template('upload.html')

@app.route('/deletefile', methods = ['GET', 'POST'])def
deletefile():
    if request.method == 'POST':
        bucket=request.form['bucket']
        name_file=request.form['filename']
```

```python
        delete_item(bucket,name_file)
        return 'file deleted successfully'

    if request.method == 'GET':
        return  render_template('delete.html')

if _name=='main_':
    app.run(debug=True)
```