

## Assignment -4

PROJECT NAME	AI - Powered Nutrition Analyst forFitness Enthusiasts.
NAME	M.Kasi Moorthi
ROLL NO	950919104011
TEAM ID	PNT2022TMID49959

### 1. Import the necessary libraries

```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import LabelEncoder
from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding
from keras.optimizers import RMSprop
from keras.preprocessing.text import Tokenizer
from keras.preprocessing import sequence
from keras.utils import pad_sequences
from keras.utils import to_categorical
from keras.callbacks import EarlyStopping
```

### 2. Read dataset and do pre-processing

#### (i) Read dataset

```
df = pd.read_csv('/content/spam.csv', delimiter=',', encoding='latin-1')
df.head()
```

Unnamed: 0 Unnamed: 1 Unnamed: 2

v1 v2 3 4

1 1 1 1

0 ham Go until jurong point, crazy.. Available only ... NaN NaN NaN 1 ham Ok lar...Joking wif u oni... NaN NaN

NaN 2  
spam Free entry in 2 a wkly comp to win FA Cup

3 ham U dun say so early hor... U c already then say... NaN NaN NaN 4 ham Nah I don't think he goes to usf, he  
lives aro... NaN NaN NaN



## (ii) Preprocessing the dataset

```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True) df.info()
```

```
<class 'pandas.core.frame.DataFrame'>RangeIndex:
```

```
5572 entries, 0 to 5571
```

```
Data columns (total 2 columns):
```

```
# Column Non-Null Count Dtype
```

```
0 v1 5572 non-null object
```

```
1 v2 5572 non-null object dtypes: object(2) memory usage:  
87.2+ KB
```

```
X = df.v2
```

```
Y = df.v1le = LabelEncoder() Y =
```

```
le.fit_transform(Y)
```

```
Y = Y.reshape(-1,1)
```

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

```
max_words = 1000
```

```
max_len = 150
```

```
tok = Tokenizer(num_words=max_words) tok.fit_on_texts(X_train)
```

```
sequences = tok.texts_to_sequences(X_train)
```

```
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

### 3,4. Create model and Add Layers(LSTM ,Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
```

```
layer = Embedding(max_words,50,input_length=max_len)(inputs)
```

```
layer = LSTM(64)(layer) layer = Dense(256,name='FC1')(layer)
```

```
layer = Activation('relu')(layer) layer = Dropout(0.5)(layer)
```

```
layer = Dense(1,name='out_layer')(layer) layer =
```

```
Activation('sigmoid')(layer) model =
Model(inputs=inputs,outputs=layer)model.summary()
```

Model: "model"

Layer (type)	Output Shape	Param #
inputs (InputLayer)	(None, 150)	0
embedding (Embedding)	(None, 150, 50)	50000
lstm (LSTM)	(None, 64)	29440
FC1 (Dense)	(None, 256)	16640
activation (Activation)		
dropout (Dropout)	(None, 256)	0
out_layer (Dense)	(None, 1)	257
activation_1 (Activation)	(None, 1)	0

== Total params: 96,337  
Trainable params: 96,337  
Non-trainable params: 0

## 5. Compile the model

```
model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy']) 7. Train
```

## and Fit the model

```
model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,
validation_split=0.2)
```

```
Epoch 1/10
30/30 [=====] - 8s 263ms/step - loss: 0.0060 - accurac Epoch
30/30 Epoch 30/30 [=====] - 8s 2/10 263ms/step - loss: 0.0572 -
accurac [=====] - 8s
263ms/step - loss: 0.0036 - accurac 3/10 Epoch
4/10
30/30 Epoch =====] 5/10 accurac
[=====] - 8s 262ms/step - loss: 0.0038 -
```

