

Assignment -4

PROJECT NAME	AI - Powered Nutrition Analyst forFitness Enthusiasts.
NAME	SIndhuja K
ROLL NO	950919104023
TEAM ID	PNT2022TMID49959

1. Import the necessary libraries

```
import pandas as pdimport numpy
as np
import matplotlib.pyplot as pltimport
seaborn as sns
from sklearn.model_selection import
train_test_splitfrom sklearn.preprocessing import
LabelEncoder from keras.models import Model
from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embeddingfrom
keras.optimizers import RMSprop
from keras.preprocessing.text import
Tokenizerfrom keras.preprocessing import
sequence from keras.utils import pad_sequences
from keras.utils import to_categorical from
keras.callbacks import EarlyStopping
```

2. Read dataset and do pre-processing

(i) Read dataset

```
df = pd.read_csv('/content/spam.csv',delimiter=',',encoding='latin-1')
df.head()
```

```
      Unnamed: 0  Unnamed: 1  Unnamed: 2
0      ham      Go until jurong point, crazy.. Available only ... NaN NaN NaN 1      ham      Ok lar...Joking wif u oni... NaN NaN
1      NaN      2      spam      Free entry in 2 a wkly comp to win FA Cup
2      fina... NaN NaN NaN
```

3 ham U dun say so early hor... U c already then say... NaN NaN NaN 4 ham Nah I don't think he goes to usf, he
lives aro... NaN NaN NaN



(ii) Preprocessing the dataset

```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True) df.info()
```

```
<class 'pandas.core.frame.DataFrame'>RangeIndex:
5572 entries, 0 to 5571
Data columns (total 2 columns):
# Column Non-Null Count Dtype
0      v1 5572 non-null object
1      v2 5572 non-null object dtypes: object(2) memory usage:
87.2+ KB
```

```
X = df.v2
Y = df.v1le = LabelEncoder() Y =
le.fit_transform(Y)
Y = Y.reshape(-1,1)
```

```
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.15)
```

```
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words) tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

3,4. Create model and Add Layers(LSTM ,Dense-(Hidden Layers), Output)

```
inputs = Input(name='inputs',shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(64)(layer) layer = Dense(256,name='FC1')(layer)
layer = Activation('relu')(layer) layer = Dropout(0.5)(layer)
layer = Dense(1,name='out_layer')(layer) layer =
Activation('sigmoid')(layer) model =
Model(inputs=inputs,outputs=layer)model.summary()
```

Model: "model"

Layer (type) Output Shape Param #

=====

```

= inputs (InputLayer) [(None, 150)] 0

embedding (Embedding) (None, 150, 50) 50000

lstm (LSTM) (None, 64) 29440 FC1 (Dense)

(None, 256) 16640 activation (Activation)

(None, 256) 0 dropout (Dropout) (None, 256) 0

out_layer (Dense) (None, 1) 257 activation_1

(Activation) (None, 1) 0

```

```

=====
= Total params: 96,337
Trainable params: 96,337
Non-trainable params: 0

```

5. Compile the model

`model.compile(loss='binary_crossentropy',optimizer=RMSprop(),metrics=['accuracy'])` **7. Train**

and Fit the model

```

model.fit(sequences_matrix,Y_train,batch_size=128,epochs=10,
        validation_split=0.2)

```

```

Epoch 1/10
30/30 [=====] - 8s 263ms/step - loss: 0.0060 - accurac
Epoch 30/30 Epoch 30/30 [=====] - 8s
2/10 263ms/step - loss: 0.0572 - accurac
[=====] - 8s
263ms/step - loss: 0.0036 - accurac 3/10 Epoch
4/10
30/30 Epoch [====] 5/10 accurac
[===== - 8s 262ms/step - loss: 0.0038 -
===== - 8s - 8s 263ms/step 0.0018 0.0022 accurac
30/30 Epoch [=====] [=====]
30/30 Epoch 6/10 7/10 261ms/step - loss: - loss: - accurac -
[=====][=====]

30/30 310ms/step - loss: 0.0020 - accurac

```

```
[=====] - 9s
Epoch 8/10
30/30 Epoch    30/30 Epoch    [=====]    9/10    [=====]
===== - 8s - 8s    261ms/step    264ms/step    0.0015 0.0015 - accurac -
=====]
10/10          - loss: - loss:          accurac

30/30          263ms/step - loss: 0.0021 - accurac
[=====] - 8s
<keras.callbacks.History at 0x7f2b60b5f110>
```

6. Save the model

```
model.save('sms_classifier.h5')
```

Preprocessing the Test Dataset

```
test_sequences = tok.texts_to_sequences(X_test)
test_sequences_matrix = pad_sequences(test_sequences, maxlen=max_len)
```

7. Testing the model

```
accr = model.evaluate(test_sequences_matrix,Y_test)
```

```
27/27 [=====] - 1s 21ms/step - loss: 0.2618 - accuracy
```

```
print('Test set\n Loss: {:.3f}\n Accuracy: {:.3f}'.format(accr[0],accr[1]))
```

```
Test set Loss: 0.262
Accuracy: 0.977
```