

**TIN KERCAD** Gas Leakage monitoring sensor Saved

**Code** **Start Simulation** **Send To**

Text 1 (Arduino Uno R3)

```

1 #include <Servo.h>
2
3 Servo myservo;
4
5
6 #define ledR2 5
7 #define ledR1 4
8 #define ledY2 3
9 #define ledY1 2
10 #define ledG1 1
11 #define gas A0
12 #define buzzer 8
13 #define serv 9
14
15 void setup()
16 {
17   pinMode(ledR1, OUTPUT);
18   pinMode(ledR2, OUTPUT);
19   pinMode(ledY1, OUTPUT);
20   pinMode(ledY2, OUTPUT);
21   pinMode(ledG1, OUTPUT);
22   pinMode(buzzer, OUTPUT);
23   myservo.attach(serv);
24   pinMode(gas, INPUT);
25 }

```

Serial Monitor

**TIN KERCAD** Gas Leakage monitoring sensor Saved

**Code** **Start Simulation** **Send To**

Text 1 (Arduino Uno R3)

```

21   pinMode(ledG1, OUTPUT);
22   pinMode(buzzer, OUTPUT);
23   myservo.attach(serv);
24   pinMode(gas, INPUT);
25
26
27   Serial.begin(9600);
28 }
29
30 void loop()
31 {
32   int read= analogRead(gas);
33   int val= map(read,80,380,0,100);
34   Serial.println(val);
35
36   int servo= map(read,80,380,0,180);
37   myservo.write(servo);
38
39
40   digitalWrite(ledG1, HIGH);
41
42
43   if(val>=20 && val<40){
44     digitalWrite(ledY1,HIGH);
45
46

```

Serial Monitor

**TIN KERCAD** Gas Leakage monitoring sensor Saved

**Code** **Start Simulation** **Send To**

Text 1 (Arduino Uno R3)

```

40   digitalWrite(ledG1, HIGH);
41
42
43   if(val>=20 && val<40){
44     digitalWrite(ledY1,HIGH);
45
46
47
48   if(val>=40 && val<60){
49     digitalWrite(ledY2,HIGH);
50
51
52   if(val>=60 && val<80){
53     digitalWrite(ledR1,HIGH);
54
55
56   if(val>=80){
57     digitalWrite(ledG1, HIGH);
58     digitalWrite(ledY1, HIGH);
59     digitalWrite(ledY2, HIGH);
60     digitalWrite(ledR1, HIGH);
61     digitalWrite(ledR2, HIGH);
62
63     delay(500);
64
65

```

Serial Monitor

TIN  
KER  
CAD

Gas Leakage monitoring sensor

Saved

Code

Start Simulation

Send To

Text

1 (Arduino Uno R3)

```

59     digitalWrite(ledY2, HIGH);
60     digitalWrite(ledR1, HIGH);
61     digitalWrite(ledR2, HIGH);
62
63     delay(500);
64     digitalWrite(ledG1, LOW);
65     digitalWrite(ledY1, LOW);
66     digitalWrite(ledY2, LOW);
67     digitalWrite(ledR1, LOW);
68     digitalWrite(ledR2, LOW);
69
70     delay(1000);
71
72     tone(buzzer,1000,500); // function that allows you to set
73
74 }
75
76 if (val<80){
77     noTone(buzzer);
78 }
79
80
81
82 }

```

Serial Monitor

TIN  
KER  
CAD

Gas Leakage monitoring sensor

Saved

Code

Initializing...

Send To

1 (Arduino Uno R3)

```

59     digitalWrite(ledY2, HIGH);
60     digitalWrite(ledR1, HIGH);
61     digitalWrite(ledR2, HIGH);
62
63     delay(500);
64     digitalWrite(ledG1, LOW);
65     digitalWrite(ledY1, LOW);
66     digitalWrite(ledY2, LOW);
67     digitalWrite(ledR1, LOW);
68     digitalWrite(ledR2, LOW);
69
70     delay(1000);
71
72     tone(buzzer,1000,500); // function that allows you to set
73
74 }
75
76 if (val<80){
77     noTone(buzzer);
78 }
79
80
81
82 }

```

Serial Monitor

How the debugger works

1. Add breakpoints by clicking on the line numbers.
2. Hover over the variables while paused to see their value.
3. Use the buttons above to resume simulation or step one line at a time.

**TIN K E R C A D** Gas Leakage monitoring sensor Saved

Simulator time: 00:00:01 Code Stop Simulation Send To

1 (Arduino Uno R3)

```
59 digitalWrite(ledY2, HIGH);
60 digitalWrite(ledR1, HIGH);
61 digitalWrite(ledR2, HIGH);
62
63 delay(500);
64 digitalWrite(ledG1, LOW);
65 digitalWrite(ledY1, LOW);
66 digitalWrite(ledY2, LOW);
67 digitalWrite(ledR1, LOW);
68 digitalWrite(ledR2, LOW);
69
70 delay(1000);
71
72 tone(buzzer,1000,500); // function that allows you to set
73
74 }
75
76 if (val<80){
77   noTone(buzzer);
78 }
79
80
81
82 }
```

Serial Monitor

**How the debugger works**

1. Add breakpoints by clicking on the line numbers.
2. Hover over the variables while paused to see their value.
3. Use the buttons above to resume simulation or step one line at a time.

**TIN K E R C A D** Gas Leakage monitoring sensor Saved

Simulator time: 00:00:03 Code Stop Simulation Send To

1 (Arduino Uno R3)

Gas Sensor  
Name 1

```
59 digitalWrite(ledY2, HIGH);
60 digitalWrite(ledR1, HIGH);
61 digitalWrite(ledR2, HIGH);
62
63 delay(500);
64 digitalWrite(ledG1, LOW);
65 digitalWrite(ledY1, LOW);
66 digitalWrite(ledY2, LOW);
67 digitalWrite(ledR1, LOW);
68 digitalWrite(ledR2, LOW);
69
70 delay(1000);
71
72 tone(buzzer,1000,500); // function that allows you to set
73
74 }
75
76 if (val<80){
77   noTone(buzzer);
78 }
79
80
81
82 }
```

Serial Monitor

**How the debugger works**

1. Add breakpoints by clicking on the line numbers.
2. Hover over the variables while paused to see their value.
3. Use the buttons above to resume simulation or step one line at a time.