Assignment -4 SMS SPAM Classification

Assignment Date	26 October 2022	
Team ID	PNT2022TMID38845	
Project Name	AI BASED DISCOURSE FOR BANKING INDUSTRY	
Student Name	Charulatha S	
Student Roll Number	421219104003	
Maximum Marks	2 Marks	

Question-1. Import required library

Solution:

import pandas as pd

import numpy as np

import matplotlib.pyplot as plt

from sklearn.model_selection import train_test_split

from sklearn.preprocessing import LabelEncoder

from keras.models import Model

from keras.layers import LSTM, Activation, Dense, Dropout, Input, Embedding

from keras.optimizers import Adam

from keras.preprocessing.text import Tokenizer

from keras.preprocessing import sequence

from keras.utils import pad_sequences

from keras.utils import to_categorical

from keras.callbacks import EarlyStopping

Question-2. Read the Dataset

Solution:

```
df = pd.read_csv('spam.csv',delimiter=',',encoding='latin-1')
df.head()
```

	V1	V2	Unnamed: 2	Unnamed: 3	Unnamed: 4
0	ham	Go until jurong point, crazy Available only	NaN	NaN	NaN
1	ham	Ok lar Joking wif u oni	NaN	NaN	NaN
2	spam	Free entry in 2 a wkly comp to win FA Cup fina	NaN	NaN	NaN
3	ham	U dun say so early hor U c already then say	NaN	NaN	NaN
4	ham	Nah I don't think he goes to usf, he lives aro	NaN	NaN	NaN

Question-3. Pre processing the Dataset

Solution:

```
df.drop(['Unnamed: 2', 'Unnamed: 3', 'Unnamed: 4'],axis=1,inplace=True)
```

from wordcloud import WordCloud, STOPWORDS, ImageColorGenerator

```
X = df.v2
Y = df.v1
le = LabelEncoder()
Y = le.fit_transform(Y)
Y = Y.reshape(-1,1)
X_train,X_test,Y_train,Y_test = train_test_split(X,Y,test_size=0.25)
max_words = 1000
max_len = 150
tok = Tokenizer(num_words=max_words)
tok.fit_on_texts(X_train)
sequences = tok.texts_to_sequences(X_train)
sequences_matrix = pad_sequences(sequences,maxlen=max_len)
```

Question-4. Create Model

Solution:

```
inputs = Input(shape=[max_len])
layer = Embedding(max_words,50,input_length=max_len)(inputs)
layer = LSTM(128)(layer)
layer = Dense(128)(layer)
```

layer = Activation('relu')(layer)

layer = Dropout(0.5)(layer)

layer = Dense(1)(layer)

layer = Activation('sigmoid')(layer)

model = Model(inputs=inputs,outputs=layer)

Question-5. Add Layers (LSTM, Dense-(Hidden Layers), Output)

Solution:

model.summary()

Model: "model_1"

Layer (type)	Output Shape	Param #
input_2 (InputLayer)	[(None, 150)]	0
embedding_1 (Embedding)	(None, 150, 50)	50000
lstm_1 (LSTM)	(None, 128)	91648
dense_2 (Dense)	(None, 128)	16512
activation_2 (Activation)	(None, 128)	0
dropout_1 (Dropout)	(None, 128)	0
dense_3 (Dense)	(None, 1)	129
activation_3 (Activation)	(None, 1)	0

Total params: 158,289 Trainable params: 158,289 Non-trainable params: 0

Question-6. Compile the Model

Solution:

model.compile(loss='binary_crossentropy',optimizer=Adam(),metrics=['accuracy'])

Question-7. Fit the Model

Solution:


history = model.fit(sequences_matrix,Y_train,batch_size=20,epochs=15, validation_split=0.2)

```
Epoch 1/15
168/168 [============= ] - 34s 190ms/step - loss: 0.1980 - accuracy: 0.9354 - val_loss: 0.0649 - val_accuracy: 0.9821
Epoch 2/15
Epoch 3/15
Epoch 4/15
168/168 [============ ] - 33s 198ms/step - loss: 0.0155 - accuracy: 0.9949 - val loss: 0.0779 - val accuracy: 0.9797
Epoch 5/15
168/168 [============= ] - 32s 188ms/step - loss: 0.0132 - accuracy: 0.9964 - val loss: 0.0661 - val accuracy: 0.9821
Epoch 6/15
168/168 [===========] - 32s 190ms/step - loss: 0.0065 - accuracy: 0.9985 - val loss: 0.0772 - val accuracy: 0.9868
Epoch 7/15
168/168 [==========] - 32s 192ms/step - loss: 0.0057 - accuracy: 0.9982 - val loss: 0.0811 - val accuracy: 0.9844
Epoch 8/15
Fnoch 10/15
Epoch 11/15
Fnoch 13/15
Epoch 14/15
168/168 [===========] - 31s 187ms/step - loss: 0.0081 - accuracy: 0.9967 - val loss: 0.1005 - val accuracy: 0.9844
Epoch 15/15
```

```
metrics = pd.DataFrame(history.history)
metrics.rename(columns = {'loss': 'Training_Loss', 'accuracy': 'Training_Accuracy', 'val_loss': 'Validation_Loss', 'val_accuracy': 'Validation_Accuracy'}, inplace = True)
def plot_graphs1(var1, var2, string):
    metrics[[var1, var2]].plot()
```

```
plt.title('Training and Validation ' + string)
plt.xlabel ('Number of epochs')
plt.ylabel(string)
plt.legend([var1, var2])
```

plot_graphs1('Training_Accuracy', 'Validation_Accuracy', 'Accuracy')



Question-8. Save The Model

Solution:

model.save('Spam_sms_classifier.h5')



Question-9. Test The Model

Solution:

test_sequences = tok.texts_to_sequences(X_test)

test_sequences_matrix = pad_sequences(test_sequences,maxlen=max_len)

```
accuracy1 = model.evaluate(test_sequences_matrix,Y_test)
```

```
44/44 [===========] - 4s 82ms/step - loss: 0.1061 - accuracy: 0.9828
```

print(' loss: {:0.4f}'.format(accuracy1[0]))

print(' Accuracy: {:0.4f}'.format(accuracy1[1]))

loss: 0.1061 Accuracy: 0.9828