ASSIGNMENT - 4

| Date | 02 november 2022 |
|---------|---|
| Team ID | PNT2022TMID01040 |
| Name | Gas Leakage monitoring & Alerting system for industries |

QUESTION:

Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send "alert" to IBM cloud and display in device recent events.

CODE:

```
#include <WiFi.h>
                     // library for wifi
#include < PubSubClient.h >
                                          // library for MQTT
//----- credentials of IBM Accounts -----
#define ORG "rwazv5"
                          // IBM organisation id
#define DEVICE_TYPE "NodeRed" // Device type mentioned in ibm watson iot platform
#define DEVICE ID "12345" // Device ID mentioned in ibm watson iot platform
#define TOKEN "vC@S3TBre6(97jAOJ "
                                    // Token
#define speed 0.034
#define led 14 String
data3;
int LED = 4;
//----- customise above values -----
char server[] = ORG ".messaging.internetofthings.ibmcloud.com"; // server name
format in which data to be send
char topic[] = "iot-2/cmd/led/fmt/String"; // cmd Represent type and command is test format of
strings
char authMethod[] = "use-token-auth";  // authentication method char
token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID; //Client id
WiFiClient wifiClient;
                          // creating instance for wificlient
PubSubClient client(server, 1883, wifiClient); // calling the predefined client id by passing parameter like server id, port and wifi
credential
```


```
const int trigpin=5; const
int echopin=18;
String command;
String data="";
long duration; float
dist;
void setup()
Serial.begin(115200);
pinMode(led, OUTPUT);
pinMode(trigpin, OUTPUT);
pinMode(echopin, INPUT);
wifiConnect(); mqttConnect();
}
void loop() { bool isNearby
      dist
              <
                    100;
digitalWrite(led, isNearby);
publishData();
delay(500);
if (!client.loop())
mqttConnect();
                           // function call to connect to ibm
}
}
/* -----*/
void wifiConnect()
Serial.print("Connecting to ");
Serial.print("Wifi");
WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED)
{
delay(500);
 Serial.print(".");
Serial.print("WiFi connected, IP address: ");
Serial.println(WiFi.localIP());
```

```
}
void mqttConnect()
if (!client.connected())
Serial.print("Reconnecting MQTT client to ");
Serial.println(server);
while (!client.connect(clientId, authMethod, token))
Serial.print(".");
delay(500);
}
initManagedDevice();
Serial.println();
}
}
void initManagedDevice() {
if (client.subscribe(topic))
{
Serial.println("IBM subscribe to cmd OK");
}
else
Serial.println("subscribe to cmd FAILED");
}
void publishData()
digitalWrite(trigpin,LOW);
digitalWrite(trigpin,HIGH);
delayMicroseconds(10); digitalWrite(trigpin,LOW);
duration=pulseIn(echopin,HIGH);
dist=duration*speed/2;
if(dist<100)
{
digitalWrite(LED,HIGH); String
payload = "{\"Alert Distance\":";
payload += dist;
payload += "}";
Serial.print("\n");
Serial.print("Sending payload: "); Serial.println(payload); if (client.publish(publishTopic, (char*)
payload.c_str())) // if data is uploaded to cloud successfully, prints publish ok else prints publish failed
```

```
Serial.println("Publish OK");
}
}
if(dist>100)
digitalWrite(LED,HIGH);
String payload = "{\"Distance\":";
payload += dist;
payload += "}";
Serial.print("\n");
Serial.print("Sending payload: ");
Serial.println(payload);
if(client.publish(publishTopic, (char*) payload.c_str()))
Serial.println("Publish OK");
}
else
{
digitalWrite(LED,LOW);
Serial.println("Publish FAILED");
}
}
}
```

OUTPUT:

Code simulation on wokwi



Data sent to IBM Cloud with distance

