PROJECT DOCUMENTATION REPORT

DATE	**19 NOVEMBER 2022**
TEAM ID	**PNT2022TMID42644**
PROJECT TITLE	**INDUSTRY-SPECIFIC INTELLIGENT FIRE MANAGEMENT SYSTEM**

Team : BALLAM PRAVEEN KUMAR

Members MONICA NANCY V

SATHYAMOORTHY M

JEEVITHA P

Industry

Mentor : Santoshi

Name

Faculty

Mentor(s) : Surya M , Gowtham P.

Name

1. INTRODUCTION

1.1 Project Overview

Abstract :

Fire prevention and protection in industrial plant basically include procedures for preventing, detecting and extinguishing fires. There is much to be done to promote safe systems for fire prevention in India. The systems should be designed to protect the employees and property and to assure safe working systems. Fire prevention and protection in any industrial plant include fire detection system, fire alarm system, fire prevention plan and employing legal requirements relevant to fire and safety management.

1.2 Purpose

Nowadays, fire incidents have become a critical issue, which must be dealt with on time without any unnecessary delay to avoid the loss in lives and belongings. It is considered a fire situation when the monitored temperature exceeds 50°C. According to the national fire protection association (NFPA), two-third of U.S. household fires occur in premises with no working smoke alarms, alarms with no proper maintenance, or misplaced alarms.

This is the IOT (internet of things) based fire monitoring and controlling system which not only gives the real time information about the situation on the monitor but also takes the corrective action as per the need. In a publish and subscribe system, a device can publish a message on a topic, or it can be subscribed to a particular topic to receive message. Also it is perfect solution for internet of things application. Due to this all data can be stored in server and this data can be access by the Application program interface which we can display on the monitor and with the help of software, the operator can visualize the condition at the time of fire accident.

2. LITERATURE SURVEY

2.1 Existing problem :

In the Industries, mostly manufacturing sectors are affected due to fire accidents. Manufacturing sectors may contain specific equipment’s, that can lead to such kind of accidents. As fire accidents are considered that may include the Geographic and confined spaces of the industry also. Many of the fire accidents occurs in the industries are unexpected which could cause life and property damage. The major reasons are neglecting and breaking the government norms. The fire accidents may occur frequently in large scale heavy manufacturing industries. To create safe working conditions and to reduce the property loses, the problem solution is needed.

2.2 References :

[1] Shokouhi, M., Nasiriani, K., Khankeh, H., Fallahzadeh, H. and Khorasani-Zavareh, D., “Exploring barriers and challenges in protecting residential fire-related injuries: a qualitative study,” Journal of injury and violence research, vol. 11, no. 1, pp. 81-92, 2019.

[2] V. Jelicic; M. Magno; G. Paci; D. Brunelli; L. Benini, "Design, characterization and management of a wireless sensor network for smart gas monitoring," in 2011 4th IEEE Int. Workshop on Adv. in Sensors and Interfaces (IWASI), pp. 115-120.

[3] Saeed, F., Paul, A., Karthigaikumar, P. and Nayyar, A., “Convolutional neural network based early fire detection,” Multimedia Tools and Applications, vol. 79, pp. 9083-9099, 2020.

[4] Shah, R., Satam, P., Sayyed, M.A. and Salvi, P., “Wireless Smoke Detector and Fire Alarm System,” International Research Journal of Engineering and Technology (IRJET), vol. 6, no. 1, pp. 1407-1412, 2019.

[5] F. He; Z. Du; Y. Sun, “Indoor dangerous gas environment detected by mobile robot,” in 2009 IEEE International Conference on Robotics and Biomimetic (ROBIO), pp. 396-401.

[6] Mahzan, N. N., Enzai, N. M., Zin, N. M. and Noh, K. S. S. K. M., “Design of an Arduino based home fire alarm system with GSM module,” Journal of Physics: Conference Series, vol. 1019, no. 1, 2018, Art. no. 012079.

2.3 Problem Statement Definition

Safety is considered first in the designing of residential and commercial buildings in order to safe guard the property damage as well as loss of life. Nowadays the existing fire alarm in the markets is too complex in terms of its design and structures. It needs regular maintenance to be carried out to make sure the system performance. Meanwhile the maintenance is being done to the existing system, it could raise the cost of the system.

3. IDEATION & PROPOSED SOLUTION

3.1 Empathy Map Canvas



Mural Link: https://app.mural.co/invitation/mural/b66m2eempathymap2834/1666853699179?sender=u0e62f13a49dd379cfa3d2746&key=e549d3a1-c5e0-4975-9e0f-877cf1844181

3.2 Ideation & Brainstroming



3.3 Proposed Solution

S.No.	Parameters	Outcomes
1.	Problem Statement (Problem to be solved)	*Improving the Fire management and alert system in industries. And also providing a safe environment for the workers…
2.	Idea / Solution description	*Providing fire management and alert system in industries on IoT with fire detection and using some sensors (Gas sensor, flame sensor, temperature sensor).
3.	Novelty / Uniqueness	*An IoT system that is integrated with temperature sensor, gas sensor, flame sensor, exhaust fan ,water sprinkler and fire alert through SMS to the authority…
4.	Social Impact / Customer Satisfaction	*We can also able to reduce the damages caused by fire accidents in industries using this device by alerting everyone early….
5.	Business Model (Revenue Model)	*This product can be used in industries .This system can be used as a safety system in industries. * High Efficient and Secure…
6.	Scalability of the Solution	*This project is trying to execute the method with the help of an IoT gadget which provides a safe environment for workers in industries. *Easy to Install and Maintain…

3.4 Problem Solution fit





4.REQUIRMENT ANALYSIS

4.1 **Functional Requirements**

FR No.	**Functional Requirement (Epic)**	**Sub Requirement (Story / Sub-Task)**
FR-1	**User Requirements**	Workers and Product Protection Automatic Sprinkler System Monitors Smoke ,Gas and Temperature
FR-2	**User Registration**	Manual Registration Registration through webpage Registration through Form Registration through Gmail
FR-3	**User Confirmation**	Confirmation via Phone Confirmation via Email Confirmation via OTP
FR-4	**Payment Options**	Cash on Delivery Net Banking/UPI Credit/Debit/ATM Card
FR-5	**Product Delivery and Installation**	Door Step delivery Take away Free Installation and 1 year Warranty
FR-6	**Product Feedback**	Through Webpage Through Phone calls Through Google forms

4.2 **Non-Functional Requirements**

FR No.	**Non-Functional Requirement**	**Description**
NFR-1	**Usability**	Have a clear and self-explanatory manual. Easier to use. Easily accessible by everyone.
NFR-2	**Security**	Are inspected monthly by the Fire Alarm Technician. Inspected and tagged by a contractor annually.
NFR-3	**Reliability**	Hardware requires a regular checking and service. Software may be updated periodically. Immediate alert is provided in case of any system failure.
NFR-4	**Performance**	The equipment must have a good user interface It should have a minimal energy requirement It has to save lives of people and things.
NFR-5	**Availability**	All the features will be available when the user requires. It depends on the need of the user and the customization of the user has done.
NFR-6	**Scalability**	The product has to cover all the space of industry irrespective of the size or area.

5. PROJECT DESIGN

5.1 **Data Flow Diagrams**



5.2 Solution & Technical Architecture



5.3 User Stories

User Type	Functional Requirement	User Story Number	User Story/Task	Acceptance Criteria	Priority	Release
Customers (Mobile user, web user, care executive, Administrator)	Registration	USN - 1	As a user, I can register for the application by entering my mail, password, and confirming my password	I can access my account/ dashboard	High	Sprint - 1

		USN - 2	As a user, I will receive confirmation email once I have registered for the application	I can receive confirmation email & click confirm	High	Sprint - 1
	Dashboard	USN - 3	As a user, I can register for the application through internet	I can register & access the dashboard with Internet login	Low	Sprint - 2
		USN - 4	As a user, I can register for the application through Gmail	I can confirm the registration in Gmail	Medium	Sprint - 1
	Login	USN - 5	As a user, I can log into the application by entering email & password	I can login with my ID & password	High	Sprint - 1

6. PROJECT PLANNING & SCHEDULING

6.1 Sprint Planning & Estimation

S.No	Milestones	Activities	Timeline
1.	Literature Survey & Information Gathering	**Prepare Literature Survey for the selected project & gather necessary information.**	**29 Aug - 3rd Sept 2022**
2.	Empathy Map	**Prepare Empathy Map Canvas to capture the user gains and pains.**	**5 - 10th Sept 2022**
3.	Brainstorm	**Ideas are listed and top 3 ideas are prioritized.**	**12 - 17 Sept 2022**

4.	Proposed Solution	**Proposed solution document is prepared which includes novelty, feasibility of idea, social impact, scalability of solution.**	**19 - 24 Sept 2022**
5.	Problem Solution Fit	**Includes customer segments and customer constraints, the problem root cause and jobs to be done.**	**26 Sept - 01 Oct 2022**
6.	Solution Architecture	**From receiving data to notifying user are represented in architectural diagrams.**	**26 Sept - 01 Oct 2022**
7.	Customer Journey	**Prepare customer journey maps to understand user interactions and experiences with the applications.**	**3 - 8 Oct 2022**
8.	Functional Requirements	**Functional Requirements and non functional requirements like scalability, and accuracy are described.**	**10 - 15 Oct 2022**
9.	Data Flow Diagrams and User Stories	**Data flow diagrams and user stories are prepared and four sprint phases are described.**	**10 - 15 Oct 2022**
10.	Technology Architecture	**Technical flow graphs are created and the functions of technical stacks are defined.**	**10 - 15 Oct 2022**
11.	Prepare Milestones & Activities List	**Prepare the list for milestones & activities.**	**17 - 22 Oct 2022**
12.	Sprint Delivery Plan	**Prepare the sprint delivery plan of the project.**	**17 - 22 Oct 2022**
13.	Project Development – Delivery of Sprint 1,2,3& 4	**Develop and submit the developed code by testing it.**	**29 Oct 2022 - 19 Nov 2022**

6.2 Sprint Delivery Schedule

Product Backlog, Sprint Schedule, and Estimation

Sprint	Functional Requirement (Epic)	User Story Number	User Story / Task	Story Points	Priority	Team Members
Sprint-1	Registration (Mobile user)	USN-1	As a user, I can register for the application by entering my email, password, and confirming my password.	1	Low	Praveen Kumar B Monica Nancy V

Sprint-1	Login (Mobile user)	USN-2	As a user, I can log into the application by entering email & password	3	High	Sathyamoorthy M Jeevitha P
Sprint-2	Dashboard (Mobile user)	USN-3	By entering correct password, I could access the dashboard.	13	Medium	Praveen Kumar B Sathyamoorthy M
Sprint-3	Alert message (Mobile user)	USN-4	As a user, I can get alert messages regarding smoke and temperature parameters.	13	High	Jeevitha P Monica nancy V
Sprint-4	Data storage (Mobile user)	USN-5	As a user, I will able to store parameter values.	2	High	Praveen Kumar B Jeevitha P
Sprint-4	Checking (Mobile & web user)	USN-6	As a user I can Test the system performance, for an emergency case, it is deployed and I can use the system 24/7.	8	High	Monica Nancy V Sathyamoorthy M
Sprint-1	Login (web user)	USN-7	As a user, I can log into the application by entering email & password	13	High	Jeevitha P, Sathyamoothy M
Sprint-1	Dashboard (web user)	USN-8	I could access the dashboard.	3	Medium	Monica Nancy V Praveen Kumar
Sprint-3	Alert message (web user)	USN-9	As a user, I can get alert messages regarding smoke and temperature parameters.	5	High	Jeevitha P Praveen Kumar B
Sprint-4	Data Storage message (web user)	USN-10	As a user, I will able to store parameter values.	2	High	Sathyamoorthy M Monica Nancy V
Sprint-4	Checking (Mobile & web user)	USN-11	As a user, I can check whether the system correctly detects the fire and gas, and does it alerts the user, also whether the fire or smoke has been put down or not.	8	High	Jeevitha P Monica Nancy V

Project Tracker, Velocity & Burndown Chart:

Sprint	Total Story Points	Duration	Sprint Start Date	Sprint End Date (Planned)	Story Points Completed (as on Planned End Date)	Sprint Release Date (Actual)
Sprint-1	20	6 Days	24 Oct 2022	29 Oct 2022	20	29 Oct 2022
Sprint-2	20	6 Days	31 Oct 2022	05 Nov 2022	20	05 Nov 2022
Sprint-3	20	6 Days	07 Nov 2022	12 Nov 2022	20	12 Nov 2022
Sprint-4	20	6 Days	14 Nov 2022	19 Nov 2022	20	17 Nov 2022

Velocity:

Imagine we have a 10-day sprint duration, and the velocity of the team is 20 (points per sprint). Let's calculate the team's average velocity (AV) per iteration unit (story points per day)

$$AV = \frac{sprint\ duration}{velocity} = \frac{20}{10} = 2$$

Burndown Chart:

A burn down chart is a graphical representation of work left to do versus time. It is often used in agile software development methodologies such as Scrum. However, burn down charts can be applied to any project containing measurable progress over time.

https://www.visual-paradigm.com/scrum/scrum-burndown-chart/
https://www.atlassian.com/agile/tutorials/burndown-charts



Reference:

https://www.atlassian.com/agile/projectmanagement
https://www.atlassian.com/agile/tutorials/how-to-do-scrum-with-jira-software
https://www.atlassian.com/agile/tutorials/epics
https://www.atlassian.com/agile/tutorials/sprints
https://www.atlassian.com/agile/project-management/estimation
https://www.atlassian.com/agile/tutorials/burndown-charts

7. CODING AND SOLUTIONING (Explain the features added to the project along with code) :

CODE :

```
#include <time.h>
#include <WiFi.h>
#include <PubSubClient.h>

bool exhaust_fan_on = false;
bool sprinkler_on = false;
float temperature = 0;
int gas_level = 0;
int flame = 0;
String flame_status = "";
String accident_status = "";
String sprinkler_status = "";
void setup() {
Serial.begin(99900);
}
void loop() {
//setting a random seed
srand(time(0));
//initial variable
temperature = random(-20,125);
gas_level = random(0,1000);
int flamereading =
random(200,1024);
flame = map(flamereading,0,1024,0,2);
//set a flame status
Serial.print("Temperature : ");
Serial.println(temperature);

Serial.print("Gas_level : ");
Serial.println(gas_level);

Serial.print("Flame : ");
Serial.println(flame);
```

```
switch (flame) {
case 0:
flame_status = "No Fire";
Serial.println("Flame Status : "+flame_status);
break;
case 1:
flame_status = "Fire is Detected";
Serial.println("Flame Status : "+flame_status);
break;
}
//Gas Detection
if(gas_level > 100){
Serial.println("Gas Status : Gas leakage Detected");
}
else{
exhaust_fan_on = false;
Serial.println("Gas Status : No Gas leakage Detected");
}
//send the sprinkler status
if(flame){
sprinkler_status = "Sprinkler ON";
Serial.println("Sprinkler Status : "+sprinkler_status);
}
else{
sprinkler_status = "Sprinkler OFF";
Serial.println("Sprinkler Status : "+sprinkler_status);
}
//toggle the fan according to gas
if(gas_level > 100){
exhaust_fan_on = true;
Serial.println("Exhaust fan Status : Fan ON");
}
else{
exhaust_fan_on = false;
Serial.println("Exhaust fan Status : Fan OFF");
}
Serial.println("");
Serial.println("");
Serial.println(" ------------------------###############-------------
------");
Serial.println("");
Serial.println("");
delay(3000);
}
```

7.1 Feature 1

In the above code, we have added a feature that when the fire is detected in the industry, then the Sprinkler will be ON.

Solutioning of this feature:

7.2 Feature 2:

In the above code, we have added another feature is that when the “Gas leakage is detected” in the industry, then the Exhaust fan will be ON.

Solutioning of this feature:



8. TESTING :

8.1 Test Cases

s.no	Inputs	Outputs	Results
1	Temperature : 113.00 Gas_level : 945 Flame : 0	Flame Status : No Fire Gas Status : Gas leakage Detected Sprinkler Status : Sprinkler OFF Exhaust fan Status : Fan ON	Passed
2	Temperature : 122.00 Gas_level : 41 Flame : 0	Flame Status : No Fire Gas Status : No Gas leakage Detected Sprinkler Status : Sprinkler OFF Exhaust fan Status : Fan OFF	Passed
3	Temperature : 39.00 Gas_level : 639 Flame : 1	Flame Status : Fire is Detected Gas Status : Gas leakage Detected Sprinkler Status : Sprinkler ON Exhaust fan Status : Fan ON	Passed
4	Temperature : 40.00 Gas_level : 761 Flame : 0	Flame Status : No Fire Gas Status : Gas leakage Detected Sprinkler Status : Sprinkler OFF Exhaust fan Status : Fan ON	Passed
5	Temperature : 67.00 Gas_level : 21 Flame : 1	Flame Status : Fire is Detected Gas Status : No Gas leakage Detected Sprinkler Status : Sprinkler ON Exhaust fan Status : Fan OFF	Passed
6	Temperature : 107.00 Gas_level : 592 Flame : 1	Flame Status : Fire is Detected Gas Status : Gas leakage Detected Sprinkler Status : Sprinkler ON	Passed

		Exhaust fan Status : Fan ON	
7	Temperature : 8.00 Gas_level : 990 Flame : 0	Flame Status : No Fire Gas Status : Gas leakage Detected Sprinkler Status : Sprinkler OFF Exhaust fan Status : Fan ON	Passed
8	Temperature : 84.00 Gas_level : 532 Flame : 0	Flame Status : No Fire Gas Status : Gas leakage Detected Sprinkler Status : Sprinkler OFF Exhaust fan Status : Fan ON	Passed
9	Temperature : 123.00 Gas_level : 272 Flame : 1	Flame Status : Fire is Detected Gas Status : Gas leakage Detected Sprinkler Status : Sprinkler ON Exhaust fan Status : Fan ON	Passed
10	Temperature : 163.00 Gas_level : 94 Flame : 1	Flame Status : Fire is Detected Gas Status : No Gas leakage Detected Sprinkler Status : Sprinkler ON Exhaust fan Status : Fan OFF	Passed

9. RESULTS :


node-red-wppej-2022-11-08.eu-gb.mybluemix.net/ui/#!/0?socketid=vn2tmyJAnU2kOQHdAACK
Home
Temperature
Humidity
CO2 Percentage
Flame
Temperature
94
Degree Celcius
Humidity
27
%
CO2 Percentage
207
ppm
Flame
91
units


node-red-wppej-2022-11-08.eu-gb.mybluemix.net/red/#flow/5425640e3149be07
Node-RED
Deploy
Flow 1
debug
all nodes
all
Temperature
Flame
Gas
Humidity
IBM IoT
connected
firemanagement_db
MOTOR ON
IBM IoT
connected
MOTOR OFF
temp
Flame
Gas
Humidity
63
11/17/2022, 6:56:11 PM node: 132532cb33f52820
iot-2/type/ESP32_Controller/id/Sensor/evt/event_1/fmt/json : msg.payload : Object
{ Temperature: 124, Humidity: 25, CO2: 110, Flame: 76 }
11/17/2022, 6:56:11 PM node: 132532cb33f52820
iot-2/type/ESP32_Controller/id/Sensor/evt/event_1/fmt/json : msg.payload : number
124
11/17/2022, 6:56:11 PM node: 132532cb33f52820
iot-2/type/ESP32_Controller/id/Sensor/evt/event_1/fmt/json : msg.payload : number
25
11/17/2022, 6:56:11 PM node: 132532cb33f52820
iot-2/type/ESP32_Controller/id/Sensor/evt/event_1/fmt/json : msg.payload : number
110
11/17/2022, 6:56:11 PM node: 132532cb33f52820
iot-2/type/ESP32_Controller/id/Sensor/evt/event_1/fmt/json : msg.payload : number
76
11/17/2022, 6:56:13 PM node: 132532cb33f52820
msg.payload : Object
{ command: "Motor on" }
11/17/2022, 6:56:20 PM node: 132532cb33f52820

10. ADVANTAGES :

The main advantage and function of a fire alarm system is to ensure ultimate safety. The system warn and keep people safe and reduce the amount of destruction to a building. Proactively gave protection to secure business processes and valuable goods from fires. Protect from multiple hazards with just one system.

DISADVANTAGES

The system is essentially useless if the batteries aren't charged, since it won't work properly. It must be borne in mind that a major disadvantage of heat detectors is the fact they rely on heat to actuate. For large buildings, they can be expensive to install because of the extensive amounts of wire that are necessary to accurately monitor initiating devices.

11. CONCLUSION

It is important to implement the fire protection system in places like industries, colleges and so on as a part of building safety as well as prevention of life loss.This system recommends the use of fire alarms system,sprinkler system and smoke control system, these are helpful in notify the actions like fire and smoke conditions. It can also helps to slow down the growth of fire. The followence of guidelines make the place safe to work and in case of fire the building will include protection that will results in minimum loss.

12. FUTURE SCOPE

There haven’t really been any momentous industry standards which will keep up with technological advances a lot faster, those responsible for benefit fire detection manufacturers and the marketplace. Interconnection between multiple system has been implemented in upcoming period. Different Gas Sensor can be used to identify the accuracy of the gas while fire occurs. Making the Devices more and more capable, and their application, so that they all are evolving to connect to the internet and cooperate with other devices. The future will be with the detectors. Detector will be more of a sensor, with the detection capability for the products of combustion, such as carbon monoxide, carbon dioxide, sulfur dioxide, nitrogen oxides in addition to heat and and other subordinates matters.

13. APPENDIX

Source Code :

```
import wiotp.sdk.device
import time
import random
```

```
myConfig = {
    "identity": {
        "orgId": "0bm892",
        "typeId": "NodeMcu",
        "deviceId":"1234"
    },
    "auth": {
        "token": "12345678"
    }
}

def myCommandCallback(cmd):
    print("Message received from IBM IoT Platform: %s" % cmd.data['command'])
    m=cmd.data['command']

client = wiotp.sdk.device.DeviceClient(config=myConfig, logHandlers=None)
client.connect()

while True:
    temperature=random.randint(-20,125)
    humidity=random.randint(0,100)
    gas_level =random.randint(0,500)
    flame=random.randint(0,200)

    if (flame>80):
        print("Sprinkler ON")
    else:
        print("Sprinkler OFF")

    if (gas_level>100):
        print("Exhaust Fan ON")
    else:
        print("Exhaust Fan OFF")

    myData={'temperature':temperature, 'humidity':humidity, 'gas_level':
gas_level,'flame':flame}
    client.publishEvent(eventId="status", msgFormat="json", data=myData, qos=0,
onPublish=None)
    print("Published data Successfully: %s", myData)
    client.commandCallback = myCommandCallback
    time.sleep(2)
client.disconnect()
```

OUTPUT :


0bm892.internetofthings.ibmcloud.com/dashboard/devices/browse
IBM Watson IoT Platform
praveenkumarraj111@gmail.com
ID: 0bm892
Browse
Action
Device Types
Interfaces
Add Device
Identity
Device Information
Recent Events
State
Logs
The recent events listed show the live stream of data that is coming and going from this device.
Event
Value
Format
Last Received
status
{"temperature":87,"humidity":9,"gas_level":418,...
json
a few seconds ago
status
{"temperature":-5,"humidity":73,"gas_level":335...
json
a few seconds ago
status
{"temperature":72,"humidity":68,"gas_level":42...
json
a few seconds ago
status
{"temperature":87,"humidity":63,"gas_level":11...
json
a few seconds ago
status
{"temperature":44,"humidity":14,"gas_level":49...
json
a few seconds ago
1 Simulation running



Github Link :-

https://github.com/IBM-EPBL/IBM-Project-20918-1659766664