S.Valarmathi Assignment -4

Question-1: Write code and connections in wokwi for ultrasonic sensor. Whenever distance is less than 100 cms send “alert” to IBM cloud and display in device recent events.

Solution:

```
#define ECHO_PIN 2
#define TRIG_PIN 3
#define organization =”46x7xk”
#define deviceType=” arduino”
#define deviceId =”0504”
#define authMethod ="use-token-auth"
#define authToken =”dv*uK8y__X4O5m!V(K”

void setup() {
  // put your setup code here, to run once:
  Serial.begin(9600);
  pinMode(TRIG_PIN,OUTPUT);
  pinMode(ECHO_PIN, INPUT);
}
float readDistanceCM() {
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
```

```
int duration = pulseIn(ECHO_PIN, HIGH);
return duration * 0.034 / 2;



}

void loop() {
  // put your main code here, to run repeatedly:
  float distance = readDistanceCM();
  if(distance <= 100)
  {
    Serial.println("person detected ");
  }
  else{
    Serial.print("Measured distance: ");
    Serial.println(readDistanceCM());
  }
  delay(1000);




}
```


WOKWI
SAVE
SHARE
Docs
sketch.ino
diagram.json
Library Manager
Simulation
valarmathis202@gmail.com
Discord
My projects
The Club
Feature Roadmap
Language
Logout
#define ECHO_PIN 2
#define TRIG_PIN 3
#define organization "46x7xk"
#define deviceType=" arduino"
#define deviceId ="0504"
#define authMethod ="use-token-auth"
#define authToken ="dv*uK8y__X4OSm!V(K"
void setup() {
// put your setup code here, to run once:
Serial.begin(9600);
pinMode(TRIG_PIN,OUTPUT);
pinMode(ECHO_PIN, INPUT);
}
float readDistanceCM() {
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
int duration = pulseIn(ECHO_PIN, HIGH);
return duration * 0.034 / 2;
}
void loop() {
// put your main code here, to run repeatedly:
float distance = readDistanceCM();
if(distance <= 100)
{
Serial.println("person detected ");
}
else{
Serial.print("Measured distance: ");
Serial.println(readDistanceCM());
}
delay(1000);
}

Output:


WOKWI
SAVE
SHARE
Docs
sketch.ino
diagram.json
Library Manager
Simulation
00:07.714
72%
#define ECHO_PIN 2
#define TRIG_PIN 3
#define organization "46x7xk"
#define deviceType=" arduino"
#define deviceId ="0504"
#define authMethod ="use-token-auth"
#define authToken ="dv*uK8y__X4OSm!V(K"
void setup() {
// put your setup code here, to run once:
Serial.begin(9600);
pinMode(TRIG_PIN,OUTPUT);
pinMode(ECHO_PIN, INPUT);
}
float readDistanceCM() {
digitalWrite(TRIG_PIN, LOW);
delayMicroseconds(2);
digitalWrite(TRIG_PIN, HIGH);
delayMicroseconds(10);
digitalWrite(TRIG_PIN, LOW);
int duration = pulseIn(ECHO_PIN, HIGH);
return duration * 0.034 / 2;
}
void loop() {
// put your main code here, to run repeatedly:
float distance = readDistanceCM();
if(distance <= 100)
{
Serial.println("person detected ");
}
else{
Serial.print("Measured distance: ");
Serial.println(readDistanceCM());
}
delay(1000);
}
Measured distance: 395.27
Measured distance: 395.25
Measured distance: 395.27
Measured distance: 395.25
Measured distance: 395.25
Measured distance: 395.25
Measured distance: 395.25

Wokwi Link: https://wokwi.com/projects/347484942224065107

IBM CLOUD

Device Recent Events