# **ASSIGNMENT – 4**

# Ultrasonic sensor simulation in Wokwi

## **QUESTIONS:**

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events

#### **CODE:**

```
#include <WiFi.h>
#include
<PubSubClient.h>
void callback(char* subscribetopic, byte*
payload, unsigned int payloadLength);
//----credentials of IBM Accounts-----
#define ORG "kotoq5"//IBM ORGANITION ID
#define DEVICE TYPE "ESP32"//Device type mentioned in ibm
watson IOT Platform
#define DEVICE ID "12345"//Device ID mentioned in ibm watson
IOT Platform #define TOKEN "12345678" //Token
String data3;
char server[] = ORG
".messaging.internetofthings.ibmcloud.com";
char publishTopic[] = "iot-2/evt/Data/fmt/json";
char subscribetopic[] =
"iot-2/cmd/test/fmt/String"; char authMethod[]
```

```
= "use-token-auth";
char token[] =
TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server, 1883, callback
,wifiClient); const int trigPin =
5; const int echoPin = 18;
#define SOUND SPEED
0.034 long
duration; float
distance:
void
setup()
Serial.be
gin(11520
0);
pinMode(
trigPin,
OUTPUT
);
pinMode(
echoPin,
INPUT);
wificonne
ct();
mqttconn
ect();
void loop()
digitalWrite(trigPin, LOW);
delayMicroseconds(2);
digitalWrite(trigPin, HIGH);
delayMicroseconds(10);
digitalWrite(trigPin, LOW);
duration = pulseIn(echoPin,
HIGH);
distance = duration *
SOUND SPEED/2;
Serial.print("Distance (cm): ");
Serial.println(distance);
```

```
if(distance<100)
Serial.println("ALERT
!!"); delay(1000);
PublishData(distance)
; delay(1000);
if
(!client.loop()
mqttconnect();
delay(1000);
void
PublishData(float
dist) { mqttconnect();
String payload =
"{\"Distance\":"; payload
+= dist;
payload += ",\"ALERT!!\":""\"Distance less
than 100cms\""; payload += "}";
Serial.print("Sending payload: ");
Serial.println(payload);
if (client.publish(publishTopic, (char*) payload.c str())) {
Serial.println("Publish ok");
} else {
Serial.println("Publish failed");
void mqttconnect() {
(!client.connected())
Serial.print("Reconnecting client to ");
Serial.println(server);
while (!!!client.connect(clientId, authMethod, token)) {
Serial print
(".");
```


```
delay(500);
}
```

```
initManagedDevice();
Serial.println();
void wificonnect()
Serial.println();
Serial.print("Connecting to ");
WiFi.begin("Wokwi-GUEST"
, "", 6);
while (WiFi.status() !=
WL CONNECTED) {
delay(500);
Serial.print(".");
Serial.println("");
Serial.println("WiFi
connected");
Serial.println("IP address: ");
Serial.println(WiFi.localIP())
void initManagedDevice() {
if (client.subscribe(subscribetopic)) {
Serial.println((subscribetopic));
Serial.println("subscribe to cmd
OK");
} else {
Serial.println("subscribe to cmd FAILED");
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic);
for (int i = 0; i < payloadLength; i++) {
//Serial.print((char)payload
[i]); data3 +=
(char)payload[i];
```

```
Serial.println("data:
"+ data3); data3="";
}
```

## .json CODE:

## **CIRCUIT DIAGRAM:**



# Wokwi simulation link:

https://wokwi.com/projects/347020612138435155

## **WOKWI OUTPUT:**

```
Connecting to ....
WiFi connected
IP address:
10.10.0.2
Reconnecting client to ytluse.messaging.internetofthings.ibmcloud.com
iot-2/cmd/test/fmt/String
subscribe to cmd OK

Distance (cm): 399.92
Distance (cm): 399.96
Distance (cm): 399.94
Distance (cm): 399.98
Distance (cm): 399.94
Distance (cm): 399.94
Distance (cm): 399.92
Distance (cm): 399.92
```

# **IBM CLOUD OUTPUT:**

