


ASSIGNMENT - 1

HOME AUTOMATION

NAME : KAVIYA.S

ROLL NO: 113119UG03046



CODE

```
#include <Servo.h>
int dist = 0;
long readUltrasonicDistance(int triggerPin, int echoPin)
{
    pinMode(triggerPin, OUTPUT); // Clear the trigger
    digitalWrite(triggerPin, LOW);
    delayMicroseconds(2);
    // Sets the trigger pin to HIGH state for 10 microseconds
    digitalWrite(triggerPin, HIGH);
    delayMicroseconds(10);
    digitalWrite(triggerPin, LOW);
    pinMode(echoPin, INPUT);
    // Reads the echo pin, and returns the sound wave travel time in
    microseconds
    return pulseIn(echoPin, HIGH);
}
```

```
Servo servo_8;
void setup()
{
  servo_8.attach(8, 500, 2500);
  pinMode(2, INPUT);
  pinMode(12, OUTPUT);
  pinMode(A0, INPUT);
  pinMode(9, OUTPUT);
}

void loop()
{
  dist = 0.01723 * readUltrasonicDistance(7, 7);
  if (dist <= 100) {
    servo_8.write(90);
    delay(1000); // Wait for 1000 millisecond(s)
  } else {
    servo_8.write(0);
    delay(1000); // Wait for 1000 millisecond(s)
  }
  if (digitalRead(2) == 1) {
    digitalWrite(12, HIGH);
    delay(1000); // Wait for 1000 millisecond(s)
  } else {
    digitalWrite(12, LOW);
    delay(1000); // Wait for 1000 millisecond(s)
  }
}
```

```
if (analogRead(A0) > 200) {  
  digitalWrite(9, HIGH);  
  delay(1000); // Wait for 1000 millisecond(s)  
} else {  
  digitalWrite(9, LOW);  
  delay(1000); // Wait for 1000 millisecond(s)  
}  
}
```

<https://www.tinkercad.com/things/9NJOjICPvoj-homeautomation-kaviyas-asgt-1/editel>