SRI SAIRAM ENGINEERING COLLEGE

DEPARTMENT OF ELECTRONICS AND COMMUNICATION ENGINEERING

SMART FARMER – IoT ENABLED SMART FARMING APPLICATION

IBM NALAIYATHIRAN

SPRINT-4

TITLE	Smart Farmer – IoT enabled Smart Farming Application
DOMAIN NAME	Internet of Things
TEAM ID	PNT2022TMID04114
TEAM LEADER	PADHMASHREE.S
TEAM MEMBERS	JYOTI PAL HEMA MALINI.S HEMALATHA.G
MENTOR NAME	K. SUBHASHINI

5.5 Receiving commands from IBM cloud using Python program

```python
import time import
sys
import ibmiotf.application
import ibmiotf.device import
random
```

#Provide your IBM Watson Device

```python
Credentialsorganization = "157uf3"
deviceType = "abcd" deviceId = "7654321"
authMethod = "token" authToken =
"87654321"
```

Initialize GPIO

```python
def  myCommandCallback(cmd):    print("Command
received: %s" % cmd.data['command'])
status=cmd.data['command']    if status=="motoron":
print ("motor is on")    elif status == "motoroff":    print
("motor is off")    else :
    print ("please send proper command")

try:
        deviceOptions = {"org": organization, "type": deviceType, "id": deviceId,
"auth-method": authMethod, "auth-token": authToken}
deviceCli = ibmiotf.device.Client(deviceOptions)
        #...........................................
```

```python
except Exception as e:
        print("Caught exception connecting device: %s" %
str(e))sys.exit()
# Connect and send a datapoint "hello" with value "world" into the cloud as an
event of type "greeting" 10 times deviceCli.connect()


while True:
    #Get Sensor Data from
DHT11
temp=random.randint(90,110)
Humid=random.randint(60,100)
Mois=random. Randint(20,120)
   data = { 'temp' : temp, 'Humid': Humid ,
'Mois': Mois}
    #print data        def
myOnPublishCallback(
):
        print ("Published Temperature = %s C" % temp, "Humidity = %s %%"
%Humid, "Moisture =%s deg c" % Mois "to IBM Watson")
      success = deviceCli.publishEvent("IoTSensor", "json", data,
qos=0,on_publish=myOnPublishCallback)         if not success:
      print("Not connected to IoTF")
time.sleep(10)
    deviceCli.commandCallback = myCommandCallback #
Disconnect the device and application from the cloud
deviceCli.disconnect()
```

```python
import time
import sys
import ibmiotf.application
import ibmiotf.device
import random


#Provide your IBM Watson Device Credentials
organization = "157uf3"
deviceType = "abcd"
deviceId = "7654321"
authMethod = "token"
authToken = "87654321"

# Initialize GPIO
def myCommandCallback(cmd):
    print("Command received: %s" % cmd.data['command'])
    status=cmd.data['command']
    if status=="motoron":
        print ("motor is on")
    elif status == "motoroff":
        print ("motor is off")
    else :
        print ("please send proper command")

try:
        deviceOptions = {"org": organization, "type": deviceType, "id": deviceId, "auth-method": authMe
        deviceCli = ibmiotf.device.Client(deviceOptions)
        #...........................................
```

```
Python 3.7.0 (v3.7.0:1bf9cc5093, Jun 27 2018, 04:59:51) [MSC v.1914 64 bit (AMD6
4)] on win32
Type "copyright", "credits" or "license()" for more information.
>>>
======== RESTART: C:\Users\ELCOT\Downloads\ibmiotpublishsubscribe.py ========
2022-11-07 20:01:24,074   ibmiotf.device.Client      INFO    Connected successfu
lly: d:157uf3:abcd:7654321
Published Moisture = 90 deg C Temperature = 96 C Humidity = 76 % to IBM Watson
Published Moisture = 102 deg C Temperature = 110 C Humidity = 68 % to IBM Watson
Published Moisture = 45 deg C Temperature = 99 C Humidity = 100 % to IBM Watson
Command received: motoron
motor is on
Published Moisture = 77 deg C Temperature = 91 C Humidity = 85 % to IBM Watson
Published Moisture = 73 deg C Temperature = 94 C Humidity = 86 % to IBM Watson
Command received: motoroff
motor is off
Published Moisture = 101 deg C Temperature = 104 C Humidity = 87 % to IBM Watson
```

6. Flow Chart

7. Observations & Results

Measured Data

Moisture : 59

Temperature(c): 90

Humidity(%): 85

Switchboard

Motor on   **Motor off**

Farming Measure Data

Temperature

Humidity

91
%

0   100

Moisture

Switchboard

MOTOR SWITCH ON

MOTOR SWITCH OFF

8. Advantages & Disadvantages Advantages:

• Farms can be monitored and controlled remotely.

• Increase in convenience to farmers.

• Less labor cost.

• Better standards of living.

Disadvantages:

• Lack of internet/connectivity issues.

• Added cost of internet and internet gateway infrastructure.

• Farmers wanted to adapt the use of Mobile App.

9.Conclusion

Thus the objective of the project to implement an IOT system in order to help farmers to control and monitor their farms has been implemented successfully.